

Using the doRNG package

doRNG package – Version 1.3

Renaud Gaujoux

May 22, 2012

Contents

Introduction	1	4 Reproducible sets of loops	8
1 The %dorn% operator	3	5 Performance overhead	9
1.1 How it works	3	6 Known issues	10
1.2 Seeding computations	4	Session information	10
2 Parallel environment independence	7	References	11
3 Reproducible %dopar% loops	8		

Introduction

Research reproducibility is an issue of concern, e.g. in bioinformatics [4, 9, 5]. Some analyses require multiple independent runs to be performed, or are amenable to a split-and-reduce scheme. For example, some optimisation algorithms are run multiple times from different random starting points, and the result that achieves the least approximation error is selected. The *foreach* package¹ [2] provides a very convenient way to perform parallel computations, with different parallel environments such as MPI or Redis, using a transparent loop-like syntax:

```
# load and register parallel backend for multicore computations
library(doParallel)

## Loading required package: foreach
## Loading required package: iterators
## Loading required package: parallel
```

¹<http://cran.r-project.org/package=foreach>

```

c1 <- makeCluster(2)
registerDoParallel(c1)

# perform 5 tasks in parallel
x <- foreach(i = 1:5) %dopar% {
  i + runif(1)
}
unlist(x)

## [1] 1.514 2.775 3.388 4.832 5.991

```

For each parallel environment a *backend* is implemented as a specialised `%dopar%` operator, which performs the setup and pre/post-processing specifically required by the environment (e.g. export of variable to each worker). The `foreach` function and the `%dopar%` operator handle the generic parameter dispatch when the task are split between worker processes, as well as the reduce step – when the results are returned to the master worker.

When stochastic computations are involved, special random number generators must be used to ensure that the separate computations are indeed statistically independent – unless otherwise wanted – and that the loop is reproducible. In particular, standard `%dopar%` loops are not reproducible:

```

# with standard %dopar%: foreach loops are not reproducible
set.seed(123)
res <- foreach(i=1:5) %dopar% { runif(3) }
set.seed(123)
res2 <- foreach(i=1:5) %dopar% { runif(3) }
identical(res, res2)

## [1] FALSE

```

A random number generator commonly used to achieve reproducibility is the combined multiple-recursive generator from L’Ecuyer [6]. This generator can generate independent random streams, from a 6-length numeric seed. The idea is then to generate a sequence of random stream of the same length as the number of iteration (i.e. tasks) and use a different stream when computing each one of them.

The *doRNG* package² [3] provides convenient ways to implement reproducible parallel `foreach` loops, independently of the parallel backend used to perform the computation. We illustrate its use, showing how non-reproducible loops can be made reproducible, even when tasks are not scheduled in the same way in two separate set of runs, e.g. when the workers do not get to compute the same number of tasks or the number of workers is different. The package has been tested with the *doParallel*³ and *doMPI*⁴ packages [10, 1], but should work with other backends such as provided by the *doRedis* package⁵ [7].

²<http://cran.r-project.org/package=doRNG>

³<http://cran.r-project.org/package=doParallel>

⁴<http://cran.r-project.org/package=doMPI>

⁵<http://cran.r-project.org/package=doRedis>

1 The %dorng% operator

The *doRNG* package defines a new generic operator, `%dorng%`, to be used with `foreach` loops, instead of the standard `%dopar%`. Loops that use this operator are *de facto* reproducible.

```
# load the doRNG package
library(doRNG)

## Loading required package: methods

# using %dorng%: loops _are_ reproducible
set.seed(123)
res <- foreach(i=1:5) %dorng% { runif(3) }
set.seed(123)
res2 <- foreach(i=1:5) %dorng% { runif(3) }
identical(res, res2)

## [1] TRUE
```

1.1 How it works

For a loop with N iterations, the `%dorng%` operator internally performs the following tasks:

1. generate a sequence of random seeds $(S_i)_{1 \leq i \leq N}$ for the R random number generator "L'Ecuyer-CMRG" [6], using the function `nextRNGStream` from the *parallel* package⁶ [8], which ensure the different RNG streams are statistically independent;
2. modify the loop's R expression so that the random number generator is set to "L'Ecuyer-CMRG" at the beginning of each iteration, and is seeded with consecutive seeds in (S_n) : iteration i is seeded with S_i , $1 \leq i \leq N$;
3. call the standard `%dopar%` operator, which in turn calls the relevant (i.e. registered) `foreach` parallel backend;
4. store the whole sequence of random seeds as an attribute in the result object:

```
attr(res, "rng")

## [[1]]
## [1]      407      642048078      81368183 -2093158836      506506973      1421492218 -1906381517
##
## [[2]]
## [1]      407     1340772676 -1389246211    -999053355    -953732024     1888105061     2010658538
##
```

⁶<http://cran.r-project.org/package=parallel>

```
## [[3]]
## [1]          407 -1318496690 -948316584   683309249 -990823268 -1895972179 1275914972
##
## [[4]]
## [1]          407   524763474 1715794407 1887051490 -1833874283 494155061 -1221391662
##
## [[5]]
## [1]          407 -1816009034 -580124020 1603250023 817712173 190009158 -706984535
##
```

1.2 Seeding computations

Sequences of random streams for "L'Ecuyer-CMRG" are generated using a 6-length integer seed:

```
nextRNGstream(1:6)

## Error: could not find function "nextRNGstream"
```

However, the `%dorng%` operator provides alternative – convenient – ways of seeding reproducible loops.

set.seed: as shown above, calling `set.seed` before the loop ensure reproducibility of the results, using a single integer as a seed. The actual 6-length seed is then classically within the call to `RNGkind("L'Ecuyer-CMRG")`.

.options.RNG with single integer: the `%dorng%` operator implements an option that can be passed in the `foreach` statement, with the same arguments accepted by `set.seed`:

```
# use a single numeric as a seed
s <- foreach(i = 1:5, .options.RNG = 123) %dorng% {
  runif(3)
}
identical(s, res)

## [1] TRUE

## Pass the Normal RNG kind to use within the loop results are identical if not
## using the
## Normal kind in the loop
optsN <- list(123, normal.kind = "Ahrens")
resN.U <- foreach(i = 1:5, .options.RNG = optsN) %dorng% {
  runif(3)
}
identical(resN.U[1:5], res[1:5])
```

```
## [1] TRUE

# Results are different if the Normal kind is used and is not the same
resN <- foreach(i = 1:5, .options.RNG = 123) %dorng% {
  rnorm(3)
}
resN1 <- foreach(i = 1:5, .options.RNG = optsN) %dorng% {
  rnorm(3)
}
resN2 <- foreach(i = 1:5, .options.RNG = optsN) %dorng% {
  rnorm(3)
}
identical(resN[1:5], resN1[1:5])

## [1] FALSE

identical(resN1[1:5], resN2[1:5])

## [1] TRUE
```

.options.RNG with 6-length: the actual 6-length integer seed used for the first RNG stream may be passed via `options.RNG`:

```
# use a 6-length numeric
s <- foreach(i = 1:5, .options.RNG = 1:6) %dorng% {
  runif(3)
}
attr(s, "rng")[1:3]

## [[1]]
## [1] 407 1 2 3 4 5 6
##
## [[2]]
## [1] 407 -447371532 542750874 -935969228 -269326340 701604884 -1748056907
##
## [[3]]
## [1] 407 311773008 -1393648596 433058656 -545474683 2059732357 994549473
##
```

.options.RNG with 7-length: a 7-length integer seed may also be passed via `options.RNG`, which is useful to seed a loop with the value of `.Random.seed` as used in some iteration of another loop⁷:

⁷Note that the RNG kind is then always required to be the "L'Ecuyer-CMRG", i.e. the first element of the seed must have unit 7 (e.g. 407 or 107).

```

# use a 7-length numeric, used as first value for .Random.seed
seed <- attr(res, "rng")[[2]]
s <- foreach(i = 1:5, .options.RNG = seed) %dorng% {
  runif(3)
}
identical(s[1:4], res[2:5])

## [1] TRUE

```

.options.RNG with complete sequence of seeds: the complete description of the sequence of seeds to be used may be passed via `options.RNG`, as a list or a matrix with the seeds in columns. This is useful to seed a loop exactly as desired, e.g. using an RNG other than "L'Ecuyer-CMRG", or using different RNG kinds in each iteration, which probably have different seed length, in order to compare their stochastic properties. It also allows to reproduce `%dorng%` loops without knowing their seeding details:

```

# reproduce previous %dorng% loop
s <- foreach(i = 1:5, .options.RNG = res) %dorng% {
  runif(3)
}
identical(s, res)

## [1] TRUE

## use completely custom sequence of seeds (e.g. using RNG
'Marsaglia-Multicarry') as a
## matrix
seedM <- rbind(rep(401, 5), mapply(rep, 1:5, 2))
seedM

##      [,1] [,2] [,3] [,4] [,5]
## [1,] 401  401  401  401  401
## [2,]   1    2    3    4    5
## [3,]   1    2    3    4    5

sM <- foreach(i = 1:5, .options.RNG = seedM) %dorng% {
  runif(3)
}
# same seeds passed as a list
seedL <- lapply(seq(ncol(seedM)), function(i) seedM[, i])
sL <- foreach(i = 1:5, .options.RNG = seedL) %dorng% {
  runif(3)
}
identical(sL, sM)

## [1] TRUE

```

2 Parallel environment independence

An important feature of `%dorng%` loops is that their result is independent of the underlying parallel physical settings. Two separate runs seeded with the same value will always produce the same results. Whether they use the same number of worker processes, parallel backend or task scheduling does not influence the final result. This also applies to computations performed sequentially with the `doSEQ` backend. The following code illustrates this feature using 2 or 3 workers.

```
# define a stochastic task to perform
task <- function() c(pid=Sys.getpid(), val=runif(1))

# using the previously registered cluster with 2 workers
set.seed(123)
res_2workers <- foreach(i=1:5, .combine=rbind) %dorng% {
  task()
}
# stop cluster
stopCluster(cl)

# Sequential computation
registerDoSEQ()
set.seed(123)
res_seq <- foreach(i=1:5, .combine=rbind) %dorng% {
  task()
}
#

# Using 3 workers
cl <- makeCluster(3)
registerDoParallel(cl)
set.seed(123)
res_3workers <- foreach(i=1:5, .combine=rbind) %dorng% {
  task()
}

# task schedule is different
pid <- rbind(res1=res_seq[,1], res_2workers[,1], res2=res_3workers[,1])
storage.mode(pid) <- 'integer'
pid

##      result.1 result.2 result.3 result.4 result.5
## res1    17752    17752    17752    17752    17752
##          17764    17773    17764    17773    17773
## res2    17786    17795    17805    17786    17805

# results are identical
identical(res_seq[,2], res_2workers[,2]) && identical(res_2workers[,2],
res_3workers[,2])

## [1] TRUE
```

3 Reproducible %dopar% loops

The *doRNG* package also provides a non-invasive way to convert %dopar% loops into reproducible loops, i.e. without changing their actual definition. It is useful to quickly ensure the reproducibility of existing code or functions whose definition is not accessible (e.g. from other packages). This is achieved by registering the doRNG backend:

```
registerDoRNG(123)
res_dopar <- foreach(i = 1:5) %dopar% {
  runif(3)
}
identical(res_dopar, res)

## [1] TRUE

attr(res_dopar, "rng")

## [[1]]
## [1]          407    642048078    81368183 -2093158836    506506973    1421492218 -1906381517
##
## [[2]]
## [1]          407   1340772676 -1389246211   -999053355   -953732024   1888105061   2010658538
##
## [[3]]
## [1]          407 -1318496690   -948316584    683309249   -990823268 -1895972179   1275914972
##
## [[4]]
## [1]          407    524763474   1715794407   1887051490 -1833874283    494155061 -1221391662
##
## [[5]]
## [1]          407 -1816009034   -580124020   1603250023    817712173    190009158  -706984535
##
```

4 Reproducible sets of loops

Sequences of multiple loops are reproducible, whether using the %dorng% operator or the registered doRNG backend:

```
set.seed(456)
s1 <- foreach(i=1:5) %dorng% { runif(3) }
s2 <- foreach(i=1:5) %dorng% { runif(3) }
# the two loops do not use the same streams: different results
identical(s1, s2)

## [1] FALSE
```



```

# but the sequence of loops is reproducible as a whole
set.seed(456)
r1 <- foreach(i=1:5) %dorng% { runif(3) }
r2 <- foreach(i=1:5) %dorng% { runif(3) }
identical(r1, s1) && identical(r2, s2)

## [1] TRUE

# one can equivalently register the doRNG backend and use %dopar%
registerDoRNG(456)
r1 <- foreach(i=1:5) %dopar% { runif(3) }
r2 <- foreach(i=1:5) %dopar% { runif(3) }
identical(r1, s1) && identical(r2, s2)

## [1] TRUE

```

5 Performance overhead

The extra setup performed by the `%dorng%` operator leads to a slight performance overhead, which might be significant for very quick computations, but should not be a problem for realistic computations. The benchmarks below show that a `%dorng%` loop may take up to two seconds more than the equivalent `%dopar%` loop, which is not significant in practice, where parallelised computations typically take several minutes.

```

# load rbenchmark
library(rbenchmark)

# comparison is done on sequential computations
registerDoSEQ()
rPar <- function(n, s = 0) {
  foreach(i = 1:n) %dopar% {
    Sys.sleep(s)
  }
}
rRNG <- function(n, s = 0) {
  foreach(i = 1:n) %dorng% {
    Sys.sleep(s)
  }
}

# run benchmark
cmp <- benchmark(rPar(10), rRNG(10), rPar(50), rRNG(50), rPar(100), rRNG(100), rPar(10,
  0.1), rRNG(10, 0.1), rPar(100, 0.01), rRNG(100, 0.01), replications = 50)
# order by increasing elapsed time
cmp[order(cmp$elapsed), ]

```

##	test	replications	elapsed	relative	user.self	sys.self	user.child	sys.child
## 1	rPar(10)	50	0.563	1.000	0.57	0.00	0	0
## 2	rRNG(10)	50	0.865	1.536	0.85	0.02	0	0
## 3	rPar(50)	50	1.661	2.950	1.66	0.00	0	0
## 4	rRNG(50)	50	2.672	4.746	2.66	0.02	0	0
## 5	rPar(100)	50	3.099	5.504	3.09	0.00	0	0
## 6	rRNG(100)	50	4.994	8.870	4.95	0.04	0	0
## 7	rPar(10, 0.1)	50	50.743	90.130	0.69	0.00	0	0
## 8	rRNG(10, 0.1)	50	51.178	90.902	1.10	0.02	0	0
## 9	rPar(100, 0.01)	50	54.309	96.464	3.96	0.04	0	0
## 10	rRNG(100, 0.01)	50	56.405	100.187	6.01	0.06	0	0

6 Known issues

- Nested and/or conditional foreach loops using the operator `%:%` are not currently not supported.
- An error is thrown in `doRNG < 1.3`, when the package `iterators` was not loaded, when used with `foreach >= 1.4`.

Cleanup

```
stopCluster(cl)
```

Session information

```
R version 2.15.0 (2012-03-30)
Platform: x86_64-pc-linux-gnu (64-bit)

locale:
 [1] LC_CTYPE=en_ZA.UTF-8      LC_NUMERIC=C              LC_TIME=en_ZA.UTF-8
 [4] LC_COLLATE=en_ZA.UTF-8   LC_MONETARY=en_ZA.UTF-8  LC_MESSAGES=en_US.UTF-8
 [7] LC_PAPER=C               LC_NAME=C                 LC_ADDRESS=C
[10] LC_TELEPHONE=C           LC_MEASUREMENT=en_ZA.UTF-8 LC_IDENTIFICATION=C

attached base packages:
[1] methods    parallel  stats      graphics  grDevices  utils      datasets  base

other attached packages:
[1] doRNG_1.3          doParallel_1.0.1 iterators_1.0.6 foreach_1.4.0 knitr_0.5

loaded via a namespace (and not attached):
```

[1]	codetools_0.2-8	compiler_2.15.0	digest_0.5.2	evaluate_0.4.2	formatR_0.4
[6]	highlight_0.3.1	parser_0.0-14	plyr_1.7.1	Rcpp_0.9.10	stringr_0.6
[11]	tools_2.15.0				

References

- [1] Revolution Analytics. *doParallel: Foreach parallel adaptor for the parallel package*. R package version 1.0.1. 2012. URL: <http://CRAN.R-project.org/package=doParallel>.
- [2] Revolution Analytics. *foreach: Foreach looping construct for R*. R package version 1.4.0. 2012. URL: <http://CRAN.R-project.org/package=foreach>.
- [3] Renaud Gaujoux. *doRNG: Generic Reproducible Parallel Backend for foreach Loops*. R package version 1.3. 2012.
- [4] Torsten Hothorn and Friedrich Leisch. “Case studies in reproducibility.” In: *Briefings in bioinformatics* (Jan. 2011). ISSN: 1477-4054. DOI: [10.1093/bib/bbq084](https://doi.org/10.1093/bib/bbq084). URL: <http://www.ncbi.nlm.nih.gov/pubmed/21278369>.
- [5] John P A Ioannidis et al. “The reproducibility of lists of differentially expressed genes in microarray studies”. In: *Nature Genetics* 41.2 (2008), pp. 149–155. ISSN: 10614036. DOI: [10.1038/ng.295](https://doi.org/10.1038/ng.295). URL: <http://www.nature.com/doifinder/10.1038/ng.295>.
- [6] Pierre L’Ecuyer. “Good parameters and implementations for combined multiple recursive random number generators”. In: *Operations Research* 47.1 (1999). URL: <http://www.jstor.org/stable/10.2307/222902>.
- [7] B. W. Lewis. *doRedis: Foreach parallel adapter for the rredis package*. R package version 1.0.4. 2011. URL: <http://CRAN.R-project.org/package=doRedis>.
- [8] R Development Core Team. *R: A Language and Environment for Statistical Computing*. ISBN 3-900051-07-0. R Foundation for Statistical Computing. Vienna, Austria, 2012. URL: <http://www.R-project.org/>.
- [9] Victoria C Stodden. *The Digitization of Science: Reproducibility and Interdisciplinary Knowledge Transfer*. 2011. URL: <http://aaas.confex.com/aaas/2011/webprogram/Session3166.html>.
- [10] Steve Weston. *doMPI: Foreach parallel adaptor for the Rmpi package*. R package version 0.1-5. 2010. URL: <http://CRAN.R-project.org/package=doMPI>.