

Package ‘bnstruct’

November 9, 2016

Description Bayesian Network Structure Learning from Data with Missing Values.

The package implements the Silander-Myllymaki complete search, the Max-Min Parents-and-Children, the Hill-Climbing, the Max-Min Hill-climbing heuristic searches, and the Structural Expectation-Maximization algorithm. Available scoring functions are BDeu, AIC, BIC. The package also implements methods for generating and using bootstrap samples, imputed data, inference.

Type Package

Title Bayesian Network Structure Learning from Data with Missing Values

Version 1.0.1

Date 2016-10-20

Depends R (>= 2.10), bitops, Matrix, igraph, methods

Suggests graph, Rgraphviz, knitr, testthat

License GPL (>=2) | file LICENSE

Encoding UTF-8

RoxygenNote 5.0.1

VignetteBuilder knitr

NeedsCompilation yes

Author Francesco Sambo [aut, cre],
Alberto Franzin [aut]

Maintainer Francesco Sambo <francesco.sambo@unipd.it>

R topics documented:

add.observations<-	4
asia	4
asia_10000	5
belief.propagation	6
bn	7
BN-class	7

bn<-	8
BNDataset-class	9
boot	11
boots	12
boots<-	13
bootstrap	13
build.junction.tree	14
child	15
child_NA_5000	15
complete	16
cpts	17
cpts<-	17
dag	18
dag.to.cpdag	18
dag<-	19
data.file	20
data.file<-	20
discreteness	21
discreteness<-	22
em	22
get.most.probable.values	23
has.boots	24
has.imputed.boots	24
has.imputed.data	25
has.raw.data	26
header.file	26
header.file<-	27
imp.boots	28
imp.boots<-	28
impute	29
imputed.data	29
imputed.data<-	30
InferenceEngine-class	30
jpts	32
jpts<-	32
jt.cliques	33
jt.cliques<-	33
junction.tree	34
junction.tree<-	35
knn.impute	35
layering	36
learn.network	36
learn.params	39
learn.structure	40
marginals	43
name	44
name<-	44
node.sizes	45

node.sizes<-	45
num.boots	46
num.boots<-	46
num.items	47
num.items<-	47
num.nodes	48
num.nodes<-	48
num.variables	49
num.variables<-	49
observations	50
observations<-	50
plot	51
print	52
raw.data	52
raw.data<-	53
read.bif	53
read.dataset	54
read.dsc	55
read.net	56
sample.dataset	57
sample.row	57
save.to.eps	58
scoring.func	59
scoring.func<-	59
shd	60
show	60
struct.algo	61
struct.algo<-	61
test.updated.bn	62
tune.knn.impute	62
updated.bn	63
updated.bn<-	64
variables	64
variables<-	65
wpdag	65
wpdag.from.dag	66
wpdag<-	66
write.dsc	67
write.xgmml	67

```
add.observations<-      add further evidence to an existing list of observations of an
                        InferenceEngine.
```

Description

Add a list of observations to an InferenceEngine that already has observations, using a list composed by the two following vectors:

- `observed.vars` vector of observed variables;
- `observed.vals` vector of values observed for the variables in `observed.vars` in the corresponding position.

Usage

```
add.observations(x) <- value

## S4 replacement method for signature 'InferenceEngine'
add.observations(x) <- value
```

Arguments

`x` an [InferenceEngine](#).

`value` the list of observations of the [InferenceEngine](#).

Details

In case of multiple observations of the same variable, the last observation is the one used, as the most recent.

See Also

[observations<-](#)

```
asia                    load Asia dataset.
```

Description

Wrapper for a loader for the Asia dataset, with only raw data.

Usage

```
asia()
```

Details

The dataset has 10000 items, no missing data, so no imputation needs to be performed.

Value

a `BNDataset` containing the Child dataset.

See Also

[asia_10000](#)

Examples

```
dataset <- asia()
print(dataset)
```

asia_10000	Asia dataset.
------------	---------------

Description

The Asia dataset contains 10000 complete (no missing data, no latent variables) randomly generated items of the Asia Bayesian Network. No imputation needs to be performed, so only raw data is present.

Format

a `BNDataset` with raw data slow filled.

Details

The data the `BNDataset` object is built from is located in files `pkg_folder/extdata/asia_10000.header` and `pkg_folder/extdata/asia_10000.data`.

References

S. Lauritzen, D. Spiegelhalter. Local Computation with Probabilities on Graphical Structures and their Application to Expert Systems (with discussion). *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 50(2):157-224, 1988.

See Also

[asia](#)

belief.propagation	<i>perform belief propagation.</i>
--------------------	------------------------------------

Description

Perform belief propagation for the network of an InferenceEngine, given a set of observations when present. In the current version of bnstruct, belief propagation can be computed only over a junction tree.

Usage

```
belief.propagation(ie, observations = NULL, return.potentials = FALSE)
```

```
## S4 method for signature 'InferenceEngine'
belief.propagation(ie, observations = NULL,
  return.potentials = FALSE)
```

Arguments

ie	an InferenceEngine object.
observations	list of observations, consisting in two vector, observed.vars for the observed variables, and observed.vals for the values taken by variables listed in observed.vars. If no observations are provided, the InferenceEngine will use the ones it already contains.
return.potentials	if TRUE only the potentials are returned, instead of the default BN .

Value

updated [InferenceEngine](#) object.

Examples

```
## Not run:
dataset <- BNDataset("file.header", "file.data")
bn <- BN(dataset)
ie <- InferenceEngine(bn)
ie <- belief.propagation(ie)

observations(ie) <- list("observed.vars"=("A","G","X"), "observed.vals"=c(1,2,1))
belief.propagation(ie)

## End(Not run)
```

bn	get the BN object contained in an InferenceEngine .
----	---

Description

Return a network contained in an [InferenceEngine](#).

Usage

```
bn(x)

## S4 method for signature 'InferenceEngine'
bn(x)
```

Arguments

x an [InferenceEngine](#).

Value

the [BN](#) object contained in an [InferenceEngine](#).

BN-class	<i>BN class definition.</i>
----------	-----------------------------

Description

BN class definition.
 Instantiate a [BN](#) object.

Usage

```
## S4 method for signature 'BN'
initialize(.Object, dataset = NULL, ...)

BN(dataset = NULL, ...)
```

Arguments

.Object	a BN
dataset	a BNDataset object containing the dataset the network is built upon, if any. The remaining parameters are considered only if a starting dataset is provided.
...	potential further arguments of methods.

Details

The constructor may be invoked without parameters – in this case an empty network will be created, and its slots will be filled manually by the user. This is usually viable only if the user already has knowledge about the network structure.

Value

BN object.

Slots

name: name of the network
 num.nodes: number of nodes in the network
 variables: names of the variables in the network
 discreteness: TRUE if variable is discrete, FALSE if variable is continue
 node.sizes: if variable *i* is discrete, node.sizes[*i*] contains the cardinality of *i*, if *i* is instead discrete the value is the number of states variable *i* takes when discretized
 cpts: list of conditional probability tables of the network
 dag: adjacency matrix of the network
 wpdag: weighted partially dag
 scoring.func: scoring function used in structure learning (when performed)
 struct.algo: algorithm used in structure learning (when performed)

Examples

```
## Not run:
net.1 <- BN()

dataset <- BNdataset()
dataset <- read.dataset(dataset, "file.header", "file.data")
net.2 <- BN(dataset)

## End(Not run)
```

bn<- *set the original BN object contained in an InferenceEngine.*

Description

Add an original network to an InferenceEngine.

Usage

```
bn(x) <- value

## S4 replacement method for signature 'InferenceEngine'
bn(x) <- value
```

Arguments

x an [InferenceEngine](#).

value the [BN](#) object contained in an [InferenceEngine](#).

BNDataset-class	<i>BNDataset class.</i>
-----------------	-------------------------

Description

Contains the all of the data that can be extracted from a given dataset: raw data, imputed data, raw and imputed data with bootstrap.

initialize a [BNDataset](#) object.

Usage

```
BNDataset(data, discreteness, variables = NULL, node.sizes = NULL, ...)

## S4 method for signature 'BNDataset'
initialize(.Object)
```

Arguments

.Object	an empty BNDataset .
data	raw data.frame or path/name of the file containing the raw dataset (see 'Details').
discreteness	a vector of booleans indicating if the variables are discrete or continuous (TRUE and FALSE, respectively), or path/name of the file containing header information for the dataset (discreteness, variable names, cardinality - see 'Details').
variables	vector of variable names.
node.sizes	vector of variable cardinalities (for discrete variables) or quantization ranges (for continuous variables).
...	further arguments for reading a dataset from files (see documentation for <code>read.dataset</code>).

Details

There are two ways to build a BNDataset: using two files containing respectively header informations and data, and manually providing the data table and the related header informations (variable names, cardinality and discreteness).

The key informations needed are: 1. the data; 2. the state of variables (discrete or continuous); 3. the names of the variables; 4. the cardinalities of the variables (if discrete), or the number of levels they have to be quantized into (if continuous). Names and cardinalities/leves can be guessed by looking at the data, but it is strongly advised to provide `_all_` of the informations, in order to avoid problems later on during the execution.

Data can be provided in form of `data.frame` or matrix. It can contain NAs. By default, NAs are indicated with `'?'`; to specify a different character for NAs, it is possible to provide also the `na.string.symbol` parameter. The values contained in the data have to be numeric (real for continuous variables, integer for discrete ones). The default range of values for a discrete variable X is $[1, |X|]$, with $|X|$ being the cardinality of X . The same applies for the levels of quantization for continuous variables. If the value ranges for the data are different from the expected ones, it is possible to specify a different starting value (for the whole dataset) with the `starts.from` parameter. E.g. by `starts.from=0` we assume that the values of the variables in the dataset have range $[0, |X|-1]$. Please keep in mind that the internal representation of `bnstruct` starts from 1, and the original starting values are then lost.

It is possible to use two files, one for the data and one for the metadata, instead of providing manually all of the info. `bnstruct` requires the data files to be in a format subsequently described. The actual data has to be in (a text file containing data in) tabular format, one tuple per row, with the values for each variable separated by a space or a tab. Values for each variable have to be numbers, starting from 1 in case of discrete variables. Data files can have a first row containing the names of the corresponding variables.

In addition to the data file, a header file containing additional informations can also be provided. An header file has to be composed by three rows of tab-delimited values: 1. list of names of the variables, in the same order of the data file; 2. a list of integers representing the cardinality of the variables, in case of discrete variables, or the number of levels each variable has to be quantized in, in case of continuous variables; 3. a list that indicates, for each variable, if the variable is continuous (c or C), and thus has to be quantized before learning, or discrete (d or D). In case of need of more advanced options when reading a dataset from files, please refer to the documentation of the [read.dataset](#) method. Imputation and bootstrap are also available as separate routines ([impute](#) and [bootstrap](#), respectively).

Value

BNDataset object.

a BNDataset object.

Slots

`name`: name of the dataset

`header.file`: name and location of the header file

`data.file`: name and location of the data file

`variables`: names of the variables in the network

node.sizes: cardinality of each variable of the network
num.variables: number of variables (columns) in the dataset
discreteness: TRUE if variable is discrete, FALSE if variable is continue
num.items: number of observations (rows) in the dataset
has.raw.data: TRUE if the dataset contains data read from a file
has.imputed.data: TRUE if the dataset contains imputed data (computed from raw data)
raw.data: matrix containing raw data
imputed.data: matrix containing imputed data
has.boots: dataset has bootstrap samples
boots: list of bootstrap samples
has.imputed.boots: dataset has imputed bootstrap samples
imp.boots: list of imputed bootstrap samples
num.boots: number of bootstrap samples

See Also

read.dataset, impute, bootstrap

Examples

```
## Not run:
# create from files
dataset <- BNDataset("file.data", "file.header")

# other way: create from raw dataset and metadata
data <- matrix(c(1:16), nrow = 4, ncol = 4)
dataset <- BNDataset(data = data,
                     discreteness = rep('d',4),
                     variables = c("a", "b", "c", "d"),
                     node.sizes = c(4,8,12,16))

## End(Not run)
```

boot

get selected element of bootstrap list.

Description

Given a [BNDataset](#), return the sample corresponding to given index.

Usage

```
boot(dataset, index, use.imputed.data = FALSE)
```

```
## S4 method for signature 'BNDataset,numeric'
boot(dataset, index, use.imputed.data = FALSE)
```

Arguments

dataset a [BNDataset](#) object.
 index the index of the requested sample.
 use.imputed.data TRUE if samples from imputed dataset are to be used. Default if FALSE.

See Also

bootstrap
[bootstrap](#)

Examples

```
## Not run:
dataset <- BNDataset("file.data", "file.header")
dataset <- bootstrap(dataset, num.boots = 1000)

for (i in 1:num.boots(dataset))
  print(boot(dataset, i))

## End(Not run)
```

boots	<i>get list of bootstrap samples of a BNDataset.</i>
-------	--

Description

Return the list of samples computed from raw data of a dataset.

Usage

```
boots(x)

## S4 method for signature 'BNDataset'
boots(x)
```

Arguments

x a [BNDataset](#) object.

Value

the list of bootstrap samples.

See Also

[has.boots](#), [has.imputed.boots](#), [imp.boots](#)

boots<-	<i>set list of bootstrap samples of a BNDataset.</i>
---------	--

Description

Add to a dataset a list of samples from raw data computed using bootstrap.

Usage

```
boots(x) <- value
```

```
## S4 replacement method for signature 'BNDataset'
```

```
boots(x) <- value
```

Arguments

x	a BNDataset object.
value	the list of bootstrap samples.

bootstrap	<i>Perform bootstrap.</i>
-----------	---------------------------

Description

Create a list of num.boots samples of the original dataset.

Usage

```
bootstrap(object, num.boots = 100, seed = 0, imputation = FALSE,  
          k.impute = 10)
```

```
## S4 method for signature 'BNDataset'
```

```
bootstrap(object, num.boots = 100, seed = 0,  
          imputation = FALSE, k.impute = 10)
```

Arguments

object	the BNDataset object.
num.boots	number of sampled datasets for bootstrap.
seed	random seed.
imputation	TRUE if imputation has to be performed. Default is FALSE.
k.impute	number of neighbours to be used; for discrete variables we use mode, for continuous variables the median value is instead taken (useful only if imputation == TRUE).

Examples

```
## Not run:
dataset <- BNDataset("file.data", "file.header")
dataset <- bootstrap(dataset, num.boots = 1000)

## End(Not run)
```

build.junction.tree	<i>build a JunctionTree.</i>
---------------------	------------------------------

Description

Starting from the adjacency matrix of the directed acyclic graph of the network contained in an InferenceEngine, build a JunctionTree for the network and store it into an InferenceEngine.

Usage

```
build.junction.tree(object, ...)

## S4 method for signature 'InferenceEngine'
build.junction.tree(object, ...)
```

Arguments

object	an InferenceEngine object.
...	potential further arguments for methods.

See Also

[InferenceEngine](#)

Examples

```
## Not run:
dataset <- BNDataset("file.header", "file.data")
net <- BN(dataset)
eng <- InferenceEngine()
eng <- build.junction.tree(eng)

## End(Not run)
```

child	<i>load Child dataset.</i>
-------	----------------------------

Description

Wrapper for a loader for the Child raw dataset; also perform imputation.

Usage

```
child()
```

Details

The dataset has 5000 items, with random missing values (no latent variables). BNDataset object contains the raw dataset and imputed dataset, with k=10 (see [impute](#) for related explanation).

Value

a BNDataset containing the Child dataset.

See Also

[child_NA_5000](#)

Examples

```
dataset <- child()
print(dataset)
```

child_NA_5000	<i>Child dataset.</i>
---------------	-----------------------

Description

The Child dataset contains 5000 randomly generated items with missing data (no latent variables) of the Child Bayesian Network. Imputation is performed, so both raw and imputed data is present.

Format

a [BNDataset](#) with a raw and imputed data slow filled with 5000 items.

Details

The data the BNDataset object is built from is located in files `pkg_folder/extdata/extdata/Child_data_na_5000.head` and `pkg_folder/extdata/extdata/Child_data_na_5000.data`.

References

D. J. Spiegelhalter, R. G. Cowell (1992). Learning in probabilistic expert systems. In Bayesian Statistics 4 (J. M. Bernardo, J. O. Berger, A. P. Dawid and A. F. M. Smith, eds.) 447-466. Clarendon Press, Oxford.

See Also

[child](#)

complete

Subset a [BNDataset](#) to get only complete cases.

Description

Given a [BNDataset](#), return a copy of the original object where the `raw.data` consists only in the observations that do not contain missing values.

Usage

```
complete(x, complete.vars = seq_len(num.variables(x)))

## S4 method for signature 'BNDataset'
complete(x, complete.vars = seq_len(num.variables(x)))
```

Arguments

`x` a [BNDataset](#).

`complete.vars` vector containing the indices of the variables to be considered for the subsetting; variables not included in the vector can still contain NAs.

Details

Non-missingness can be required on a subset of variables (by default, on all variables).

If present, imputed data and bootstrap samples are eliminated from the new [BNDataset](#), as using this method *after* using [impute](#) or [bootstrap](#), there may likely be a loss of correspondence between the subsetted `raw.data` and the previously generated `imputed.data` and bootstrap samples.

Value

a copy of the original [BNDataset](#) containing only complete observations.

cpts	<i>get the list of conditional probability tables of a BN.</i>
------	--

Description

Return the list of conditional probability tables of the variables of a [BN](#) object. Each probability table is associated to the corresponding variable, and its dimensions are named according to the variable they represent.

Usage

```
cpts(x)

## S4 method for signature 'BN'
cpts(x)
```

Arguments

x an object.

Details

Each conditional probability table is represented as a multidimensional array. The ordering of the dimensions of each variable is not guaranteed to follow the actual conditional distribution. E.g. dimensions for conditional probability $P(C|A,B)$ can be either (C,A,B) or (A,B,C) , depending on if some operations have been performed, or how the probability table has been computed. Users should not rely on dimension numbers, but should instead select the dimensions using their names.

Value

list of the conditional probability tables of the desired object.

cpts<-	<i>set the list of conditional probability tables of a network.</i>
--------	---

Description

Set the list of conditional probability tables of a [BN](#) object.

Usage

```
cpts(x) <- value

## S4 replacement method for signature 'BN'
cpts(x) <- value
```

Arguments

`x` an object.
`value` list of the conditional probability tables of the object.

Details

Each conditional probability table is represented as a multidimensional array. To retrieve single dimensions (e.g. to compute marginals), users should provide dimensions names.

<code>dag</code>	<i>get adjacency matrix of a network.</i>
------------------	---

Description

Return the adjacency matrix of the directed acyclic graph representing the structure of a network.

Usage

```
dag(x)

## S4 method for signature 'BN'
dag(x)
```

Arguments

`x` an object.

Value

matrix containing the adjacency matrix of the directed acyclic graph representing the structure of the object.

<code>dag.to.cpdag</code>	<i>convert a DAG to a CPDAG</i>
---------------------------	---------------------------------

Description

Convert the adjacency matrix representing the DAG of a [BN](#) into the adjacency matrix representing a CPDAG for the network.

Usage

```
dag.to.cpdag(dag.adj.matrix, layering = NULL)
```

Arguments

`dag.adj.matrix` the adjacency matrix representing the DAG of a [BN](#).
`layering` vector containing the layers each node belongs to.

Value

the adjacency matrix representing a CPDAG for the network.

See Also

[wpdag.from.dag](#)

Examples

```
## Not run:
net <- learn.network(dataset, layering=layering)
pdag <- dag.to.cpdag(dag(net), layering)
wpdag(net) <- pdag

## End(Not run)
```

dag<-	<i>set adjacency matrix of an object.</i>
-------	---

Description

Set the adjacency matrix of the directed acyclic graph representing the structure of a network.

Usage

```
dag(x) <- value

## S4 replacement method for signature 'BN'
dag(x) <- value
```

Arguments

`x` an object.
`value` matrix containing the adjacency matrix of the directed acyclic graph representing the structure of the object.

data.file	<i>get data file of a BNDataset.</i>
-----------	--

Description

Return the data filename of a dataset (with the path to its position, as given by the user). The data filename may contain a header in the first row, containing the list of names of the variables, in the same order as in the header file. After the header, if present, the file contains a data.frame with the observations, one item per row.

Usage

```
data.file(x)

## S4 method for signature 'BNDataset'
data.file(x)
```

Arguments

x a [BNDataset](#).

Value

data filename of the dataset.

See Also

[data.file](#)

data.file<-	<i>set data file of a BNDataset.</i>
-------------	--

Description

Set the data filename of a dataset (with the path to its position, as given by the user). The data filename may contain a header in the first row, containing the list of names of the variables, in the same order as in the header file. After the header, if present, the file contains a data.frame with the observations, one item per row.

Usage

```
data.file(x) <- value

## S4 replacement method for signature 'BNDataset'
data.file(x) <- value
```

Arguments

x a [BNDataset](#).
 value data filename.

See Also

[header.file<-](#)

discreteness	<i>get status (discrete or continuous) of the variables of an object.</i>
--------------	---

Description

Get a vector representing the status of the variables (with their names) of a [BN](#) or [BNDataset](#). Elements of the vector are c if the variable is continue, and d if the variable is discrete.

Usage

```
discreteness(x)

## S4 method for signature 'BN'
discreteness(x)

## S4 method for signature 'BNDataset'
discreteness(x)
```

Arguments

x an object.

Value

vector containing, for each variable of the desired object, c if the variable is continue, and d if the variable is discrete.

discreteness<-	<i>set status (discrete or continuous) of the variables of an object.</i>
----------------	---

Description

Set the list of variable status for the variables in a network or a dataset.

Usage

```
discreteness(x) <- value

## S4 replacement method for signature 'BN'
discreteness(x) <- value

## S4 replacement method for signature 'BNdataset'
discreteness(x) <- value
```

Arguments

x	an object.
value	a vector of elements in {c,d} for continuous and discrete variables (respectively).

em	<i>expectation-maximization algorithm.</i>
----	--

Description

Learn parameters of a network using the Expectation-Maximization algorithm.

Usage

```
em(x, dataset, threshold = 0.001, max.em.iterations = 10, ess = 1)

## S4 method for signature 'InferenceEngine,BNdataset'
em(x, dataset, threshold = 0.001,
    max.em.iterations = 10, ess = 1)
```

Arguments

x	an InferenceEngine .
dataset	observed dataset with missing values for the Bayesian Network of x.
threshold	threshold for convergence, used as stopping criterion.
max.em.iterations	maximum number of iterations to run in case of no convergence.
ess	Equivalent Sample Size value.

Value

a list containing: an [InferenceEngine](#) with a new updated network ("InferenceEngine"), and the imputed dataset ("BNDataset").

Examples

```
## Not run:  
em(x, dataset)  
  
## End(Not run)
```

```
get.most.probable.values
```

compute the most probable values to be observed.

Description

Return an array containing the values that each variable of the network is more likely to take, according to the CPTS. In case of ties take the first value.

Usage

```
get.most.probable.values(x)  
  
## S4 method for signature 'BN'  
get.most.probable.values(x)  
  
## S4 method for signature 'InferenceEngine'  
get.most.probable.values(x)
```

Arguments

x a [BN](#) or [InferenceEngine](#) object.

Value

array containing, in each position, the most probable value for the corresponding variable.

Examples

```
## Not run:  
# try with a BN object x  
get.most.probable.values(x)  
  
# now build an InferenceEngine object  
eng <- InferenceEngine(x)  
get.most.probable.values(eng)
```

```
## End(Not run)
```

has.boots	<i>check whether a BNDataset has bootstrap samples or not.</i>
-----------	--

Description

Return TRUE if the given dataset contains samples for bootstrap, FALSE otherwise.

Usage

```
has.boots(x)

## S4 method for signature 'BNDataset'
has.boots(x)
```

Arguments

x a [BNDataset](#) object.

Value

TRUE if dataset has bootstrap samples.

See Also

[has.imputed.boots](#), [boots](#), [imp.boots](#)

has.imputed.boots	<i>check whether a BNDataset has bootstrap samples from imputed data or not.</i>
-------------------	--

Description

Return TRUE if the given dataset contains samples for bootstrap from inputted dataset, FALSE otherwise.

Usage

```
has.imputed.boots(x)

## S4 method for signature 'BNDataset'
has.imputed.boots(x)
```

Arguments

x a [BNDataset](#) object.

Value

TRUE if dataset has bootstrap samples from imputed data.

See Also

[has.boots](#), [boots](#), [imp.boots](#)

has.imputed.data	<i>check if a BNDataset contains imputed data.</i>
------------------	--

Description

Check whether a [BNDataset](#) object actually contains imputed data.

Usage

```
has.imputed.data(x)

## S4 method for signature 'BNDataset'
has.imputed.data(x)
```

Arguments

x a [BNDataset](#).

See Also

[has.raw.data](#), [raw.data](#), [imputed.data](#)

Examples

```
## Not run:
x <- BNDataset()
has.imputed.data(x) # FALSE

x <- read.dataset(x, "file.header", "file.data")
has.imputed.data(x) # FALSE, since read.dataset() actually reads raw data.

x <- impute(x)
has.imputed.data(x) # TRUE

## End(Not run)
```

has.raw.data	<i>check if a BNDataset contains raw data.</i>
--------------	--

Description

Check whether a [BNDataset](#) object actually contains raw data.

Usage

```
has.raw.data(x)

## S4 method for signature 'BNDataset'
has.raw.data(x)
```

Arguments

x a [BNDataset](#).

See Also

[has.imputed.data](#), [raw.data](#), [imputed.data](#)

Examples

```
## Not run:
x <- BNDataset()
has.raw.data(x) # FALSE

x <- read.dataset(x, "file.header", "file.data")
has.raw.data(x) # TRUE, since read.dataset() actually reads raw data.

## End(Not run)
```

header.file	<i>get header file of a BNDataset.</i>
-------------	--

Description

Return the header filename of a dataset (with the path to its position, as given by the user), present if the dataset has been read from a file and not manually inserted. The header file contains three rows:

1. list of names of the variables, in the same order as in the data file;
2. list of cardinalities of the variables, if discrete, or levels for quantization if continuous;
3. list of status of the variables: c for continuous variables, d for discrete ones.

Usage

```
header.file(x)

## S4 method for signature 'BNDataset'
header.file(x)
```

Arguments

x a [BNDataset](#).

Value

header filename of the dataset.

See Also

[data.file](#)

header.file<- *set header file of a [BNDataset](#).*

Description

Set the header filename of a dataset (with the path to its position, as given by the user). The header file has to contain three rows:

1. list of names of the variables, in the same order as in the data file;
2. list of cardinalities of the variables, if discrete, or levels for quantization if continuous;
3. list of status of the variables: c for continuous variables, d for discrete ones.

Further rows are ignored.

Usage

```
header.file(x) <- value

## S4 replacement method for signature 'BNDataset'
header.file(x) <- value
```

Arguments

x a [BNDataset](#).
value header filename.

See Also

[data.file<-](#)

imp.boots	<i>get list of bootstrap samples from imputed data of a BNDataset.</i>
-----------	--

Description

Return the list of samples computed from raw data of a dataset.

Usage

```
imp.boots(x)

## S4 method for signature 'BNDataset'
imp.boots(x)
```

Arguments

x a [BNDataset](#) object.

Value

the list of bootstrap samples from imputed data.

See Also

[has.boots](#), [has.imputed.boots](#), [boots](#)

imp.boots<-	<i>set list of bootstrap samples from imputed data of a BNDataset.</i>
-------------	--

Description

Add to a dataset a list of samples from imputed data computed using bootstrap.

Usage

```
imp.boots(x) <- value

## S4 replacement method for signature 'BNDataset'
imp.boots(x) <- value
```

Arguments

x a [BNDataset](#) object.
value the list of bootstrap samples from imputed data.

impute	<i>Impute a BNDataset raw data with missing values.</i>
--------	---

Description

Impute a [BNDataset](#) raw data with missing values.

Usage

```
impute(object, k.impute = 10)

## S4 method for signature 'BNDataset'
impute(object, k.impute = 10)
```

Arguments

object	the BNDataset object.
k.impute	number of neighbours to be used; for discrete variables we use mode, for continuous variables the median value is instead taken.

Examples

```
## Not run:
dataset <- BNDataset("file.data", "file.header")
dataset <- impute(dataset)

## End(Not run)
```

imputed.data	<i>get imputed data of a BNDataset.</i>
--------------	---

Description

Return imputed data contained in a [BNDataset](#) object, if any.

Usage

```
imputed.data(x)

## S4 method for signature 'BNDataset'
imputed.data(x)
```

Arguments

x	a BNDataset .
---	-------------------------------

See Also

[has.raw.data](#), [has.imputed.data](#), [raw.data](#)

<code>imputed.data<-</code>	<i>add imputed data.</i>
--------------------------------	--------------------------

Description

Insert imputed data in a [BNDataset](#) object.

Usage

```
imputed.data(x) <- value

## S4 replacement method for signature 'BNDataset'
imputed.data(x) <- value
```

Arguments

<code>x</code>	a BNDataset .
<code>value</code>	a matrix of integers containing a dataset.

See Also

[has.imputed.data](#), [imputed.data](#), [read.dataset](#)

<code>InferenceEngine-class</code>	<i>InferenceEngine class.</i>
------------------------------------	-------------------------------

Description

InferenceEngine class.
 Constructor method of [InferenceEngine](#) class.
 constructor for [InferenceEngine](#) object

Usage

```
## S4 method for signature 'InferenceEngine'
initialize(.Object, ...)

InferenceEngine(bn = NULL, observations = NULL, ...)
```

Arguments

- `.Object` an empty InferenceEngine object.
- `...` potential further arguments of methods.
- `bn` a BN object.
- `observations` a list of observations composed by the two following vectors:
 - `observed.vars`: vector of observed variables;
 - `observed.vals`: vector of values observed for the variables in `observed.vars` in the corresponding position.

Value

- an InferenceEngine object.
- InferenceEngine object.

Slots

- `junction.tree`: junction tree adjacency matrix.
- `num.nodes`: number of nodes in the junction tree.
- `cliques`: list of cliques composing the nodes of the junction tree.
- `triangulated.graph`: adjacency matrix of the original triangulated graph.
- `jpts`: inferred joint probability tables.
- `bn`: original Bayesian Network (as object of class BN) as provided by the user, or learnt from a dataset. NULL if missing.
- `updated.bn`: Bayesian Network (as object of class BN) as modified by a belief propagation computation. In particular, it will have different conditional probability tables with respect to its original version. NULL if missing.
- `observed.vars`: list of observed variables, by name or number.
- `observed.vals`: list of observed values for the corresponding variables in `observed.vars`.

Examples

```
## Not run:
dataset <- BNdataset()
dataset <- read.dataset(dataset, "file.header", "file.data")
bn <- BN(dataset)
eng <- InferenceEngine(bn)

obs <- list(c("A", "G", "X"), c(1, 2, 1))
eng.2 <- InferenceEngine(bn, obs)

## End(Not run)
```

jpts	<i>get the list of joint probability tables compiled by an InferenceEngine.</i>
------	---

Description

Return the list of joint probability tables for the cliques of the junction tree obtained after belief propagation has been performed.

Usage

```
jpts(x)

## S4 method for signature 'InferenceEngine'
jpts(x)
```

Arguments

x an [InferenceEngine](#).

Details

Each joint probability table is represented as a multidimensional array. To retrieve single dimensions (e.g. to compute marginals), users should not rely on dimension numbers, but should instead select the dimensions using their names.

Value

the list of joint probability tables compiled by the [InferenceEngine](#).

jpts<-	<i>set the list of joint probability tables compiled by an InferenceEngine.</i>
--------	---

Description

Add a list of joint probability tables for the cliques of the junction tree.

Usage

```
jpts(x) <- value

## S4 replacement method for signature 'InferenceEngine'
jpts(x) <- value
```

Arguments

x an [InferenceEngine](#).
 value the list of joint probability tables compiled by the [InferenceEngine](#).

Details

Each joint probability table is represented as a multidimensional array. To retrieve single dimensions (e.g. to compute marginals), users should provide dimension names.

jt.cliques	<i>get the list of cliques of the junction tree of an InferenceEngine.</i>
------------	--

Description

Return the list of cliques containing the variables associated to each node of a junction tree.

Usage

```
jt.cliques(x)

## S4 method for signature 'InferenceEngine'
jt.cliques(x)
```

Arguments

x an [InferenceEngine](#).

Value

the list of cliques of the junction tree contained in the [InferenceEngine](#).

jt.cliques<-	<i>set the list of cliques of the junction tree of an InferenceEngine.</i>
--------------	--

Description

Add to the [InferenceEngine](#) a list containing the cliques of variables composing the nodes of the junction tree.

Usage

```
jt.cliques(x) <- value

## S4 replacement method for signature 'InferenceEngine'
jt.cliques(x) <- value
```

Arguments

x an [InferenceEngine](#).
value the list of cliques of the junction tree contained in the [InferenceEngine](#).

junction.tree *get the junction tree of an [InferenceEngine](#).*

Description

Return the adjacency matrix representing the junction tree computed for a network.

Usage

```
junction.tree(x)  
  
## S4 method for signature 'InferenceEngine'  
junction.tree(x)
```

Arguments

x an [InferenceEngine](#).

Details

Rows and columns are named after the (variables in the) cliques that each node of the junction tree represent.

Value

the junction tree contained in the [InferenceEngine](#).

See Also

[build.junction.tree](#)

junction.tree<-	set the junction tree of an InferenceEngine .
-----------------	---

Description

Set the adjacency matrix of the junction tree computed for a network.

Usage

```
junction.tree(x) <- value

## S4 replacement method for signature 'InferenceEngine'
junction.tree(x) <- value
```

Arguments

x	an InferenceEngine .
value	the junction tree to be inserted in the InferenceEngine .

knn.impute	Perform imputation of a data frame using k-NN.
------------	--

Description

Perform imputation of missing data in a data frame using the k-Nearest Neighbour algorithm. For discrete variables we use the mode, for continuous variables the median value is instead taken.

Usage

```
knn.impute(data, k = 10, cat.var = 1:ncol(data), to.impute = 1:nrow(data),
  using = 1:nrow(data))
```

Arguments

data	a data frame
k	number of neighbours to be used; for categorical variables the mode of the neighbours is used, for continuous variables the median value is used instead. Default: 10.
cat.var	vector containing the indices of the variables to be considered as categorical. Default: all variables.
to.impute	vector indicating which rows of the dataset are to be imputed. Default: impute all rows.
using	vector indicating which rows of the dataset are to be used to search for neighbours. Default: use all rows.

Value

imputed data frame.

layering	<i>return the layering of the nodes.</i>
----------	--

Description

Compute the topological ordering of the nodes of a network, in order to divide the network in layers.

Usage

```
layering(x)

## S4 method for signature 'BN'
layering(x)
```

Arguments

x a [BN](#) object.

Value

a vector containing layers the nodes can be divided into.

Examples

```
## Not run:
dataset <- BNdataset("file.header", "file.data")
x <- BN(dataset)
x <- learn.network(x, dataset)
layering(x)

## End(Not run)
```

learn.network	<i>learn a network (structure and parameters) of a BN from a BNdataset.</i>
---------------	---

Description

Learn a network (structure and parameters) of a [BN](#) from a [BNdataset](#) (see the Details section).

Usage

```
learn.network(x, ...)

## S4 method for signature 'BN'
learn.network(x, y = NULL, algo = "mmhc",
  scoring.func = "BDeu", initial.network = NULL, alpha = 0.05, ess = 1,
  bootstrap = FALSE, layering = c(), max.fanin.layers = NULL,
  max.fanin = num.variables(dataset), layer.struct = NULL,
  cont.nodes = c(), use.imputed.data = FALSE, use.cpc = TRUE, ...)

## S4 method for signature 'BNdataset'
learn.network(x, algo = "mmhc", scoring.func = "BDeu",
  initial.network = NULL, alpha = 0.05, ess = 1, bootstrap = FALSE,
  layering = c(), max.fanin.layers = NULL,
  max.fanin = num.variables(dataset), layer.struct = NULL,
  cont.nodes = c(), use.imputed.data = FALSE, use.cpc = TRUE, ...)
```

Arguments

x	can be a BN or a BNdataset . If x is a BN , then also the dataset parameter must be given.
...	potential further arguments for methods.
y	a BNdataset object, to be provided only if x is a BN .
algo	the algorithm to use. Currently, one among <code>sm</code> (Silander-Myllymaki), <code>mmpc</code> (Max-Min Parent-and-Children), <code>mmhc</code> (Max-Min Hill Climbing, default), <code>hc</code> (Hill Climbing) and <code>sem</code> (Structural Expectation Maximization).
scoring.func	the scoring function to use. Currently, one among <code>BDeu</code> , <code>AIC</code> , <code>BIC</code> .
initial.network	network structure to be used as starting point for structure search. Can take different values: a <code>BN</code> object, a matrix containing the adjacency matrix of the structure of the network, or the string <code>random.chain</code> to sample a random chain as starting point.
alpha	confidence threshold (only for <code>mmhc</code>).
ess	Equivalent Sample Size value.
bootstrap	<code>TRUE</code> to use bootstrap samples.
layering	vector containing the layers each node belongs to.
max.fanin.layers	matrix of available parents in each layer (only for <code>sm</code>).
max.fanin	maximum number of parents for each node (only for <code>sm</code>).
layer.struct	0/1 matrix for indicating which layers can contain parent nodes for nodes in a layer (only for <code>mmhc</code>).
cont.nodes	vector containing the index of continuous variables.
use.imputed.data	<code>TRUE</code> to learn the structure from the imputed dataset (if available, a check is performed). Default is to use raw dataset

`use.cpc` (when using `mmhc`) compute Candidate Parent-and-Children sets instead of starting the Hill Climbing from an empty graph.

Details

Learn the structure (the directed acyclic graph) of a `BN` object according to a `BNDataset`. We provide five algorithms for learning the structure of the network, that can be chosen with the `algo` parameter. The first one is the Silander-Myllymäki (`sm`) exact search-and-score algorithm, that performs a complete evaluation of the search space in order to discover the best network; this algorithm may take a very long time, and can be inapplicable when discovering networks with more than 25–30 nodes. Even for small networks, users are strongly encouraged to provide meaningful parameters such as the layering of the nodes, or the maximum number of parents – refer to the documentation in package manual for more details on the method parameters.

The second method is the constraint-based Max-Min Parents-and-Children (`mmpc`), that returns the skeleton of the network. Given the possible presence of loops, due to the non-directionality of the edges discovered, no parameter learning is possible using this algorithm. Also note that in the case of a very dense network and lots of observations, the statistical evaluation of the search space may take a long time. Also for this algorithm there are parameters that may need to be tuned, mainly the confidence threshold of the statistical pruning. Please refer to the rest of this documentation for their explanation.

The third algorithm is another heuristic, the Hill-Climbing (`hc`). It can start from the complete space of possibilities (default) or from a reduced subset of possible edges, using the `cpc` argument.

The fourth algorithm (and the default one) is the Max-Min Hill-Climbing heuristic (`mmhc`), that performs a statistical sieving of the search space followed by a greedy evaluation, by combining the `MMPC` and the `HC` algorithms. It is considerably faster than the complete method, at the cost of a (likely) lower quality. As for `MMPC`, the computational time depends on the density of the network, the number of observations and the tuning of the parameters.

The fifth method is the Structural Expectation-Maximization (`sem`) algorithm, for learning a network from a dataset with missing values. It iterates a sequence of Expectation-Maximization (in order to “fill in” the holes in the dataset) and structure learning from the guessed dataset, until convergence. The structure learning used inside `SEM`, due to computational reasons, is `MMHC`. Convergence of `SEM` can be controlled with the parameters `struct.threshold` and `param.threshold`, for the structure and the parameter convergence, respectively.

Search-and-score methods also need a scoring function to compute an estimated measure of each configuration of nodes. We provide three of the most popular scoring functions, `BDeu` (Bayesian-Dirichlet equivalent uniform, default), `AIC` (Akaike Information Criterion) and `BIC` (Bayesian Information Criterion). The scoring function can be chosen using the `scoring.func` parameter.

Structure learning sets the `dag` field of the `BN` under study, unless bootstrap or the `mmpc` algorithm are employed. In these cases, given the possible presence of loops, the `wpdag` field is set.

In case of missing data, the default behaviour (with no other indication from the user) is to learn the structure using `mmhc` starting from the raw dataset, using only the available cases with no imputation.

Then, the parameters of the network are learnt using `MAP` (Maximum A Posteriori) estimation (when not using bootstrap or `mmpc`).

See documentation for `learn.structure` and `learn.params` for more informations.

Value

new [BN](#) object with structure (DAG) and conditional probabilities as learnt from the given dataset.

See Also

learn.structure learn.params

Examples

```
## Not run:
mydataset <- BNdataset("data.file", "header.file")

# starting from a BN
net <- BN(mydataset)
net <- learn.network(net, mydataset)

# start directly from the dataset
net <- learn.network(mydataset)

## End(Not run)
```

learn.params	<i>learn the parameters of a BN.</i>
--------------	--

Description

Learn the parameters of a [BN](#) object according to a [BNdataset](#) using MAP (Maximum A Posteriori) estimation.

Usage

```
learn.params(bn, dataset, ess = 1, use.imputed.data = F)

## S4 method for signature 'BN,BNdataset'
learn.params(bn, dataset, ess = 1,
  use.imputed.data = FALSE)
```

Arguments

bn	a BN object.
dataset	a BNdataset object.
ess	Equivalent Sample Size value.
use.imputed.data	use imputed data.

Details

Parameter learning is not possible in case of networks learnt using the mmhc algorithm, or from bootstrap samples, as there may be loops.

Value

new [BN](#) object with conditional probabilities.

See Also

[learn.network](#)

Examples

```
## Not run:
## first create a BN and learn its structure from a dataset
dataset <- BNdataset("file.header", "file.data")
bn <- BN(dataset)
bn <- learn.structure(bn, dataset)
bn <- learn.params(bn, dataset, ess=1)

## End(Not run)
```

learn.structure	<i>learn the structure of a network.</i>
-----------------	--

Description

Learn the structure (the directed acyclic graph) of a [BN](#) object according to a [BNdataset](#).

Usage

```
learn.structure(bn, dataset, algo = "mmhc", scoring.func = "BDeu",
  initial.network = NULL, alpha = 0.05, ess = 1, bootstrap = FALSE,
  layering = c(), max.fanin.layers = NULL,
  max.fanin = num.variables(dataset), layer.struct = NULL,
  cont.nodes = c(), use.imputed.data = FALSE, use.cpc = TRUE, ...)

## S4 method for signature 'BN,BNdataset'
learn.structure(bn, dataset, algo = "mmhc",
  scoring.func = "BDeu", initial.network = NULL, alpha = 0.05, ess = 1,
  bootstrap = FALSE, layering = c(), max.fanin.layers = NULL,
  max.fanin = num.variables(dataset), layer.struct = NULL,
  cont.nodes = c(), use.imputed.data = FALSE, use.cpc = TRUE, ...)
```

Arguments

<code>bn</code>	a BN object.
<code>dataset</code>	a BNDataset .
<code>algo</code>	the algorithm to use. Currently, one among <code>sm</code> (Silander-Myllymaki), <code>mmpc</code> (Max-Min Parent-and-Children), <code>mmhc</code> (Max-Min Hill Climbing, default), <code>hc</code> (Hill Climbing) and <code>sem</code> (Structural Expectation Maximization).
<code>scoring.func</code>	the scoring function to use. Currently, one among <code>BDeu</code> , <code>AIC</code> , <code>BIC</code> .
<code>initial.network</code>	network structure to be used as starting point for structure search. Can take different values: a <code>BN</code> object, a matrix containing the adjacency matrix of the structure of the network, or the string <code>random.chain</code> to sample a random chain as starting point.
<code>alpha</code>	confidence threshold (only for <code>mmhc</code>).
<code>ess</code>	Equivalent Sample Size value.
<code>bootstrap</code>	<code>TRUE</code> to use bootstrap samples.
<code>layering</code>	vector containing the layers each node belongs to (only for <code>sm</code>).
<code>max.fanin.layers</code>	matrix of available parents in each layer (only for <code>sm</code>).
<code>max.fanin</code>	maximum number of parents for each node (only for <code>sm</code>).
<code>layer.struct</code>	prior knowledge for layering structure (only for <code>mmhc</code>).
<code>cont.nodes</code>	vector containing the index of continuous variables.
<code>use.imputed.data</code>	<code>TRUE</code> to learn the structure from the imputed dataset (if available, a check is performed). Default is to use raw dataset
<code>use.cpc</code>	(when using <code>mmhc</code>) compute Candidate Parent-and-Children sets instead of starting the Hill Climbing from an empty graph.
<code>...</code>	potential further arguments for method.

Details

We provide three algorithms in order to learn the structure of the network, that can be chosen with the `algo` parameter. The first is the Silander-Myllymaki (`sm`) exact search-and-score algorithm, that performs a complete evaluation of the search space in order to discover the best network; this algorithm may take a very long time, and can be inapplicable when discovering networks with more than 25–30 nodes. Even for small networks, users are strongly encouraged to provide meaningful parameters such as the layering of the nodes, or the maximum number of parents – refer to the documentation in package manual for more details on the method parameters.

The second method is the constraint-based Max-Min Parents-and-Children (`mmpc`), that returns the skeleton of the network. Given the possible presence of loops, due to the non-directionality of the edges discovered, no parameter learning is possible using this algorithm. Also note that in the case of a very dense network and lots of observations, the statistical evaluation of the search space may take a long time. Also for this algorithm there are parameters that may need to be tuned, mainly the confidence threshold of the statistical pruning. Please refer to the rest of this documentation for their explanation.

The third algorithm is another heuristic, the Hill-Climbing (hc). It can start from the complete space of possibilities (default) or from a reduced subset of possible edges, using the `cpc` argument.

The fourth algorithm (and the default one) is the Max-Min Hill-Climbing heuristic (mmhc), that performs a statistical sieving of the search space followed by a greedy evaluation, by combining the MMPC and the HC algorithms. It is considerably faster than the complete method, at the cost of a (likely) lower quality. As for MMPC, the computational time depends on the density of the network, the number of observations and the tuning of the parameters.

The fifth method is the Structural Expectation-Maximization (sem) algorithm, for learning a network from a dataset with missing values. It iterates a sequence of Expectation-Maximization (in order to “fill in” the holes in the dataset) and structure learning from the guessed dataset, until convergence. The structure learning used inside SEM, due to computational reasons, is MMHC. Convergence of SEM can be controlled with the parameters `struct.threshold` and `param.threshold`, for the structure and the parameter convergence, respectively. for learning a network from a dataset with missing values. It iterates a sequence of Expectation-Maximization (in order to “fill in” the holes in the dataset) and structure learning from the guessed dataset, until convergence. The structure learning used inside SEM, due to computational reasons, is MMHC. Convergence of SEM can be controlled with the parameters `struct.threshold` and `param.threshold`, for the structure and the parameter convergence, respectively.

Search-and-score methods also need a scoring function to compute an estimated measure of each configuration of nodes. We provide three of the most popular scoring functions, BDeu (Bayesian-Dirichlet equivalent uniform, default), AIC (Akaike Information Criterion) and BIC (Bayesian Information Criterion). The scoring function can be chosen using the `scoring.func` parameter.

Structure learning sets the `dag` field of the BN under study, unless bootstrap or the `mmpc` algorithm are employed. In these cases, given the possible presence of loops, the `wpdag` field is set.

In case of missing data, the default behaviour (with no other indication from the user) is to learn the structure using `mmhc` starting from the raw dataset.

Value

new [BN](#) object with DAG.

See Also

[learn.network](#)

Examples

```
## Not run:
dataset <- BNdataset("file.header", "file.data")
bn <- BN(dataset)
# use MMHC
bn <- learn.structure(bn, dataset, alpha=0.05, ess=1, bootstrap=FALSE)

# now use Silander-Myllymaki
layers <- layering(bn)
mfl <- as.matrix(read.table(header=F,
text='0 1 1 1 1 0 1 1 1 1 0 0 8 7 7 0 0 0 14 6 0 0 0 0 19'))
bn <- learn.structure(bn, dataset, algo='sm', max.fanin=3, cont.nodes=c(),
                      layering=layers, max.fanin.layers=mfl, use.imputed.data=FALSE)
```

```
## End(Not run)
```

<code>marginals</code>	<i>compute the list of inferred marginals of a BN.</i>
------------------------	--

Description

Given an [InferenceEngine](#), it returns a list containing the marginals for the variables in the network, according to the propagated beliefs.

Usage

```
marginals(x, ...)
```

S4 method for signature 'InferenceEngine'

```
marginals(x, ...)
```

Arguments

<code>x</code>	an InferenceEngine
<code>...</code>	potential further arguments of methods.

Value

a list containing the marginals of each variable, as probability tables.

Examples

```
## Not run:
eng <- InferenceEngine(net)
marginals(eng)

## End(Not run)
```

name	<i>get name of an object.</i>
------	-------------------------------

Description

Return the name of an object, of class [BN](#) or [BNDataset](#).

Usage

```
name(x)

## S4 method for signature 'BN'
name(x)

## S4 method for signature 'BNDataset'
name(x)
```

Arguments

x an object.

Value

name of the object.

name<-	<i>set name of an object.</i>
--------	-------------------------------

Description

Set the name slot of an object of type [BN](#) or [BNDataset](#).

Usage

```
name(x) <- value

## S4 replacement method for signature 'BN'
name(x) <- value

## S4 replacement method for signature 'BNDataset'
name(x) <- value
```

Arguments

x an object.
 value the new name of the object.

node.sizes	<i>get size of the variables of an object.</i>
------------	--

Description

Return a list containing the size of the variables of an object. It is the actual cardinality of discrete variables, and the cardinality of the discretized variable for continuous variables.

Usage

```
node.sizes(x)

## S4 method for signature 'BN'
node.sizes(x)

## S4 method for signature 'BNdataset'
node.sizes(x)
```

Arguments

x an object.

Value

vector containing the size of each variable of the desired object.

node.sizes<-	<i>set the size of variables of an object.</i>
--------------	--

Description

Set the size of the variables of a BN or BNdataset object. It represents the actual cardinality of discrete variables, and the cardinality of the discretized variable for continuous variables.

Usage

```
node.sizes(x) <- value

## S4 replacement method for signature 'BN'
node.sizes(x) <- value

## S4 replacement method for signature 'BNdataset'
node.sizes(x) <- value
```

Arguments

x an object.
 value vector containing the size of each variable of the object.

num.boots *get number of bootstrap samples of a [BNDataset](#).*

Description

Return the number of bootstrap samples computed from a dataset.

Usage

```
num.boots(x)

## S4 method for signature 'BNDataset'
num.boots(x)
```

Arguments

x a [BNDataset](#) object.

Value

the number of bootstrap samples.

num.boots<- *set number of bootstrap samples of a [BNDataset](#).*

Description

Set the length of the list of samples of a dataset computed using bootstrap.

Usage

```
num.boots(x) <- value

## S4 replacement method for signature 'BNDataset'
num.boots(x) <- value
```

Arguments

x a [BNDataset](#) object.
 value the number of bootstrap samples.

num.items	<i>get number of items of a BNDataset.</i>
-----------	--

Description

Return the number of items in a dataset, that is, the number of rows in its data slot.

Usage

```
num.items(x)

## S4 method for signature 'BNDataset'
num.items(x)
```

Arguments

x a [BNDataset](#) object.

Value

number of items of the desired dataset.

num.items<-	<i>set number of items of a BNDataset.</i>
-------------	--

Description

Set the number of observed items (rows) in a dataset.

Usage

```
num.items(x) <- value

## S4 replacement method for signature 'BNDataset'
num.items(x) <- value
```

Arguments

x a [BNDataset](#) object.

value number of items of the desired dataset.

num.nodes	<i>get number of nodes of an object.</i>
-----------	--

Description

Return the name of an object, of class [BN](#) or [InferenceEngine](#).

Usage

```
num.nodes(x)

## S4 method for signature 'BN'
num.nodes(x)

## S4 method for signature 'InferenceEngine'
num.nodes(x)
```

Arguments

x an object.

Value

number of nodes of the desired object.

num.nodes<-	<i>set number of nodes of an object.</i>
-------------	--

Description

Set the number of nodes of an object of type [BN](#) (number of nodes of the network) or [InferenceEngine](#) (where parameter contains the number of nodes of the junction tree).

Usage

```
num.nodes(x) <- value

## S4 replacement method for signature 'BN'
num.nodes(x) <- value

## S4 replacement method for signature 'InferenceEngine'
num.nodes(x) <- value
```

Arguments

x an object.
value the number of nodes in the object.

num.variables	<i>get number of variables of a BNDataSet.</i>
---------------	--

Description

Return the number of the variables contained in a dataset. This value corresponds to the value of [num.nodes](#) of a network built upon the same dataset.

Usage

```
num.variables(x)

## S4 method for signature 'BNDataSet'
num.variables(x)

## S4 method for signature 'BNDataSet'
num.variables(x)
```

Arguments

x a [BNDataSet](#) object.

Value

number of variables of the desired dataset.

See Also

[num.nodes](#)

num.variables<-	<i>set number of variables of a BNDataSet.</i>
-----------------	--

Description

Set the number of variables observed in a dataset.

Usage

```
num.variables(x) <- value

## S4 replacement method for signature 'BNDataSet'
num.variables(x) <- value
```

Arguments

x a [BNDataSet](#) object.
 value number of variables of the dataset.

observations	<i>get the list of observations of an InferenceEngine.</i>
--------------	--

Description

Return the list of observations added to an [InferenceEngine](#).

Usage

```
observations(x)

## S4 method for signature 'InferenceEngine'
observations(x)
```

Arguments

x an [InferenceEngine](#).

Details

Output is a list in the following format:

- observed.varsvector of observed variables;
- observed.valsvector of values observed for the variables in observed.vars in the corresponding position.

Value

the list of observations of the [InferenceEngine](#).

observations<-	<i>set the list of observations of an InferenceEngine.</i>
----------------	--

Description

Add a list of observations to an [InferenceEngine](#), using a list of observations composed by the two following vectors:

- observed.varsvector of observed variables;
- observed.valsvector of values observed for the variables in observed.vars in the corresponding position.

Usage

```
observations(x) <- value

## S4 replacement method for signature 'InferenceEngine'
observations(x) <- value
```

Arguments

`x` an [InferenceEngine](#).
`value` the list of observations of the [InferenceEngine](#).

Details

Replace previous list of observations, if present. In order to add evidence, and not just replace it, one must use the [add.observations<-](#) method.

In case of multiple observations of the same variable, the last observation is the one used, as the most recent.

See Also

[add.observations<-](#)

plot	<i>plot a BN as a picture.</i>
------	--

Description

plot a [BN](#) as a picture.

Usage

```
## S3 method for class 'BN'
plot(x, ..., use.node.names = TRUE, frac = 0.2,
      max.weight = max(dag(x)), node.col = rep("white", num.nodes(x)),
      plot.wpdag = FALSE)
```

Arguments

`x` a [BN](#) object.
`...` potential further arguments for methods.
`use.node.names` TRUE if node names have to be printed. If FALSE, numbers are used instead.
`frac` minimum fraction [0,1] of presence of an edge to be plotted (used in case of `plot.wpdag=TRUE`).
`max.weight` maximum possible weight of an edge (used in case of `plot.wpdag=TRUE`).
`node.col` list of (R) colors for the nodes.
`plot.wpdag` if TRUE plot the network according to the WPDAG computed using bootstrap instead of the DAG.

print	<i>print an object to stdout.</i>
-------	-----------------------------------

Description

print an object to stdout.

Usage

```
print(x, ...)

## S4 method for signature 'BN'
print(x, ...)

## S4 method for signature 'BNDataset'
print(x, show.raw.data = FALSE,
      show.imputed.data = FALSE, ...)

## S4 method for signature 'InferenceEngine'
print(x, engine = "jt", ...)
```

Arguments

x	an object.
...	potential other arguments.
show.raw.data	when x is a BNDataset , print also raw dataset, if available.
show.imputed.data	when x is a BNDataset , print also imputed dataset, if available.
engine	when x is an InferenceEngine , specify the inference engine to be shown. Currently only engine = 'jt' is supported.

raw.data	<i>get raw data of a BNDataset.</i>
----------	-------------------------------------

Description

Return raw data contained in a [BNDataset](#) object, if any.

Usage

```
raw.data(x)

## S4 method for signature 'BNDataset'
raw.data(x)
```

`raw.data<-`

53

Arguments

`x` a [BNDataset](#).

See Also

[has.raw.data](#), [has.imputed.data](#)

<code>raw.data<-</code>	<i>add raw data.</i>
----------------------------	----------------------

Description

Insert raw data in a [BNDataset](#) object.

Usage

```
raw.data(x) <- value
```

```
## S4 replacement method for signature 'BNDataset'  
raw.data(x) <- value
```

Arguments

`x` a [BNDataset](#).

`value` a matrix of integers containing a dataset.

See Also

[has.raw.data](#), [raw.data](#), [read.dataset](#)

<code>read.bif</code>	<i>Read a network from a .bif file.</i>
-----------------------	---

Description

Read a network described in a .bif-formatted file, and build a [BN](#) object.

Usage

```
read.bif(x)
```

```
## S4 method for signature 'character'  
read.bif(x)
```

Arguments

x the .bif file, with absolute/relative position.

Details

The method relies on a coherent ordering of variable values and parameters in the file.

Value

a [BN](#) object.

read.dataset	<i>Read a dataset from file.</i>
--------------	----------------------------------

Description

There are two ways to build a BNDataset: using two files containing respectively header informations and data, and manually providing the data table and the related header informations (variable names, cardinality and discreteness).

Usage

```
read.dataset(object, data.file, header.file, data.with.header = FALSE,
             na.string.symbol = "?", sep.symbol = "", starts.from = 1)
```

```
## S4 method for signature 'BNDataset,character,character'
read.dataset(object, data.file,
             header.file, data.with.header = FALSE, na.string.symbol = "?",
             sep.symbol = "", starts.from = 1)
```

Arguments

object the [BNDataset](#) object.

data.file the data file.

header.file the header file.

data.with.header TRUE if the first row of dataset file is an header (e.g. it contains the variable names).

na.string.symbol character that denotes NA in the dataset.

sep.symbol separator among values in the dataset.

starts.from starting value for entries in the dataset (observed values, default is 1).

Details

The key informations needed are: 1. the data; 2. the state of variables (discrete or continuous); 3. the names of the variables; 4. the cardinalities of the variables (if discrete), or the number of levels they have to be quantized into (if continuous). Names and cardinalities/leves can be guessed by looking at the data, but it is strongly advised to provide `_all_` of the informations, in order to avoid problems later on during the execution.

Data can be provided in form of `data.frame` or matrix. It can contain NAs. By default, NAs are indicated with `'?'`; to specify a different character for NAs, it is possible to provide also the `na.string.symbol` parameter. The values contained in the data have to be numeric (real for continuous variables, integer for discrete ones). The default range of values for a discrete variable `X` is `[1, |X|]`, with `|X|` being the cardinality of `X`. The same applies for the levels of quantization for continuous variables. If the value ranges for the data are different from the expected ones, it is possible to specify a different starting value (for the whole dataset) with the `starts.from` parameter. E.g. by `starts.from=0` we assume that the values of the variables in the dataset have range `[0, |X|-1]`. Please keep in mind that the internal representation of `bnstruct` starts from 1, and the original starting values are then lost.

It is possible to use two files, one for the data and one for the metadata, instead of providing manually all of the info. `bnstruct` requires the data files to be in a format subsequently described. The actual data has to be in (a text file containing data in) tabular format, one tuple per row, with the values for each variable separated by a space or a tab. Values for each variable have to be numbers, starting from 1 in case of discrete variables. Data files can have a first row containing the names of the corresponding variables.

In addition to the data file, a header file containing additional informations can also be provided. An header file has to be composed by three rows of tab-delimited values: 1. list of names of the variables, in the same order of the data file; 2. a list of integers representing the cardinality of the variables, in case of discrete variables, or the number of levels each variable has to be quantized in, in case of continuous variables; 3. a list that indicates, for each variable, if the variable is continuous (c or C), and thus has to be quantized before learning, or discrete (d or D).

See Also

`BNDataset`

Examples

```
## Not run:
dataset <- BNDataset()
dataset <- read.dataset(dataset, "file.data", "file.header")

## End(Not run)
```

Description

Read a network described in a .dsc-formatted file, and build a [BN](#) object.

Usage

```
read.dsc(x)

## S4 method for signature 'character'
read.dsc(x)
```

Arguments

x the .dsc file, with absolute/relative position.

Details

The method relies on a coherent ordering of variable values and parameters in the file.

Value

a [BN](#) object.

read.net	<i>Read a network from a .net file.</i>
----------	---

Description

Read a network described in a .net-formatted file, and build a [BN](#) object.

Usage

```
read.net(x)

## S4 method for signature 'character'
read.net(x)
```

Arguments

x the .net file, with absolute/relative position.

Details

The method relies on a coherent ordering of variable values and parameters in the file.

Value

a [BN](#) object.

sample.dataset	sample a BNDataset from a network of an inference engine.
----------------	---

Description

sample a [BNDataset](#) from a network of an inference engine.

Usage

```
sample.dataset(x, n = 100, mar = 0)

## S4 method for signature 'BN'
sample.dataset(x, n = 100, mar = 0)

## S4 method for signature 'InferenceEngine'
sample.dataset(x, n = 100)
```

Arguments

x	a BN or InferenceEngine object.
n	number of items to sample.
mar	fraction [0,1] of missing values in the sampled dataset (missing at random), default value is 0 (no missing values).

Value

a [BNDataset](#)

sample.row	sample a row vector of values for a network.
------------	--

Description

sample a row vector of values for a network.

Usage

```
sample.row(x, mar = 0)

## S4 method for signature 'BN'
sample.row(x, mar = 0)
```

Arguments

x	a BN or InferenceEngine object.
mar	fraction [0,1] of missing values in the sampled vector (missing at random), default value is 0 (no missing values).

Value

a vector of values.

save.to.eps	<i>save a BN picture as .eps file.</i>
-------------	--

Description

Save an image of a Bayesian Network as an .eps file.

Usage

```
save.to.eps(x, filename)

## S4 method for signature 'BN,character'
save.to.eps(x, filename)
```

Arguments

x	a BN object
filename	name (with path, if needed) of the file to be created

See Also

[plot](#)

Examples

```
## Not run:
save.to.eps(x, "out.eps")

## End(Not run)
```

scoring.func	<i>Read the scoring function used to learn the structure of a network.</i>
--------------	--

Description

Read the scoring function used in the [learn.structure](#) method. Outcome is meaningful only if the structure of a network has been learnt.

Usage

```
scoring.func(x)

## S4 method for signature 'BN'
scoring.func(x)
```

Arguments

x the [BN](#) object.

Value

the scoring function used.

scoring.func<-	<i>Set the scoring function used to learn the structure of a network.</i>
----------------	---

Description

Set the scoring function used in the [learn.structure](#) method.

Usage

```
scoring.func(x) <- value

## S4 replacement method for signature 'BN'
scoring.func(x) <- value
```

Arguments

x the [BN](#) object.
value the scoring function used.

Value

updated BN.

shd	<i>compute the Structural Hamming Distance between two adjacency matrices.</i>
-----	--

Description

Compute the Structural Hamming Distance between two adjacency matrices, that is, the distance, in terms of edges, between two network structures. The lower the shd, the more similar are the two network structures.

Usage

```
shd(g1, g2)
```

Arguments

g1	first adjacency matrix.
g2	second adjacency matrix.

show	<i>Show method for objects.</i>
------	---------------------------------

Description

The show method allows to provide a custom aspect for the output that is generated when the name of an instance is given as command in an R session.

Usage

```
show(object)
```

Arguments

object	an object.
--------	------------

struct.algo	<i>Read the algorithm used to learn the structure of a network.</i>
-------------	---

Description

Read the algorithm used in the [learn.structure](#) method. Outcome is meaningful only if the structure of a network has been learnt.

Usage

```
struct.algo(x)

## S4 method for signature 'BN'
struct.algo(x)
```

Arguments

x the [BN](#) object.

Value

the structure learning algorithm used.

struct.algo<-	<i>Set the algorithm used to learn the structure of a network.</i>
---------------	--

Description

Set the algorithm used in the [learn.structure](#) method.

Usage

```
struct.algo(x) <- value

## S4 replacement method for signature 'BN'
struct.algo(x) <- value
```

Arguments

x the [BN](#) object.
value the scoring function used.

Value

updated BN.

test.updated.bn	<i>check if an updated BN is present in an InferenceEngine.</i>
-----------------	---

Description

Check if an InferenceEngine actually contains an updated network, in order to provide the chance of a fallback and use the original network if no belief propagation has been performed.

Usage

```
test.updated.bn(x)

## S4 method for signature 'InferenceEngine'
test.updated.bn(x)
```

Arguments

x an InferenceEngine.

Value

TRUE if an updated network is contained in the InferenceEngine, FALSE otherwise.

Examples

```
## Not run:
dataset <- BNdataset("file.header", "file.data")
bn <- BN(dataset)
ie <- InferenceEngine(bn)
test.updated.bn(ie) # FALSE

observations(ie) <- list("observed.vars"=("A","G","X"), "observed.vals"=c(1,2,1))
ie <- belief.propagation(ie)
test.updated.bn(ie) # TRUE

## End(Not run)
```

tune.knn.impute	<i>tune the parameter k of the knn algorithm used in imputation.</i>
-----------------	--

Description

tune the parameter k of the knn algorithm used in imputation.

Usage

```
tune.knn.impute(data, cat.var = 1:ncol(data), k.min = 1, k.max = 20,
  frac.miss = 0.1, n.iter = 20, seed = 0)
```

Arguments

data	a data frame
cat.var	vector containing the categorical variables
k.min	minimum value for k
k.max	maximum value for k
frac.miss	fraction of missing values to add
n.iter	number of iterations for each k
seed	random seed

Value

matrix of error distributions

updated.bn	<i>get the updated BN object contained in an InferenceEngine.</i>
------------	---

Description

Return an updated network contained in an [InferenceEngine](#).

Usage

```
updated.bn(x)

## S4 method for signature 'InferenceEngine'
updated.bn(x)
```

Arguments

x	an InferenceEngine .
---	--------------------------------------

Value

the updated [BN](#) object contained in an [InferenceEngine](#).

updated.bn<-	<i>set the updated BN object contained in an InferenceEngine.</i>
--------------	---

Description

Add an updated network to an InferenceEngine.

Usage

```
updated.bn(x) <- value
```

```
## S4 replacement method for signature 'InferenceEngine'
updated.bn(x) <- value
```

Arguments

x	an InferenceEngine.
value	the updated BN object contained in an InferenceEngine.

variables	<i>get variables of an object.</i>
-----------	------------------------------------

Description

Get the list of variables (with their names) of a BN or BNDataset.

Usage

```
variables(x)
```

```
## S4 method for signature 'BN'
variables(x)
```

```
## S4 method for signature 'BNDataset'
variables(x)
```

Arguments

x	an object.
---	------------

Value

vector of the variables names of the desired object.

variables<-	<i>set variables of an object.</i>
-------------	------------------------------------

Description

Set the list of variable names in a [BN](#) or [BNDataset](#) object.

Usage

```
variables(x) <- value
```

```
## S4 replacement method for signature 'BN'
variables(x) <- value
```

```
## S4 replacement method for signature 'BNDataset'
variables(x) <- value
```

Arguments

x	an object.
value	vector containing the variable names of the object. Overwrites num.nodes slot if non-matching.

wpdag	<i>get the WPDAG of an object.</i>
-------	------------------------------------

Description

Return the weighted partially directed acyclic graph of a network, when available (e.g. when bootstrap on dataset is performed).

Usage

```
wpdag(x)
```

```
## S4 method for signature 'BN'
wpdag(x)
```

Arguments

x	an object.
---	------------

Value

matrix containing the WPDAG of the object.

wpdag.from.dag	<i>Initialize a WPDAG from a DAG.</i>
----------------	---------------------------------------

Description

Given a [BN](#) object with a dag, return a network with its wpdag set as the CPDAG computed starting from the dag.

Usage

```
wpdag.from.dag(x, layering = NULL)

## S4 method for signature 'BN'
wpdag.from.dag(x, layering = NULL)
```

Arguments

x	a BN object.
layering	vector containing the layers each node belongs to.

Value

a [BN](#) object with an initialized wpdag.

See Also

[dag.to.cpdag](#)

Examples

```
## Not run:
net <- learn.network(dataset, layering=layering)
wp.net <- wpdag.from.dag(net, layering)

## End(Not run)
```

wpdag<-	<i>set WPDAG of the object.</i>
---------	---------------------------------

Description

Set the weighted partially directed acyclic graph of a network (e.g. in case bootstrap on dataset is performed).

Usage

```
wpdag(x) <- value

## S4 replacement method for signature 'BN'
wpdag(x) <- value
```

Arguments

x	an object.
value	matrix containng the WPDAG of the object.

write.dsc	<i>Write a network saving it in a .dsc file.</i>
-----------	--

Description

Write a network on disk, saving it in a .dsc-formatted file.

Usage

```
write.dsc(x, path = "./")

## S4 method for signature 'BN'
write.dsc(x, path = "./")
```

Arguments

x	the BN object.
path	the relative or absolute path of the directory of the created file.

write.xgmml	<i>Write a network saving it in an XGMML file.</i>
-------------	--

Description

Write a network on disk, saving it in an XGMML file, for importing it in Cytoscape.

Usage

```
write.xgmml(x, filename = "./", write.wpdag = FALSE,
  node.col = rep("white", num.nodes(x)), frac = 0.2,
  max.weight = max(wpdag(x)))

## S4 method for signature 'BN'
write.xgmml(x, filename = "./", write.wpdag = FALSE,
  node.col = rep("white", num.nodes(x)), frac = 0.2,
  max.weight = max(wpdag(x)))
```

Arguments

<code>x</code>	the BN object.
<code>filename</code>	file name (with relative or absolute path) to be written.
<code>write.wpdag</code>	write the weighted PDAG computed using bootstrap samples or the MMPC structure algorithm, instead of the normaldag (default FALSE).
<code>node.col</code>	vector of colors for each node of the network (in R <code>colnames</code>).
<code>frac</code>	frac minimum fraction [0,1] of presence of an edge to be plotted (used in case of <code>write.wpdag=TRUE</code>).
<code>max.weight</code>	maximum possible weight of an edge (used in case of <code>write.wpdag=TRUE</code>).

Index

add.observations<-, 4
add.observations<-, InferenceEngine-method
 (add.observations<-), 4
asia, 4, 5
asia_10000, 5, 5

belief.propagation, 6
belief.propagation, InferenceEngine
 (belief.propagation), 6
belief.propagation, InferenceEngine-method
 (belief.propagation), 6
BN, 6–9, 17–19, 21, 23, 31, 36–42, 44, 48, 51,
 53, 54, 56–59, 61–68
BN (BN-class), 7
bn, 7
BN, BN-class (BN-class), 7
bn, InferenceEngine (bn), 7
bn, InferenceEngine-method (bn), 7
BN-class, 7
bn<-, 8
bn<-, InferenceEngine-method (bn<-), 8
BNdataset, 5, 7, 9, 11–13, 15, 16, 20, 21,
 24–30, 36–41, 44, 46, 47, 49, 52–54,
 57, 64, 65
BNdataset (BNdataset-class), 9
BNdataset, BNdataset-class
 (BNdataset-class), 9
BNdataset-class, 9
boot, 11
boot, BNdataset (boot), 11
boot, BNdataset, numeric-method (boot), 11
boots, 12, 24, 25, 28
boots, BNdataset (boots), 12
boots, BNdataset-method (boots), 12
boots<-, 13
boots<-, BNdataset-method (boots<-), 13
bootstrap, 10, 12, 13, 16
bootstrap, BNdataset (bootstrap), 13
bootstrap, BNdataset-method (bootstrap),
 13

build.junction.tree, 14, 34
build.junction.tree, InferenceEngine
 (build.junction.tree), 14
build.junction.tree, InferenceEngine-method
 (build.junction.tree), 14

child, 15, 16
child_NA_5000, 15, 15
complete, 16
complete, BNdataset (complete), 16
complete, BNdataset-method (complete), 16
cpts, 17
cpts, BN (cpts), 17
cpts, BN-method (cpts), 17
cpts<-, 17
cpts<-, BN-method (cpts<-), 17

dag, 18
dag, BN (dag), 18
dag, BN-method (dag), 18
dag.to.cpdag, 18, 66
dag<-, 19
dag<-, BN-method (dag<-), 19
data.file, 20, 20, 27
data.file, BNdataset (data.file), 20
data.file, BNdataset-method (data.file),
 20
data.file<-, 20
data.file<-, BNdataset-method
 (data.file<-), 20
discreteness, 21
discreteness, BN (discreteness), 21
discreteness, BN-method (discreteness),
 21
discreteness, BNdataset (discreteness),
 21
discreteness, BNdataset-method
 (discreteness), 21
discreteness<-, 22

- discreteness<-, BN-method
(discreteness<-), [22](#)
- discreteness<-, BNDataset-method
(discreteness<-), [22](#)
- em, [22](#)
- em, InferenceEngine, BNDataset (em), [22](#)
- em, InferenceEngine, BNDataset-method
(em), [22](#)
- get.most.probable.values, [23](#)
- get.most.probable.values, BN
(get.most.probable.values), [23](#)
- get.most.probable.values, BN-method
(get.most.probable.values), [23](#)
- get.most.probable.values, InferenceEngine
(get.most.probable.values), [23](#)
- get.most.probable.values, InferenceEngine-method
(get.most.probable.values), [23](#)
- has.boots, [12](#), [24](#), [25](#), [28](#)
- has.boots, BNDataset (has.boots), [24](#)
- has.boots, BNDataset-method (has.boots),
[24](#)
- has.imputed.boots, [12](#), [24](#), [24](#), [28](#)
- has.imputed.boots, BNDataset
(has.imputed.boots), [24](#)
- has.imputed.boots, BNDataset-method
(has.imputed.boots), [24](#)
- has.imputed.data, [25](#), [26](#), [30](#), [53](#)
- has.imputed.data, BNDataset
(has.imputed.data), [25](#)
- has.imputed.data, BNDataset-method
(has.imputed.data), [25](#)
- has.raw.data, [25](#), [26](#), [30](#), [53](#)
- has.raw.data, BNDataset (has.raw.data),
[26](#)
- has.raw.data, BNDataset-method
(has.raw.data), [26](#)
- header.file, [26](#)
- header.file, BNDataset (header.file), [26](#)
- header.file, BNDataset-method
(header.file), [26](#)
- header.file<-, [27](#)
- header.file<-, BNDataset-method
(header.file<-), [27](#)
- imp.boots, [12](#), [24](#), [25](#), [28](#)
- imp.boots, BNDataset (imp.boots), [28](#)
- imp.boots<-, [28](#)
- imp.boots<-, BNDataset-method
(imp.boots<-), [28](#)
- impute, [10](#), [15](#), [16](#), [29](#)
- impute, BNDataset (impute), [29](#)
- impute, BNDataset-method (impute), [29](#)
- imputed.data, [25](#), [26](#), [29](#), [30](#)
- imputed.data, BNDataset (imputed.data),
[29](#)
- imputed.data, BNDataset-method
(imputed.data), [29](#)
- imputed.data<-, [30](#)
- imputed.data<-, BNDataset-method
(imputed.data<-), [30](#)
- InferenceEngine, [4](#), [6–9](#), [14](#), [22](#), [23](#), [30](#),
[32–35](#), [43](#), [48](#), [50–52](#), [57](#), [58](#), [62–64](#)
- InferenceEngine
(InferenceEngine-class), [30](#)
- InferenceEngine, InferenceEngine-class
(InferenceEngine-class), [30](#)
- InferenceEngine-class, [30](#)
- initialize, BN-method (BN-class), [7](#)
- initialize, BNDataset-method
(BNDataset-class), [9](#)
- initialize, InferenceEngine-method
(InferenceEngine-class), [30](#)
- jpts, [32](#)
- jpts, InferenceEngine (jpts), [32](#)
- jpts, InferenceEngine-method (jpts), [32](#)
- jpts<-, [32](#)
- jpts<-, InferenceEngine-method (jpts<-),
[32](#)
- jt.cliques, [33](#)
- jt.cliques, InferenceEngine
(jt.cliques), [33](#)
- jt.cliques, InferenceEngine-method
(jt.cliques), [33](#)
- jt.cliques<-, [33](#)
- jt.cliques<-, InferenceEngine-method
(jt.cliques<-), [33](#)
- junction.tree, [34](#)
- junction.tree, InferenceEngine
(junction.tree), [34](#)
- junction.tree, InferenceEngine-method
(junction.tree), [34](#)
- junction.tree<-, [35](#)

junction.tree<- , InferenceEngine-method
 (junction.tree<-), 35

knn.impute, 35

layering, 36
 layering, BN (layering), 36
 layering, BN-method (layering), 36
 learn.network, 36
 learn.network, BN (learn.network), 36
 learn.network, BN-method
 (learn.network), 36
 learn.network, BNdataset
 (learn.network), 36
 learn.network, BNdataset-method
 (learn.network), 36
 learn.params, 38, 39
 learn.params, BN, BNdataset
 (learn.params), 39
 learn.params, BN, BNdataset-method
 (learn.params), 39
 learn.structure, 38, 40, 59, 61
 learn.structure, BN, BNdataset
 (learn.structure), 40
 learn.structure, BN, BNdataset-method
 (learn.structure), 40

marginals, 43
 marginals, InferenceEngine (marginals),
 43
 marginals, InferenceEngine-method
 (marginals), 43

name, 44
 name, BN (name), 44
 name, BN-method (name), 44
 name, BNdataset (name), 44
 name, BNdataset-method (name), 44
 name<-, 44
 name<-, BN-method (name<-), 44
 name<-, BNdataset-method (name<-), 44
 node.sizes, 45
 node.sizes, BN (node.sizes), 45
 node.sizes, BN-method (node.sizes), 45
 node.sizes, BNdataset (node.sizes), 45
 node.sizes, BNdataset-method
 (node.sizes), 45
 node.sizes<-, 45
 node.sizes<-, BN-method (node.sizes<-),
 45

node.sizes<-, BNdataset-method
 (node.sizes<-), 45
 num.boots, 46
 num.boots, BNdataset (num.boots), 46
 num.boots, BNdataset-method (num.boots),
 46
 num.boots<-, 46
 num.boots<-, BNdataset-method
 (num.boots<-), 46
 num.items, 47
 num.items, BNdataset (num.items), 47
 num.items, BNdataset-method (num.items),
 47
 num.items<-, 47
 num.items<-, BNdataset-method
 (num.items<-), 47
 num.nodes, 48, 49
 num.nodes, BN (num.nodes), 48
 num.nodes, BN-method (num.nodes), 48
 num.nodes, InferenceEngine (num.nodes),
 48
 num.nodes, InferenceEngine-method
 (num.nodes), 48
 num.nodes<-, 48
 num.nodes<-, BN-method (num.nodes<-), 48
 num.nodes<-, InferenceEngine-method
 (num.nodes<-), 48
 num.variables, 49
 num.variables, BNdataset
 (num.variables), 49
 num.variables, BNdataset-method
 (num.variables), 49
 num.variables<-, 49
 num.variables<-, BNdataset-method
 (num.variables<-), 49

observations, 50
 observations, InferenceEngine
 (observations), 50
 observations, InferenceEngine-method
 (observations), 50
 observations<-, 50
 observations<-, InferenceEngine-method
 (observations<-), 50

plot, 51, 58
 plot, BN (plot), 51
 plot.BN (plot), 51
 plot.BN, BN (plot), 51

- print, 52
- print, BN (print), 52
- print, BN-method (print), 52
- print, BNdataset (print), 52
- print, BNdataset-method (print), 52
- print, InferenceEngine (print), 52
- print, InferenceEngine-method (print), 52
- raw.data, 25, 26, 30, 52, 53
- raw.data, BNdataset (raw.data), 52
- raw.data, BNdataset-method (raw.data), 52
- raw.data<-, 53
- raw.data<-, BNdataset-method (raw.data<-), 53
- read.bif, 53
- read.bif, character (read.bif), 53
- read.bif, character-method (read.bif), 53
- read.dataset, 10, 30, 53, 54
- read.dataset, BNdataset, character, character (read.dataset), 54
- read.dataset, BNdataset, character, character-method (read.dataset), 54
- read.dsc, 55
- read.dsc, character (read.dsc), 55
- read.dsc, character-method (read.dsc), 55
- read.net, 56
- read.net, character (read.net), 56
- read.net, character-method (read.net), 56
- sample.dataset, 57
- sample.dataset, BN (sample.dataset), 57
- sample.dataset, BN-method (sample.dataset), 57
- sample.dataset, InferenceEngine (sample.dataset), 57
- sample.dataset, InferenceEngine-method (sample.dataset), 57
- sample.row, 57
- sample.row, BN (sample.row), 57
- sample.row, BN-method (sample.row), 57
- save.to.eps, 58
- save.to.eps, BN, character (save.to.eps), 58
- save.to.eps, BN, character-method (save.to.eps), 58
- scoring.func, 59
- scoring.func, BN (scoring.func), 59
- scoring.func, BN-method (scoring.func), 59
- scoring.func<-, 59
- scoring.func<-, BN-method (scoring.func<-), 59
- shd, 60
- show, 60
- show, AllTheClasses-method (show), 60
- show, BN-method (show), 60
- show, BNdataset-method (show), 60
- show, InferenceEngine-method (show), 60
- struct.algo, 61
- struct.algo, BN (struct.algo), 61
- struct.algo, BN-method (struct.algo), 61
- struct.algo<-, 61
- struct.algo<-, BN-method (struct.algo<-), 61
- test.updated.bn, 62
- test.updated.bn, InferenceEngine (test.updated.bn), 62
- test.updated.bn, InferenceEngine-method (test.updated.bn), 62
- tune.knn.impute, 62
- updated.bn, 63
- updated.bn, InferenceEngine (updated.bn), 63
- updated.bn, InferenceEngine-method (updated.bn), 63
- updated.bn<-, 64
- updated.bn<-, InferenceEngine-method (updated.bn<-), 64
- variables, 64
- variables, BN (variables), 64
- variables, BN-method (variables), 64
- variables, BNdataset (variables), 64
- variables, BNdataset-method (variables), 64
- variables<-, 65
- variables<-, BN-method (variables<-), 65
- variables<-, BNdataset-method (variables<-), 65
- wpdag, 65
- wpdag, BN (wpdag), 65
- wpdag, BN-method (wpdag), 65
- wpdag.from.dag, 19, 66
- wpdag.from.dag, BN (wpdag.from.dag), 66
- wpdag.from.dag, BN-method (wpdag.from.dag), 66

wpdag<-, [66](#)
wpdag<- ,BN-method (wpdag<-), [66](#)
write.dsc, [67](#)
write.dsc,BN (write.dsc), [67](#)
write.dsc,BN-method (write.dsc), [67](#)
write.xgmml, [67](#)
write.xgmml,BN (write.xgmml), [67](#)
write.xgmml,BN-method (write.xgmml), [67](#)