

Package ‘rearr’

October 26, 2020

Title Rearranging Data

Version 0.1.0

Description Arrange data by a set of methods. Use rearrangers to reorder data points and mutators to change their values. From basic utilities, to centering the greatest value, to swirling in 3-dimensional space, 'rearr' enables creativity when plotting and experimenting with data.

License MIT + file LICENSE

URL <https://github.com/ludvigolsen/rearr>

BugReports <https://github.com/ludvigolsen/rearr/issues>

Depends R (>= 3.5)

Imports checkmate (>= 2.0.0),
dplyr (>= 0.8.5),
lifecycle,
plyr,
purrr (>= 0.3.4),
rlang (>= 0.4.7),
stats,
utils

Suggests covr,
ggplot2,
knitr,
plotly,
testthat,
tidyr,
xpectr (>= 0.4.0)

RdMacros lifecycle

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

R topics documented:

angle	2
apply_transformation_matrix	4

center_max	7
center_min	9
centroid	10
circularize	12
closest_to	14
cluster_groups	17
create_dimming_fn	21
create_n_fn	22
create_origin_fn	24
degrees_to_radians	25
dim_values	26
distance	29
expand_distances	31
expand_distances_each	36
flip_values	41
furthest_from	44
generate_clusters	47
hexagonalize	49
is_most_centered	51
median_index	53
midrange	54
min_max_scale	55
most_centered	57
pair_extremes	58
position_max	61
position_min	63
rev_windows	64
roll_elements	66
roll_values	68
rotate_2d	72
rotate_3d	74
shear_2d	78
shear_3d	81
square	85
swirl_2d	88
swirl_3d	91
to_unit_length	96
transfer_centroids	98
triangularize	99
vector_length	102

Index**105**

angle*Calculate the angle to an origin*

Description

Experimental

Calculates the angle between each data point (x_2, y_2) and the origin (x_1, y_1) with:

$$\text{atan2}(y_2 - y_1, x_2 - x_1)$$

And converts to degrees $[0-360)$, measured counterclockwise from the $\{x > x_1, y = y_1\}$ line.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and finding the angle to e.g. the centroid of each group.

Usage

```
angle(
  data,
  x_col = NULL,
  y_col = NULL,
  origin = NULL,
  origin_fn = NULL,
  degrees_col_name = ".degrees",
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
x_col	Name of x column in `data`. If NULL and `data` is a vector, the index of `data` is used. If `data` is a data.frame, it must be specified.
y_col	Name of y column in `data`. If `data` is a data.frame, it must be specified.
origin	Coordinates of the origin to calculate angle to. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
degrees_col_name	Name of new column with the degrees.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with the additional columns (degrees and origin coordinates).

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other measuring functions: [distance\(\)](#), [vector_length\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = runif(20),
  "y" = runif(20),
  "g" = rep(1:4, each = 5)
)

# Calculate angles in the two dimensions (x and y)
# With the origin at x=0.5, y=0.5
df_angles <- angle(
  data = df,
  x_col = "x",
  y_col = "y",
  origin = c(0.5, 0.5)
)
df_angles

# Plot points with degrees
# Degrees are measured counterclockwise around the
# positive side of the x-axis
df_angles %>%
  ggplot(aes(x = x, y = y, color = .degrees)) +
  geom_segment(aes(x = 0.5, xend = 1, y = 0.5, yend = 0.5), color = "magenta") +
  geom_point() +
  theme_minimal()

# Calculate angles to the centroid for each group in 'g'
angle(
  data = dplyr::group_by(df, g),
  x_col = "x",
  y_col = "y",
  origin_fn = centroid
)
```

apply_transformation_matrix

Apply transformation matrix to a set of columns

Description

Experimental

Perform [matrix multiplication](#) with a transformation matrix and a set of `data.frame` columns.

The data points in ``data`` are moved prior to the transformation, to bring the origin to 0 in all dimensions. After the transformation, the inverse move is applied to bring the origin back to its original position. See ``Details`` section.

The columns in ``data`` are transposed, making the operation (without the origin movement):

$$matdata[,cols]^T$$

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped `data.frame` and transforming around e.g. the centroid of each group.

Usage

```
apply_transformation_matrix(
  data,
  mat,
  cols,
  origin = NULL,
  origin_fn = NULL,
  suffix = "_transformed",
  keep_original = TRUE,
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

<code>data</code>	<code>data.frame</code> or vector.
<code>mat</code>	Transformation matrix. Must have the same number of columns as <code>`cols`</code> .
<code>cols</code>	Columns to mutate values of. Must be specified when <code>`data`</code> is a <code>data.frame</code> .
<code>origin</code>	Coordinates of the origin. Vector with the same number of elements as <code>`cols`</code> (i.e. <code>origin_x</code> , <code>origin_y</code> , ...). Ignored when <code>`origin_fn`</code> is not <code>NULL</code> .
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of <code>`cols`</code> . Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
<code>suffix</code>	Suffix to add to the names of the generated columns. Use an empty string (i.e. <code>""</code>) to overwrite the original columns.
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>origin_col_name</code>	Name of new column with the origin coordinates. If <code>NULL</code> , no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Details

Example with 2 columns (x, y) and a 2x2 transformation matrix:

- Move origin to (0, 0):
`x = x - origin_x`
`y = y - origin_y`
- Convert to transposed matrix:
`data_mat = rbind(x, y)`
- Matrix multiplication:
`transformed = mat %*% data_mat`
- Move origin to original position (after extraction from transformed):
`x = x + origin_x`
`y = y + origin_y`

Value

`data.frame` (tibble) with the new, transformed columns and the origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: `cluster_groups()`, `dim_values()`, `expand_distances_each()`, `expand_distances()`, `flip_values()`, `roll_values()`, `rotate_2d()`, `rotate_3d()`, `shear_2d()`, `shear_3d()`, `swirl_2d()`, `swirl_3d()`

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(3)

# Create a data frame
df <- data.frame(
  "x" = 1:12,
  "y" = 13:24,
  "z" = runif(12),
  "g" = c(
    1, 1, 1, 1, 2, 2,
    2, 2, 3, 3, 3, 3
  )
)

# Apply identity matrix
mat <- matrix(c(1, 0, 0, 0, 1, 0, 0, 0, 1), nrow = 3)
apply_transformation_matrix(
  data = df,
```

```

    mat = mat,
    cols = c("x", "y", "z"),
    origin = c(0, 0, 0)
  )

  # Apply rotation matrix
  # 90 degrees around z-axis
  # Origin is the most centered point
  mat <- matrix(c(0, 1, 0, -1, 0, 0, 0, 0, 1), nrow = 3)
  res <- apply_transformation_matrix(
    data = df,
    mat = mat,
    cols = c("x", "y", "z"),
    origin_fn = most_centered
  )

  # Plot the rotation
  # z wasn't changed so we plot x and y
  res %>%
    ggplot(aes(x = x, y = y)) +
    geom_point() +
    geom_point(aes(x = x_transformed, y = y_transformed)) +
    theme_minimal()

  # Apply rotation matrix to grouped data frame
  # Around centroids
  # Same matrix as before
  res <- apply_transformation_matrix(
    data = dplyr::group_by(df, g),
    mat = mat,
    cols = c("x", "y", "z"),
    origin_fn = centroid
  )

  # Plot the rotation
  res %>%
    ggplot(aes(x = x, y = y, color = g)) +
    geom_point() +
    geom_point(aes(x = x_transformed, y = y_transformed)) +
    theme_minimal()

```

center_max

*Centers the highest value with values decreasing around it***Description****Experimental**

The highest value is positioned in the middle with the other values decreasing around it.

Example:

The column values:

```
c(1,2,3,4, 5)
```

are **ordered as:**

```
c(1,3, 5,4,2)
```

Usage

```
center_max(data, col = NULL, shuffle_sides = FALSE)
```

Arguments

data	data.frame or vector.
col	Column to create sorting factor by. When NULL and `data` is a data.frame, the row numbers are used.
shuffle_sides	Whether to shuffle which elements are left and right of the center. (Logical)

Value

The sorted data.frame (tibble) / vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: [center_min\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [pair_extremes\(\)](#), [position_max\(\)](#), [position_min\(\)](#), [rev_windows\(\)](#), [roll_elements\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Center by the index (row numbers)
center_max(df)

# Center by each of the columns
center_max(df, col = "A")
center_max(df, col = "B")
center_max(df, col = "C")

# Randomize which elements are left and right of the center
center_max(df, col = "A", shuffle_sides = TRUE)
```



```
# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  center_max(col = "A")

# Plot the centered values
plot(x = 1:10, y = center_max(df, col = "B")$B)
plot(x = 1:10, y = center_max(df, col = "B", shuffle_sides = TRUE)$B)
```

center_min

Centers the lowest value with values increasing around it

Description

Experimental

The lowest value is positioned in the middle with the other values increasing around it.

Example:

The column values:

```
c(1,2,3,4,5)
```

are **ordered as**:

```
c(5,3, 1,2,4)
```

Usage

```
center_min(data, col = NULL, shuffle_sides = FALSE)
```

Arguments

data	data.frame or vector.
col	Column to create sorting factor by. When NULL and `data` is a data.frame, the row numbers are used.
shuffle_sides	Whether to shuffle which elements are left and right of the center. (Logical)

Value

The sorted data.frame (tibble) / vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: [center_max\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [pair_extremes\(\)](#), [position_max\(\)](#), [position_min\(\)](#), [rev_windows\(\)](#), [roll_elements\(\)](#)

Examples

```

# Attach packages
library(rearrrr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Center by the index (row numbers)
center_min(df)

# Center by each of the columns
center_min(df, col = "A")
center_min(df, col = "B")
center_min(df, col = "C")

# Randomize which elements are left and right of the center
center_min(df, col = "A", shuffle_sides = TRUE)

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  center_min(col = "A")

# Plot the centered values
plot(x = 1:10, y = center_min(df, col = "B")$B)
plot(x = 1:10, y = center_min(df, col = "B", shuffle_sides = TRUE)$B)

```

centroid

*Find the coordinates for the centroid***Description****Experimental**

Calculates the mean of each passed vector/column.

Usage

```
centroid(..., cols = NULL, na.rm = FALSE)
```

Arguments

<code>...</code>	Numeric vectors or a single <code>data.frame</code> .
<code>cols</code>	Names of columns to use when <code>`...`</code> is a single <code>data.frame</code> .
<code>na.rm</code>	Whether to ignore missing values when calculating means. (Logical)

Value

Means of the supplied vectors/columns. Either as a vector or a `data.frame`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other coordinate functions: [create_origin_fn\(\)](#), [is_most_centered\(\)](#), [midrange\(\)](#), [most_centered\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Find centroid coordinates
# Aka. the means of each vector
centroid(x, y, z)

#
# For data.frames
#

# Create data frame
df <- data.frame(
  "x" = x,
  "y" = y,
  "z" = z,
  "g" = rep(1:2, each = 5)
)

# Find centroid coordinates
# Aka. the means of each column
centroid(df, cols = c("x", "y", "z"))

# When 'df' is grouped
df %>%
  dplyr::group_by(g) %>%
  centroid(cols = c("x", "y", "z"))
```

circularize

*Create x-coordinates so the points form a circle***Description****Experimental**

Create the x-coordinates for a vector of y-coordinates such that they form a circle.

This will likely look most like a circle when the y-coordinates are somewhat equally distributed, e.g. a uniform distribution.

Usage

```
circularize(
  data,
  y_col = NULL,
  .min = NULL,
  .max = NULL,
  offset_x = 0,
  keep_original = TRUE,
  x_col_name = ".circle_x",
  degrees_col_name = ".degrees",
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

<code>data</code>	data.frame or vector.
<code>y_col</code>	Name of column in `data` with y-coordinates to create x-coordinates for.
<code>.min</code>	Minimum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>.max</code>	Maximum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>offset_x</code>	Value to offset the x-coordinates by.
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>x_col_name</code>	Name of new column with the x-coordinates.
<code>degrees_col_name</code>	Name of new column with the angles in degrees. If NULL, no column is added. Angling is counterclockwise around $(0, 0)$ and starts at $(\max(x), 0)$.
<code>origin_col_name</code>	Name of new column with the origin coordinates (center of circle). If NULL, no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with the added x-coordinates and the angle in degrees.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other forming functions: [hexagonalize\(\)](#), [square\(\)](#), [triangularize\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "y" = runif(200),
  "g" = factor(rep(1:5, each = 40))
)

# Circularize 'y'
df_circ <- circularize(df, y_col = "y")
df_circ

# Plot circle
df_circ %>%
  ggplot(aes(x = .circle_x, y = y, color = .degrees)) +
  geom_point() +
  theme_minimal()

#
# Grouped circularization
#

# Circularize 'y' for each group
# First cluster the groups a bit to move the
# circles away from each other
df_circ <- df %>%
  cluster_groups(
    cols = "y",
    group_cols = "g",
    suffix = "",
    overwrite = TRUE
  ) %>%
  dplyr::group_by(g) %>%
  circularize(
    y_col = "y",
    overwrite = TRUE
  )

# Plot circles
df_circ %>%
```

```

ggplot(aes(x = .circle_x, y = y, color = g)) +
  geom_point() +
  theme_minimal()

#
# Specifying minimum value
#

# Specify minimum value manually
df_circ <- circularize(df, y_col = "y", .min = -2)
df_circ

# Plot circle
df_circ %>%
  ggplot(aes(x = .circle_x, y = y, color = .degrees)) +
  geom_point() +
  theme_minimal()

#
# Multiple circles by contraction
#

# Start by circularizing 'y'
df_circ <- circularize(df, y_col = "y")

# Contract '.circle_x' and 'y' towards the centroid
# To contract with multiple multipliers at once,
# we wrap the call in purrr::map_dfr
df_expanded <- purrr::map_dfr(
  .x = 1:10 / 10,
  .f = function(mult) {
    expand_distances(
      data = df_circ,
      cols = c(".circle_x", "y"),
      multiplier = mult,
      origin_fn = centroid,
      overwrite = TRUE
    )
  }
)
df_expanded

df_expanded %>%
  ggplot(aes(
    x = .circle_x_expanded, y = y_expanded,
    color = .degrees, alpha = .multiplier
  )) +
  geom_point() +
  theme_minimal()

```

Description

Experimental

Values are ordered by how close they are to the origin.

In 1d (when `cols` has length 1), the origin can be thought of as a target value. In n dimensions, the origin can be thought of as coordinates.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped `data.frame` and ordering the rows by their distance to the centroid of each group.

The `*_vec()` version takes and returns a vector.

Example:

The column values:

```
c(1,2,3,4,5)
```

and `origin = 2`

are **ordered as**:

```
c(2,1,3,4,5)
```

Usage

```
closest_to(
  data,
  cols = NULL,
  origin = NULL,
  origin_fn = NULL,
  shuffle_ties = FALSE,
  origin_col_name = ".origin",
  distance_col_name = ".distance",
  overwrite = FALSE
)
```

```
closest_to_vec(data, origin = NULL, origin_fn = NULL, shuffle_ties = FALSE)
```

Arguments

<code>data</code>	<code>data.frame</code> or vector.
<code>cols</code>	Column(s) to create sorting factor by. When <code>NULL</code> and `data` is a <code>data.frame</code> , the row numbers are used.
<code>origin</code>	Coordinates of the origin to calculate distances to. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not <code>NULL</code> .
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
<code>shuffle_ties</code>	Whether to shuffle elements with the same distance to the origin. (Logical)

`origin_col_name` Name of new column with the origin coordinates. If NULL, no column is added.

`distance_col_name` Name of new column with the distances to the origin. If NULL, no column is added.

`overwrite` Whether to allow overwriting of existing columns. (Logical)

Value

The sorted `data.frame` (`tibble`) / `vector`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: `center_max()`, `center_min()`, `furthest_from()`, `pair_extremes()`, `position_max()`, `position_min()`, `rev_windows()`, `roll_elements()`

Other distance functions: `dim_values()`, `distance()`, `expand_distances_each()`, `expand_distances()`, `furthest_from()`, `swirl_2d()`, `swirl_3d()`

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Closest to 3 in a vector
closest_to_vec(1:10, origin = 3)

# Closest to the third row (index of data.frame)
closest_to(df, origin = 3)$index

# By each of the columns
closest_to(df, cols = "A", origin = 3)$A
closest_to(df, cols = "A", origin_fn = most_centered)$A
closest_to(df, cols = "B", origin = 0.5)$B
closest_to(df, cols = "B", origin_fn = centroid)$B
```



```

# Shuffle the elements with the same distance to the origin
closest_to(df,
  cols = "A",
  origin_fn = create_origin_fn(median),
  shuffle_ties = TRUE
)$A

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  closest_to(
    cols = "A",
    origin_fn = create_origin_fn(median)
  )

# Plot the rearranged values
plot(
  x = 1:10,
  y = closest_to(df,
    cols = "B",
    origin_fn = create_origin_fn(median)
  )$B,
  xlab = "Position",
  ylab = "B"
)
plot(
  x = 1:10,
  y = closest_to(df,
    cols = "A",
    origin_fn = create_origin_fn(median),
    shuffle_ties = TRUE
  )$A,
  xlab = "Position",
  ylab = "A"
)

# In multiple dimensions
df %>%
  closest_to(cols = c("A", "B"), origin_fn = most_centered)

```

cluster_groups

Move data points into clusters

Description

Experimental

Transform values such that the elements in each group move closer to their centroid.

Usage

```

cluster_groups(
  data,
  cols,

```

```

group_cols = NULL,
scale_min_fn = function(x) { quantile(x, 0.025) },
scale_max_fn = function(x) { quantile(x, 0.975) },
keep_centroids = FALSE,
multiplier = 0.05,
suffix = "_clustered",
keep_original = TRUE,
overwrite = FALSE
)

```

Arguments

data	data.frame. If <code>group_cols</code> is NULL, it must be grouped with <code>dplyr::group_by()</code> .
cols	Names of columns in <code>data</code> to mutate. Each column is considered a dimension to contract distances in.
group_cols	Names of grouping columns in <code>data</code> . Must be distinct from the names in <code>cols</code> . If NULL and <code>data</code> is grouped, those groups are used instead.
scale_min_fn, scale_max_fn	Function to find the minimum/maximum value in the original data when rescaling the contracted data. Input: A numeric vector. Output: A numeric scalar.
keep_centroids	Whether to ensure the clusters have their original centroids. (Logical)
multiplier	Numeric constant to multiply the distance to the group centroid by. A smaller value makes the clusters more compact and vice versa.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Details

- Contracts the distance from each data point to the centroid of its group.
- Performs MinMax scaling such that the scale of the data points is *similar* to the original data.
- If enabled (not default), the centroids are moved to the original centroids.

Value

data.frame (tibble) with the clustered columns.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other clustering functions: [generate_clusters\(\)](#), [transfer_centroids\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(2)

# Create a data frame
df <- data.frame(
  "x" = runif(50),
  "y" = runif(50),
  "z" = runif(50),
  "g" = rep(c(1, 2, 3, 4, 5), each = 10)
)

# Move the data points into clusters
cluster_groups(df,
  cols = c("x", "y"),
  group_col = "g"
)
cluster_groups(df,
  cols = c("x", "y"),
  group_col = "g",
  multiplier = 0.1
)
cluster_groups(df,
  cols = c("x"),
  group_col = "g",
  multiplier = 0.1
)

#
# Plotting clusters
#

# Cluster x and y for each group in g
df_clustered <- cluster_groups(
  data = df,
  cols = c("x", "y"),
  group_col = "g"
)

# Plot the clusters over the original data points
# As we work with random data, the cluster might overlap
ggplot(
  df_clustered,
  aes(x = x_clustered, y = y_clustered, color = factor(g))
)
```

```

) +
  # Original data
  geom_point(aes(x = x, y = y), alpha = 0.3, size = 0.8) +
  # Clustered data
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "g")

#
# Maintain original group centroids
#

df_clustered <- cluster_groups(
  data = df,
  cols = c("x", "y"),
  group_col = "g",
  keep_centroids = TRUE
)

# Plot the clusters over the original data points
# As we work with random data, the cluster might overlap
ggplot(
  df_clustered,
  aes(x = x_clustered, y = y_clustered, color = factor(g))
) +
  # Original data
  geom_point(aes(x = x, y = y), alpha = 0.3, size = 0.8) +
  # Clustered data
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "g")

#
# Three dimensions
#

# Cluster in 3d
df_clustered <- cluster_groups(
  data = df,
  cols = c("x", "y", "z"),
  group_col = "g"
)

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_clustered$x_clustered,
  y = df_clustered$y_clustered,
  z = df_clustered$z_clustered,
  type = "scatter3d",
  mode = "markers",
  color = df_clustered$g
)

## End(Not run)

```

create_dimming_fn	Create dimming_fn function
-------------------	----------------------------

Description

Experimental

Creates a function that takes 2 inputs (`x`, `d`) and performs the operation:

$$x * (numerator / ((add_to_distance + d)^{exponent}))$$

Here, `x` is the current value and `d` is its distance to an origin. The greater the distance, the more we will dim the value of `x`.

With the default values, the returned function is:

```
function(x,d){
  x * (1 / ((1 + d) ^ 2))
}
```

Usage

```
create_dimming_fn(numerator = 1, exponent = 2, add_to_distance = 1)
```

Arguments

numerator	The numerator. Defaults to 1.
exponent	The exponent. Defaults to 2.
add_to_distance	Constant to add to the distance before exponentiation. Ensures dimming even when the distance (d) is below 1. Defaults to 1.

Value

Function with the arguments x and d, with both expected to be numeric vectors. More specifically:

```
function(x,d){
  x * (numerator / ((add_to_distance + d) ^ exponent))
}
```

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other function creators: [create_n_fn\(\)](#), [create_origin_fn\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(ggplot2)

# Set seed
set.seed(1)

# Create two vectors
x <- runif(10)
d <- runif(10, max = 0.5)

# Create dimming_fn with an add_to_distance of 0
# Note: In practice this risks zero-division
non_smoothed_dimming_fn <- create_dimming_fn(add_to_distance = 0)
non_smoothed_dimming_fn
as.list(environment(non_smoothed_dimming_fn))

# Use median_origin_fn
non_smoothed_dimming_fn(x, d)

# Plotting the dimming

# Create data.frame with distance-based dimming
df <- data.frame(
  "x" = 1,
  "d" = 1:10
)
df$x_dimmed <- non_smoothed_dimming_fn(df$x, df$d)

# Plot the dimming
ggplot(df, aes(x=d, y=x_dimmed)) +
  geom_point() +
  geom_line() +
  theme_minimal()
```

create_n_fn

Create n_fn function

Description

Experimental

Creates a function that applies a supplied function to all input vectors, or their indices, and rounds the results.

As used with [roll_elements\(\)](#). E.g. to find the the median index in a subset of a grouped data.frame.

Usage

```
create_n_fn(fn, use_index = FALSE, negate = FALSE, round_fn = round, ...)
```

Arguments

fn	Function to apply to each dimension. Should return a numeric scalar.
use_index	Whether to apply `fn` to the <i>indices</i> of the vectors. (Logical) The indices are created with seq_along(x).
negate	Whether to negate the result. I.e. to multiply it with -1. (Logical)
round_fn	Function for rounding results of `fn`. Rounding is done <i>prior</i> to negation. E.g. round , floor , or ceiling . To avoid rounding, supply identity .
...	Arguments for `fn`. E.g. `na.rm = TRUE`.

Value

Function with the dots (`...`) argument that applies the `fn` function to each element in `...` (or indices thereof) (usually one vector per dimension). The results are rounded with `round_fn`.

Note: The dots argument in the generated function should not to be confused with the dots argument in `create_n_fn()`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other n functions: [median_index\(\)](#)

Other function creators: [create_dimming_fn\(\)](#), [create_origin_fn\(\)](#)

Examples

```
# Attach packages
library(rearr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Create n_fn that gets the median index
# and rounds down with floor()
median_index_fn <- create_n_fn(median, use_index = TRUE, round_fn = floor)

# Use median_index_fn
median_index_fn(x, y, z)

# Create n_fn that gets the median of each dimension
median_n_fn <- create_n_fn(median)

# Use median_n_fn
median_n_fn(x, y, z)
```

```

# Should be the same as
round(c(median(x), median(y), median(z)))

# Use mean and ignore missing values
mean_n_fn <- create_n_fn(mean, na.rm = TRUE)

# Add missing values
x[[2]] <- NA
y[[5]] <- NA

# Use mean_n_fn
mean_n_fn(x, y, z)

# Should be the same as
round(c(
  mean(x, na.rm = TRUE),
  mean(y, na.rm = TRUE),
  mean(z, na.rm = TRUE)
))

```

create_origin_fn	<i>Create origin_fn function</i>
------------------	----------------------------------

Description

Experimental

Creates a function that applies a supplied function to all input vectors.

Usage

```
create_origin_fn(fn, ...)
```

Arguments

fn	Function to apply to each dimension. Should return a numeric scalar.
...	Arguments for `fn`. E.g. `na.rm = TRUE`.

Value

Function with the dots (...) argument that applies the `fn` function to each element in ... (usually one vector per dimension).

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other coordinate functions: [centroid\(\)](#), [is_most_centered\(\)](#), [midrange\(\)](#), [most_centered\(\)](#)
 Other function creators: [create_dimming_fn\(\)](#), [create_n_fn\(\)](#)

Examples

```
# Attach packages
library(rearrrr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Create origin_fn that gets the median of each dimension
median_origin_fn <- create_origin_fn(median)

# Use median_origin_fn
median_origin_fn(x, y, z)

# Should be the same as
c(median(x), median(y), median(z))

# Use mean and ignore missing values
mean_origin_fn <- create_origin_fn(mean, na.rm = TRUE)

# Add missing values
x[[2]] <- NA
y[[5]] <- NA

# Use mean_origin_fn
mean_origin_fn(x, y, z)

# Should be the same as
c(mean(x, na.rm = TRUE),
  mean(y, na.rm = TRUE),
  mean(z, na.rm = TRUE)
)
```

degrees_to_radians	<i>Conversion between radians and degrees</i>
--------------------	---

Description**Experimental**

Convert degrees to radians or radians to degrees.

Usage

```
degrees_to_radians(degrees)
```

```
radians_to_degrees(radians)
```

Arguments

degrees	vector of degrees to convert to radians with	$\text{'degrees'} * (\pi/180)$
radians	vector of radians to convert to degrees with	$\text{'radians'} / (\pi/180)$

Value

vector with converted degrees/radians.
Missing values (NAs) are returned as they are.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Degrees to radians
degrees_to_radians(c(90, 180, 270))

# Radians to degrees
radians_to_degrees(c(pi / 2, pi, 1.5 * pi))

# Get back the original degrees
radians_to_degrees(degrees_to_radians(c(90, 180, 270)))
```

dim_values	<i>Dim values of a dimension based on the distance to an n-dimensional origin</i>
------------	---

Description**Experimental**

Dims the values in the dimming dimension (last by default) based on the data point's distance to the origin.

Distance is calculated as:

$$d(P1, P2) = \text{sqrt}((x2 - x1)^2 + (y2 - y1)^2 + (z2 - z1)^2 + \dots)$$

The default `dimming_fn` multiplies by the inverse-square of $1 + \text{distance}$ and is calculated as:

$$\text{dimming_fn}(x, d) = x * (1 / (1 + d)^2)$$

Where x is the value in the dimming dimension. The +1 is added to ensure that values are dimmed even when the distance is below 1. The quickest way to change the exponent or the +1 is with [create_dimming_fn\(\)](#).

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and dimming around e.g. the centroid of each group.

Usage

```
dim_values(
  data,
  cols,
  dimming_fn = create_dimming_fn(numerator = 1, exponent = 2, add_to_distance = 1),
  origin = NULL,
  origin_fn = NULL,
  dim_col = tail(cols, 1),
  suffix = "_dimmed",
  keep_original = TRUE,
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to calculate distances from. The dimming column (`dim_col`) is dimmed based on all the columns. Each column is considered a dimension. N.B. when the dimming dimension is included in `cols`, it is used in the distance calculation as well.
dimming_fn	Function for calculating the dimmed values. Input: Two (2) input arguments: <ol style="list-style-type: none"> 1. A numeric vector with the values in the dimming dimension. 2. A numeric vector with corresponding distances to the origin. Output: A numeric vector with the same length as the input vectors. E.g.: <pre>function(x,d){ x * (1 / ((1 + d) ^ 2)) }</pre> This kind of dimming function can be created with <code>create_dimming_fn()</code> , which for instance makes it easy to change the exponent (the 2 above).
origin	Coordinates of the origin to dim around. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. `create_origin_fn(median)` would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
dim_col	Name of column to dim. Default is the last column in `cols`. When the `dim_col` is not present in `cols`, it is not used in the distance calculation.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.

keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Details

- Calculates distances to origin with:

$$d(P1, P2) = \text{sqrt}((x2 - x1)^2 + (y2 - y1)^2 + (z2 - z1)^2 + \dots)$$

- Applies the `dimming_fn` to the `dim_col` based on the distances.

Value

`data.frame` (tibble) with the dimmed column, along with the origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other distance functions: [closest_to\(\)](#), [distance\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [furthest_from\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(7)

# Create a data frame with clusters
df <- generate_clusters(
  num_rows = 70,
  num_cols = 3,
  num_clusters = 5,
  compactness = 1.6
) %>%
  dplyr::rename(x = D1, y = D2, z = D3) %>%
  dplyr::mutate(o = 1)

# Dim the values in the z column
dim_values(
  data = df,
```

```

    cols = c("x", "y", "z"),
    origin = c(0.5, 0.5, 0.5)
  )

  # Dim the values in the `o` column (all 1s)
  # around the centroid
  dim_values(
    data = df,
    cols = c("x", "y"),
    dim_col = "o",
    origin_fn = centroid
  )

  # Specify dimming_fn
  # around the centroid
  dim_values(
    data = df,
    cols = c("x", "y"),
    dim_col = "o",
    origin_fn = centroid,
    dimming_fn = function(x, d) {
      x * 1 / (2^(1 + d))
    }
  )

  #
  # Dim cluster-wise
  #

  # Group-wise dimming
  df_dimmed <- df %>%
    dplyr::group_by(.cluster) %>%
    dim_values(
      cols = c("x", "y"),
      dim_col = "o",
      origin_fn = centroid
    )

  # Plot the dimmed data such that the alpha (opacity) is
  # controlled by the dimming
  # (Note: This works because the `o` column is 1 for all values)
  ggplot(
    data = df_dimmed,
    aes(x = x, y = y, alpha = o_dimmed, color = .cluster)
  ) +
    geom_point() +
    theme_minimal() +
    labs(x = "x", y = "y", color = "Cluster", alpha = "o_dimmed")

```

distance

Calculate the distance to an origin

Description

Experimental

Calculates the distance to the specified origin with:

$$d(P1, P2) = \text{sqrt}((x2 - x1)^2 + (y2 - y1)^2 + (z2 - z1)^2 + \dots)$$

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and finding the distance to e.g. the centroid of each group.

Usage

```
distance(
  data,
  cols = NULL,
  origin = NULL,
  origin_fn = NULL,
  distance_col_name = ".distance",
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to measure distance in. Each column is considered a dimension.
origin	Coordinates of the origin to calculate distances to. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. `create_origin_fn(median)` would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
distance_col_name	Name of new column with the distances.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with the additional columns (distances and origin coordinates).

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other measuring functions: [angle\(\)](#), [vector_length\(\)](#)

Other distance functions: [closest_to\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [furthest_from\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = runif(20),
  "y" = runif(20),
  "g" = rep(1:4, each = 5)
)

# Calculate distances in the two dimensions (x and y)
# With the origin at x=0.5, y=0.5
distance(
  data = df,
  cols = c("x", "y"),
  origin = c(0.5, 0.5)
)

# Calculate distances to the centroid for each group in 'g'
distance(
  data = dplyr::group_by(df, g),
  cols = c("x", "y"),
  origin_fn = centroid
)
```

expand_distances

Expand the distances to an origin

Description**Experimental**

Moves the data points in n-dimensional space such that their distance to a specified origin is increased/decreased. A `multiplier` greater than 1 leads to expansion, while a positive `multiplier` lower than 1 leads to contraction.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped `data.frame` and expanding around e.g. the centroid of each group.

The multiplier/exponent can be supplied as a constant or as a function that returns a constant. The latter can be useful when supplying a grouped `data.frame` and the multiplier/exponent depends on the data in the groups.

For expansion in each dimension separately, use [expand_distances_each\(\)](#).

NOTE: When exponentiating, the default is to first add 1 to the distances, to ensure expansion even when the distance is between 0 and 1. If you need the purely exponentiated distances, disable ``add_one_exp``.

Usage

```
expand_distances(
  data,
  cols = NULL,
  multiplier = NULL,
  multiplier_fn = NULL,
  origin = NULL,
  origin_fn = NULL,
  exponentiate = FALSE,
  add_one_exp = TRUE,
  suffix = "_expanded",
  keep_original = TRUE,
  mult_col_name = ifelse(isTRUE(exponentiate), ".exponent", ".multiplier"),
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to expand coordinates of. Each column is considered a dimension.
multiplier	Constant to multiply/exponentiate the distances to the origin by. N.B. When `exponentiate` is TRUE, the `multiplier` becomes an <i>exponent</i> .
multiplier_fn	Function for finding the `multiplier`. Input: Each column will be passed as a vector in the order of `cols`. Output: A numeric scalar.
origin	Coordinates of the origin to expand around. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
exponentiate	Whether to exponentiate instead of multiplying. (Logical)
add_one_exp	Whether to add 1 to the distances before exponentiating to ensure they don't contract when between 0 and 1. The added value is subtracted after the exponentiation. (Logical) The distances to the origin (`d`) are exponentiated as such: $d \leftarrow -d + 1$

	<pre>d <- d ^ multiplier d <- d - 1</pre> <p>N.B. Ignored when <code>`exponentiate`</code> is FALSE.</p>
suffix	<p>Suffix to add to the names of the generated columns.</p> <p>Use an empty string (i.e. <code>""</code>) to overwrite the original columns.</p>
keep_original	<p>Whether to keep the original columns. (Logical)</p> <p>Some columns may have been overwritten, in which case only the newest versions are returned.</p>
mult_col_name	Name of new column with the <code>`multiplier`</code> . If NULL, no column is added.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Details

Increases the distance to the origin in n-dimensional space by multiplying or exponentiating it by the multiplier.

We first move the origin to the zero-coordinates (e.g. `c(0, 0, 0)`) and normalize each vector to unit length. We then multiply this unit vector by the multiplied/exponentiated distance and moves the origin back to its original coordinates.

The distance to the specified origin is calculated with:

$$d(P1, P2) = \text{sqrt}((x2 - x1)^2 + (y2 - y1)^2 + (z2 - z1)^2 + \dots)$$

Note: By default (when ``add_one_exp`` is TRUE), we add 1 to the distance before the exponentiation and subtract it afterwards. See ``add_one_exp``.

Value

`data.frame` (tibble) with the expanded columns, along with the applied multiplier/exponent and origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other expander functions: [expand_distances_each\(\)](#)

Other distance functions: [closest_to\(\)](#), [dim_values\(\)](#), [distance\(\)](#), [expand_distances_each\(\)](#), [furthest_from\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```

# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = runif(20),
  "y" = runif(20),
  "g" = rep(1:4, each = 5)
)

# Expand distances in the two dimensions (x and y)
# With the origin at x=0.5, y=0.5
# We multiply the distances by 2
expand_distances(
  data = df,
  cols = c("x", "y"),
  multiplier = 2,
  origin = c(0.5, 0.5)
)

# Expand distances in the two dimensions (x and y)
# With the origin at x=0.5, y=0.5
# We exponentiate the distances by 2
expand_distances(
  data = df,
  cols = c("x", "y"),
  multiplier = 2,
  exponentiate = TRUE,
  origin = 0.5
)

# Expand values in one dimension (x)
# With the origin at x=0.5
# We exponentiate the distances by 3
expand_distances(
  data = df,
  cols = c("x"),
  multiplier = 3,
  exponentiate = TRUE,
  origin = 0.5
)

# Expand x and y around the centroid
# We use exponentiation for a more drastic effect
# The add_one_exp makes sure it expands
# even when x or y is in the range [0, <1]
# To compare multiple exponents, we wrap the
# call in purrr::map_dfr
df_expanded <- purrr::map_dfr(

```

```

.x = c(1, 3, 5),
.f = function(exponent) {
  expand_distances(
    data = df,
    cols = c("x", "y"),
    multiplier = exponent,
    origin_fn = centroid,
    exponentiate = TRUE,
    add_one_exp = TRUE
  )
}
)
df_expanded

# Plot the expansions of x and y around the overall centroid
ggplot(df_expanded, aes(x = x_expanded, y = y_expanded, color = factor(.exponent))) +
  geom_vline(
    xintercept = df_expanded[[".origin"]][[1]][[1]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_hline(
    yintercept = df_expanded[[".origin"]][[1]][[2]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_path(size = 0.2) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "Exponent")

# Expand x and y around the centroid using multiplication
# To compare multiple multipliers, we wrap the
# call in purrr::map_dfr
df_expanded <- purrr::map_dfr(
  .x = c(1, 3, 5),
  .f = function(multiplier) {
    expand_distances(df,
      cols = c("x", "y"),
      multiplier = multiplier,
      origin_fn = centroid,
      exponentiate = FALSE
    )
  }
)
df_expanded

# Plot the expansions of x and y around the overall centroid
ggplot(df_expanded, aes(x = x_expanded, y = y_expanded, color = factor(.multiplier))) +
  geom_vline(
    xintercept = df_expanded[[".origin"]][[1]][[1]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_hline(
    yintercept = df_expanded[[".origin"]][[1]][[2]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_path(size = 0.2, alpha = .8) +
  geom_point() +

```

```

theme_minimal() +
labs(x = "x", y = "y", color = "Multiplier")

#
# Contraction
#

# Group-wise contraction to create clusters
df_contracted <- df %>%
  dplyr::group_by(g) %>%
  expand_distances(
    cols = c("x", "y"),
    multiplier = 0.07,
    suffix = "_contracted",
    origin_fn = centroid
  )

# Plot the clustered data point on top of the original data points
ggplot(df_contracted, aes(x = x_contracted, y = y_contracted, color = factor(g))) +
  geom_point(aes(x = x, y = y, color = factor(g)), alpha = 0.3, shape = 16) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "g")

```

expand_distances_each *Expand the distances to an origin in each dimension*

Description

Experimental

Moves the data points in n-dimensional space such that their distance to the specified origin is increased/decreased *in each dimension separately*. A `multiplier` greater than 1 leads to expansion, while a positive `multiplier` lower than 1 leads to contraction.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and expanding around e.g. the centroid of each group.

The multipliers/exponents can be supplied as constant(s) or as a function that returns constants. The latter can be useful when supplying a grouped data.frame and the multiplier/exponent depends on the data in the groups. If supplying multiple constants, there must be one per dimension (length of `cols`).

For expansion of the *multidimensional* distance, use `expand_distances()`.

NOTE: When exponentiating, the default is to first add 1 or -1 (depending on the sign of the distance) to the distances, to ensure expansion even when the distance is between -1 and 1. If you need the purely exponentiated distances, disable `add_one_exp`.

Usage

```

expand_distances_each(
  data,
  cols = NULL,
  multipliers = NULL,

```

```

multipliers_fn = NULL,
origin = NULL,
origin_fn = NULL,
exponentiate = FALSE,
add_one_exp = TRUE,
suffix = "_expanded",
keep_original = TRUE,
mult_col_name = ifelse(isTRUE(exponentiate), ".exponents", ".multipliers"),
origin_col_name = ".origin",
overwrite = FALSE
)

```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to expand. Each column is considered a dimension to expand in.
multipliers	Constant(s) to multiply/exponentiate the distance to the origin by. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. When `exponentiate` is TRUE, the `multipliers` become <i>exponents</i> .
multipliers_fn	Function for finding the `multipliers`. Input: Each column will be passed as a vector in the order of `cols`. Output: A numeric vector with one element per dimension. Just as for `origin_fn`, it can be created with create_origin_fn() if you want to apply the same function to each dimension. See `origin_fn`.
origin	Coordinates of the origin to expand around. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. `create_origin_fn(median)` would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
exponentiate	Whether to exponentiate instead of multiplying. (Logical)
add_one_exp	Whether to add the sign (either 1 or -1) before exponentiating to ensure the values don't contract. The added value is subtracted after the exponentiation. (Logical) Exponentiation becomes: <pre> x <-x + sign(x) x <-sign(x) * abs(x) ^ multiplier x <-x -sign(x) </pre> N.B. Ignored when `exponentiate` is FALSE.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.

<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>mult_col_name</code>	Name of new column with the multiplier(s). If NULL, no column is added.
<code>origin_col_name</code>	Name of new column with the origin coordinates. If NULL, no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Details

For each value of each dimension (column), either multiply or exponentiate by the multiplier:

Multiplication

```
x <- x * multiplier
```

Exponentiation

```
x <- sign(x) * abs(x) ^ multiplier
```

Note: By default (when ``add_one_exp`` is TRUE), we add the sign (1 / -1) of the value before the exponentiation and subtract it afterwards. See ``add_one_exp``.

Value

`data.frame` (tibble) with the expanded columns, along with the applied multiplier/exponent and origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other expander functions: [expand_distances\(\)](#)

Other distance functions: [closest_to\(\)](#), [dim_values\(\)](#), [distance\(\)](#), [expand_distances\(\)](#), [furthest_from\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = runif(20),
  "y" = runif(20),
```

```

    "g" = rep(1:4, each = 5)
  )

  # Expand values in the two dimensions (x and y)
  # With the origin at x=0.5, y=0.5
  # We expand x by 2 and y by 4
  expand_distances_each(
    data = df,
    cols = c("x", "y"),
    multipliers = c(2, 4),
    origin = c(0.5, 0.5)
  )

  # Expand values in the two dimensions (x and y)
  # With the origin at x=0.5, y=0.5
  # We expand both by 3
  expand_distances_each(
    data = df,
    cols = c("x", "y"),
    multipliers = 3,
    origin = 0.5
  )

  # Expand values in one dimension (x)
  # With the origin at x=0.5
  # We expand by 3
  expand_distances_each(
    data = df,
    cols = c("x"),
    multipliers = 3,
    origin = 0.5
  )

  # Expand x and y around the centroid
  # We use exponentiation for a more drastic effect
  # The add_one_exp makes sure it expands
  # even when x or y is in the range [>-1, <1]
  # To compare multiple exponents, we wrap the
  # call in purrr::map_dfr
  df_expanded <- purrr::map_dfr(
    .x = c(1, 2.0, 3.0, 4.0),
    .f = function(exponent) {
      expand_distances_each(
        data = df,
        cols = c("x", "y"),
        multipliers = exponent,
        origin_fn = centroid,
        exponentiate = TRUE,
        add_one_exp = TRUE
      )
    }
  )
  df_expanded

  # Plot the expansions of x and y around the overall centroid
  ggplot(df_expanded, aes(x = x_expanded, y = y_expanded, color = factor(.exponents))) +
    geom_vline(

```

```

    xintercept = df_expanded[["origin"]][[1]][[1]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_hline(
    yintercept = df_expanded[["origin"]][[1]][[2]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "Exponent")

# Expand x and y around the centroid using multiplication
# To compare multiple multipliers, we wrap the
# call in purrr::map_dfr
df_expanded <- purrr::map_dfr(
  .x = c(1, 2.0, 3.0, 4.0),
  .f = function(multiplier) {
    expand_distances_each(df,
      cols = c("x", "y"),
      multipliers = multiplier,
      origin_fn = centroid,
      exponentiate = FALSE
    )
  }
)
df_expanded

# Plot the expansions of x and y around the overall centroid
ggplot(df_expanded, aes(x = x_expanded, y = y_expanded, color = factor(.multipliers))) +
  geom_vline(
    xintercept = df_expanded[["origin"]][[1]][[1]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_hline(
    yintercept = df_expanded[["origin"]][[1]][[2]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "Multiplier")

# Expand x and y with different multipliers
# around the centroid using multiplication
df_expanded <- expand_distances_each(
  df,
  cols = c("x", "y"),
  multipliers = c(1.25, 10),
  origin_fn = centroid,
  exponentiate = FALSE
)
df_expanded

# Plot the expansions of x and y around the overall centroid
# Note how the y axis is expanded a lot more than the x-axis
ggplot(df_expanded, aes(x = x_expanded, y = y_expanded)) +
  geom_vline(
    xintercept = df_expanded[["origin"]][[1]][[1]],

```



```

    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_hline(
    yintercept = df_expanded[["origin"]][[1]][[2]],
    size = 0.2, alpha = .4, linetype = "dashed"
  ) +
  geom_line(aes(color = "Expanded")) +
  geom_point(aes(color = "Expanded")) +
  geom_line(aes(x = x, y = y, color = "Original")) +
  geom_point(aes(x = x, y = y, color = "Original")) +
  theme_minimal() +
  labs(x = "x", y = "y", color = "Multiplier")

#
# Contraction
#

# Group-wise contraction to create clusters
df_contracted <- df %>%
  dplyr::group_by(g) %>%
  expand_distances_each(
    cols = c("x", "y"),
    multipliers = 0.07,
    suffix = "_contracted",
    origin_fn = centroid
  )

# Plot the clustered data point on top of the original data points
ggplot(df_contracted, aes(x = x_contracted, y = y_contracted, color = factor(g))) +
  geom_point(aes(x = x, y = y, color = factor(g)), alpha = 0.3, shape = 16) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "g")

```

flip_values

Flip the values around an origin

Description

Experimental

The values are flipped with the formula ' $x = 2 * c - x$ ' where x is the value and c is the origin coordinate to flip the values around.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and flipping around e.g. the centroid of each group. By default the median value in each dimension is used.

The *_vec() version take and return a vector.

Example:

The column values:

```
c(5, 2, 7, 4, 3, 1)
```

```
and the origin_fn = create_origin_fn(median)
```

Changes the values to :

```
c(2, 5, 0, 3, 4, 6)
```

Usage

```
flip_values(
  data,
  cols = NULL,
  origin = NULL,
  origin_fn = create_origin_fn(median),
  suffix = "_flipped",
  keep_original = TRUE,
  origin_col_name = ".origin",
  overwrite = FALSE
)

flip_values_vec(data, origin = NULL, origin_fn = create_origin_fn(median))
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to flip values of.
origin	Coordinates of the origin to flip around. A scalar to use in all dimensions (columns) or a vector with one scalar per dimension. N.B. Ignored when `origin_fn` is not NULL. Remember to set it to NULL when passing origin coordinates manually!
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with create_origin_fn() if you want to apply the same function to each dimension. E.g. `create_origin_fn(median)` would find the median of each column. Built-in functions are centroid() , most_centered() , and midrange()
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```

# Attach packages
library(rearrrr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "Index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Flip values of the columns
flip_values(df$A)
flip_values(df, cols = "A")
flip_values(df, cols = "B", origin = 0.3, origin_fn = NULL, keep_original = FALSE)
flip_values(df,
  cols = c("A", "B"),
  origin = c(3, 0.3),
  origin_fn = NULL,
  suffix = "",
  keep_original = FALSE,
  overwrite = TRUE
)
flip_values(df, cols = c("A", "B"), origin_fn = create_origin_fn(max))

# Grouped by G
df %>%
  dplyr::group_by(G) %>%
  flip_values(
    cols = c("A", "B"),
    origin_fn = create_origin_fn(median),
    keep_original = FALSE
  )

# Plot A and flipped A

# First flip A around the median and then around the value 3.
df <- df %>%
  flip_values(cols = "A", suffix = "_flip_median", origin_col_name = NULL) %>%
  flip_values(cols = "A", suffix = "_flip_3", origin = 3,
    origin_fn = NULL, origin_col_name = NULL)

# Plot A and A flipped around its median
ggplot(df, aes(x = Index, y = A)) +
  geom_line(aes(color = "A")) +
  geom_line(aes(y = A_flip_median, color = "Flipped A (median)")) +

```

```

geom_hline(aes(color = "Median A", yintercept = median(A))) +
theme_minimal()

# Plot A and A flipped around the value 3
ggplot(df, aes(x = Index, y = A)) +
  geom_line(aes(color = "A")) +
  geom_line(aes(y = A_flip_3, color = "Flipped A (3)")) +
  geom_hline(aes(color = "3", yintercept = 3)) +
  theme_minimal()

```

furthest_from

Orders values by longest distance to an origin

Description

Experimental

Values are ordered by how far they are from the origin.

In 1d (when `cols` has length 1), the origin can be thought of as a target value. In n dimensions, the origin can be thought of as coordinates.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and ordering the rows by their distance to the centroid of each group.

The `*_vec()` version takes and returns a vector.

Example:

The column values:

```
c(1,2,3,4,5)
```

and `origin = 2`

are **ordered as:**

```
c(5,4,1,3, 2)
```

Usage

```

furthest_from(
  data,
  cols = NULL,
  origin = NULL,
  origin_fn = NULL,
  shuffle_ties = FALSE,
  origin_col_name = ".origin",
  distance_col_name = ".distance",
  overwrite = FALSE
)

```

```
furthest_from_vec(data, origin = NULL, origin_fn = NULL, shuffle_ties = FALSE)
```

Arguments

<code>data</code>	data.frame or vector.
<code>cols</code>	Column(s) to create sorting factor by. When NULL and <code>`data`</code> is a data.frame, the row numbers are used.
<code>origin</code>	Coordinates of the origin to calculate distances to. A scalar to use in all dimensions or a vector with one scalar per dimension. N.B. Ignored when <code>`origin_fn`</code> is not NULL.
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of <code>`cols`</code> . Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
<code>shuffle_ties</code>	Whether to shuffle elements with the same distance to the origin. (Logical)
<code>origin_col_name</code>	Name of new column with the origin coordinates. If NULL, no column is added.
<code>distance_col_name</code>	Name of new column with the distances to the origin. If NULL, no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Value

The sorted data.frame (tibble) / vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: `center_max()`, `center_min()`, `closest_to()`, `pair_extremes()`, `position_max()`, `position_min()`, `rev_windows()`, `roll_elements()`

Other distance functions: `closest_to()`, `dim_values()`, `distance()`, `expand_distances_each()`, `expand_distances()`, `swirl_2d()`, `swirl_3d()`

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
```

```

    "B" = runif(10),
    "G" = c(
      1, 1, 1, 2, 2,
      2, 3, 3, 3, 3
    ),
    stringsAsFactors = FALSE
  )

# Furthest from 3 in a vector
furthest_from_vec(1:10, origin = 3)

# Furthest from the third row (index of data.frame)
furthest_from(df, origin = 3)$index

# By each of the columns
furthest_from(df, cols = "A", origin = 3)$A
furthest_from(df, cols = "A", origin_fn = most_centered)$A
furthest_from(df, cols = "B", origin = 0.5)$B
furthest_from(df, cols = "B", origin_fn = centroid)$B

# Shuffle the elements with the same distance to the origin
furthest_from(df,
  cols = "A",
  origin_fn = create_origin_fn(median),
  shuffle_ties = TRUE
)$A

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  furthest_from(
    cols = "A",
    origin_fn = create_origin_fn(median)
  )

# Plot the rearranged values
plot(
  x = 1:10,
  y = furthest_from(df,
    cols = "B",
    origin_fn = create_origin_fn(median)
  )$B,
  xlab = "Position", ylab = "B"
)
plot(
  x = 1:10,
  y = furthest_from(df,
    cols = "A",
    origin_fn = create_origin_fn(median),
    shuffle_ties = TRUE
  )$A,
  xlab = "Position", ylab = "A"
)

# In multiple dimensions
df %>%

```

```
furthest_from(cols = c("A", "B"), origin_fn = most_centered)
```

generate_clusters	<i>Generate n-dimensional clusters</i>
-------------------	--

Description

Experimental

Generates `data.frame` (tibble) with clustered groups.

Usage

```
generate_clusters(
  num_rows,
  num_cols,
  num_clusters,
  compactness = 1.6,
  generator = runif,
  name_prefix = "D",
  cluster_col_name = ".cluster"
)
```

Arguments

<code>num_rows</code>	Number of rows.
<code>num_cols</code>	Number of columns (dimensions).
<code>num_clusters</code>	Number of clusters.
<code>compactness</code>	How compact the clusters should be. A larger value leads to more compact clusters (on average). Technically, it is passed to the <code>'multiplier'</code> argument in <code>cluster_groups()</code> as <code>'0.1/compactness'</code> .
<code>generator</code>	Function to generate the numeric values. Must have the <i>number of values to generate</i> as its first (and only required) argument, as that is the only argument we pass to it.
<code>name_prefix</code>	Prefix string for naming columns.
<code>cluster_col_name</code>	Name of cluster factor.

Details

- Generates `data.frame` with random values using the `'generator'`.
- Divides the rows into groups (the clusters).
- Contracts the distance from each data point to the centroid of its group.
- Performs MinMax scaling such that the scale of the data points is similar to the generated data.

Value

`data.frame` (tibble) with the clustered columns and the cluster grouping factor.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other clustering functions: [cluster_groups\(\)](#), [transfer_centroids\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)
library(plotly)

# Set seed
set.seed(10)

# Generate clusters
generate_clusters(num_rows = 20, num_cols = 3, num_clusters = 3, compactness = 1.6)
generate_clusters(num_rows = 20, num_cols = 5, num_clusters = 6, compactness = 2.5)

# Generate clusters and plot them
# Tip: Call this multiple times
# to see the behavior of `generate_clusters()`
generate_clusters(
  num_rows = 50, num_cols = 2,
  num_clusters = 5, compactness = 1.6
) %>%
  ggplot(
    aes(x = D1, y = D2, color = .cluster)
  ) +
  geom_point() +
  theme_minimal() +
  labs(x = "D1", y = "D2", color = "Cluster")

#
# Plot clusters in 3d view
#

# Generate clusters
clusters <- generate_clusters(
  num_rows = 50, num_cols = 3,
  num_clusters = 5, compactness = 1.6
)

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = clusters$D1,
  y = clusters$D2,
  z = clusters$D3,
  type = "scatter3d",
  mode = "markers",
  color = clusters$.cluster
)
```



```
## End(Not run)
```

hexagonalize

Create x-coordinates so the points form a hexagon

Description

Experimental

Create the x-coordinates for a vector of y-coordinates such that they form a hexagon.

This will likely look most like a hexagon when the y-coordinates are somewhat equally distributed, e.g. a uniform distribution.

Usage

```
hexagonalize(
  data,
  y_col = NULL,
  .min = NULL,
  .max = NULL,
  offset_x = 0,
  keep_original = TRUE,
  x_col_name = ".hexagon_x",
  edge_col_name = ".edge",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
y_col	Name of column in `data` with y-coordinates to create x-coordinates for.
.min	Minimum y-coordinate. If NULL, it is inferred by the given y-coordinates.
.max	Maximum y-coordinate. If NULL, it is inferred by the given y-coordinates.
offset_x	Value to offset the x-coordinates by.
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
x_col_name	Name of new column with the x-coordinates.
edge_col_name	Name of new column with the edge identifiers. If NULL, no column is added. Numbering is clockwise and starts at the upper-right edge.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with the added x-coordinates and an identifier for the edge the data point is a part of.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other forming functions: [circularize\(\)](#), [square\(\)](#), [triangularize\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "y" = runif(200),
  "g" = factor(rep(1:5, each = 40))
)

# Hexagonalize 'y'
df_hex <- hexagonalize(df, y_col = "y")
df_hex

# Plot hexagon
df_hex %>%
  ggplot(aes(x = .hexagon_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Grouped hexagonalization
#

# Hexagonalize 'y' for each group
# First cluster the groups a bit to move the
# hexagons away from each other
df_hex <- df %>%
  cluster_groups(
    cols = "y",
    group_cols = "g",
    suffix = "",
    overwrite = TRUE
  ) %>%
  dplyr::group_by(g) %>%
  hexagonalize(
    y_col = "y",
    overwrite = TRUE
  )

# Plot hexagons
df_hex %>%
```

```

    ggplot(aes(x = .hexagon_x, y = y, color = g)) +
    geom_point() +
    theme_minimal()

#
# Specifying minimum value
#

# Specify minimum value manually
df_hex <- hexagonalize(df, y_col = "y", .min = -2)
df_hex

# Plot hexagon
df_hex %>%
  ggplot(aes(x = .hexagon_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Multiple hexagons by contraction
#

# Start by hexagonalizing 'y'
df_hex <- hexagonalize(df, y_col = "y")

# Contract '.hexagon_x' and 'y' towards the centroid
# To contract with multiple multipliers at once,
# we wrap the call in purrr::map_dfr
df_expanded <- purrr::map_dfr(
  .x = c(1, 0.75, 0.5, 0.25, 0.125),
  .f = function(mult) {
    expand_distances(
      data = df_hex,
      cols = c(".hexagon_x", "y"),
      multiplier = mult,
      origin_fn = centroid,
      overwrite = TRUE
    )
  }
)
df_expanded

df_expanded %>%
  ggplot(aes(
    x = .hexagon_x_expanded, y = y_expanded,
    color = .edge, alpha = .multiplier
  )) +
  geom_point() +
  theme_minimal()

```

Description

Experimental

Finds the data point with the shortest distance to the centroid.

To get the coordinates of the most centered data point, use [most_centered\(\)](#) instead.

Usage

```
is_most_centered(..., na.rm = FALSE)
```

Arguments

...	Numeric vectors.
na.rm	Whether to ignore missing values. At least one data point must be complete. (Logical)

Value

Logical vector (TRUE/FALSE) indicating if a data point is the most centered.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other coordinate functions: [centroid\(\)](#), [create_origin_fn\(\)](#), [midrange\(\)](#), [most_centered\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Find the data point closest to the centroid
is_most_centered(x, y, z)

# Compare to coordinates for the most centered
most_centered(x, y, z)

#
# For data.frames
#

# Create data frame
df <- data.frame(
```

```

"x" = x,
"y" = y,
"z" = z,
"g" = rep(1:2, each = 5)
)

# Filter the data points
# closest to the centroid
df %>%
  dplyr::filter(is_most_centered(x, y, z))

# When 'df' is grouped
df %>%
  dplyr::group_by(g) %>%
  dplyr::filter(is_most_centered(x, y, z))

# Add as column
df %>%
  dplyr::group_by(g) %>%
  dplyr::mutate(mc = is_most_centered(x, y, z))

```

median_index

Find index of interest for each vector

Description

Experimental

Applies function to the indices of each vector in `...`.

These functions were created with [create_n_fn\(\)](#).

Usage

```
median_index(..., negate = FALSE, round_fn = round)
```

```
quantile_index(..., prob, type = 7, negate = FALSE, round_fn = round)
```

Arguments

<code>...</code>	Numeric vectors.
<code>negate</code>	Whether to negate the result. I.e. to multiply it with -1 . (Logical)
<code>round_fn</code>	Function for rounding output. Rounding is done <i>prior</i> to negation. E.g. round , floor , or ceiling .
<code>prob</code>	Probability in $[0, 1]$ for quantile() .
<code>type</code>	Quantile algorithm to use. See quantile() .

Value

numeric vector with one element per supplied vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other n functions: [create_n_fn\(\)](#)

Examples

```
# Attach packages
library(rearr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(15)
z <- runif(20)

median_index(x, y, z)
quantile_index(x, y, z, prob = 0.2)

# Negate result
median_index(x, y, z, negate = TRUE)
```

midrange	<i>Find the midrange values</i>
----------	---------------------------------

Description**Experimental**

Calculates the midrange for each of the passed vectors/columns.

Midrange is defined as:

$$(max + min)/2$$

Usage

```
midrange(..., cols = NULL, na.rm = FALSE)
```

Arguments

...	Numeric vectors or a single data.frame.
cols	Names of columns to use when `...` is a single data.frame.
na.rm	Whether to ignore missing values when calculating min and max values. (Logical)

Value

Either a vector with the midrange of each supplied vector or a data.frame with the midrange of each supplied column along with any grouping variables.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other coordinate functions: [centroid\(\)](#), [create_origin_fn\(\)](#), [is_most_centered\(\)](#), [most_centered\(\)](#)

Examples

```
# Attach packages
library(rearrrr)
library(dplyr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Find midrange for each vector
midrange(x, y, z)

#
# For data.frames
#

# Create data frame
df <- data.frame(
  "x" = x,
  "y" = y,
  "z" = z,
  "g" = rep(1:2, each = 5)
)

# Find midrange for each column
midrange(df, cols = c("x", "y", "z"))

# When 'df' is grouped
df %>%
  dplyr::group_by(g) %>%
  midrange(cols = c("x", "y", "z"))
```

Description**Experimental**

Scales the values to a range with MinMax scaling.

Usage

```
min_max_scale(
  x,
  new_min,
  new_max,
  old_min = NULL,
  old_max = NULL,
  na.rm = FALSE
)
```

Arguments

<code>x</code>	Numeric vector to scale.
<code>new_min</code>	Minimum value of target range.
<code>new_max</code>	Maximum value of target range.
<code>old_min</code>	Minimum value of original range. If NULL, this is the minimum value in <code>`x`</code> .
<code>old_max</code>	Maximum value of original range. If NULL, this is the maximum value in <code>`x`</code> .
<code>na.rm</code>	Whether missing values should be removed when calculating <code>`old_min`</code> and/or <code>`old_max`</code> . N.B. Ignored when both <code>`old_min`</code> and <code>`old_max`</code> are NULL.

Value

Scaled version of ``x``.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other scaling functions: [to_unit_length\(\)](#)

Examples

```
# Attach packages
library(rearr)

# Set seed
set.seed(1)

# Create numeric vector
x <- runif(10)

# Scale
```



```
min_max_scale(x, new_min = -1, new_max = 0)
min_max_scale(x, new_min = -1, new_max = 0, old_max = 3)
```

most_centered	<i>Find the coordinates for the data point closest to the centroid</i>
---------------	--

Description

Experimental

Returns the coordinates for the data point with the shortest distance to the [centroid](#).

To get a logical vector (TRUE/FALSE) indicating whether a data point is the most centered, use [is_most_centered\(\)](#).

Usage

```
most_centered(..., cols = NULL, na.rm = FALSE)
```

Arguments

...	Numeric vectors or a single data.frame.
cols	Names of columns to use when `...` is a single data.frame.
na.rm	Whether to ignore missing values. At least one data point must be complete. (Logical)

Value

The coordinates for the data point closest to the centroid. Either as a vector or a data.frame.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other coordinate functions: [centroid\(\)](#), [create_origin_fn\(\)](#), [is_most_centered\(\)](#), [midrange\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create three vectors
x <- runif(10)
y <- runif(10)
z <- runif(10)

# Find coordinates of the data point
# closest to the centroid
```

```

most_centered(x, y, z)

# Compare to centroid coordinates
centroid(x, y, z)

#
# For data.frames
#

# Create data frame
df <- data.frame(
  "x" = x,
  "y" = y,
  "z" = z,
  "g" = rep(1:2, each = 5)
)

# Find coordinates of the data point
# closest to the centroid
most_centered(df, cols = c("x", "y", "z"))

# When 'df' is grouped
df %>%
  dplyr::group_by(g) %>%
  most_centered(cols = c("x", "y", "z"))

# Filter to only include most centered data points
df %>%
  dplyr::group_by(g) %>%
  dplyr::filter(is_most_centered(x, y, z))

```

pair_extremes

Pair extreme values and sort by the pairs

Description

Experimental

The values are paired/grouped such that the highest and lowest values form the first group, the second highest and the second lowest values form the second group, and so on. The values are then sorted by these groups/pairs.

When `data` has an uneven number of rows, the `unequal_method` determines which group should have only 1 element.

The `*_vec()` version takes and returns a vector.

Example:

The column values:

```
c(1, 2, 3, 4, 5, 6)
```

Creates the **sorting factor**:

```
c(1, 2, 3, 3, 2, 1)
```

And are **ordered as**:

```
c(1, 6, 2, 5, 3, 4)
```

Usage

```
pair_extremes(
  data,
  col = NULL,
  unequal_method = "middle",
  shuffle_members = FALSE,
  shuffle_pairs = FALSE,
  factor_name = ".pair",
  overwrite = FALSE
)

pair_extremes_vec(
  data,
  unequal_method = "middle",
  shuffle_members = FALSE,
  shuffle_pairs = FALSE
)
```

Arguments

data	data.frame or vector.
col	Column to create sorting factor by. When NULL and `data` is a data.frame, the row numbers are used.
unequal_method	Method for dealing with an unequal number of rows in `data`. One of: first, middle or last first: The first group will have size 1. Example: The column values: c(1,2,3,4,5) Creates the sorting factor : c(1,2,3,3,2) And are ordered as : c(1,2,5,3,4) middle: The middle group will have size 1. Example: The column values: c(1,2,3,4,5) Creates the sorting factor : c(1,3,2,3,1) And are ordered as : c(1,5,3,2,4) last: The last group will have size 1. Example: The column values: c(1,2,3,4,5) Creates the sorting factor : c(1,2,2,1,3) And are ordered as : c(1,4,2,3,5)
shuffle_members	Whether to shuffle the pair members. (Logical)

shuffle_pairs Whether to shuffle the pairs. (Logical)
 factor_name Name of new column with the sorting factor. If NULL, no column is added.
 overwrite Whether to allow overwriting of existing columns. (Logical)

Value

The sorted data.frame (tibble) / vector. Optionally with the sorting factor added.

When `data` is a vector and `keep_factors` is FALSE, the output will be a vector. Otherwise, a data.frame.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: [center_max\(\)](#), [center_min\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [position_max\(\)](#), [position_min\(\)](#), [rev_windows\(\)](#), [roll_elements\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Pair extreme indices (row numbers)
pair_extremes(df)

# Pair extremes in each of the columns
pair_extremes(df, col = "A")$A
pair_extremes(df, col = "B")$B
pair_extremes(df, col = "C")$C

# Shuffle the members pair-wise
pair_extremes(df, col = "A", shuffle_members = TRUE)

# Shuffle the order of the pairs
pair_extremes(df, col = "A", shuffle_pairs = TRUE)
```

```

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  pair_extremes(col = "A")

# Plot the extreme pairs
plot(
  x = 1:10,
  y = pair_extremes(df, col = "B")$B
)
# With shuffled pair members (run a few times)
plot(
  x = 1:10,
  y = pair_extremes(df, col = "B", shuffle_members = TRUE)$B
)
# With shuffled pairs (run a few times)
plot(
  x = rep(1:5, each = 2),
  y = pair_extremes(df, col = "B", shuffle_pairs = TRUE)$B
)

```

position_max

*Positions the highest values with values decreasing around it***Description****Experimental**

The highest value is positioned at the given index/quantile with the other values decreasing around it.

Example:

The column values:

```
c(1,2,3,4,5)
```

and position = 2

are **ordered as:**

```
c(3, 5,4,2,1)
```

Usage

```
position_max(data, col = NULL, position = NULL, shuffle_sides = FALSE)
```

Arguments

data	data.frame or vector.
col	Column to create sorting factor by. When NULL and `data` is a data.frame, the row numbers are used.
position	Index or quantile (in 0-1) at which to position the element of interest.
shuffle_sides	Whether to shuffle which elements are left and right of the position. (Logical)

Value

The sorted data.frame (tibble) / vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: `center_max()`, `center_min()`, `closest_to()`, `furthest_from()`, `pair_extremes()`, `position_min()`, `rev_windows()`, `roll_elements()`

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Position the highest index (row number)
position_max(df, position = 3)$index
position_max(df, position = 8)$index

# Position the maximum value in each of the columns
position_max(df, col = "A", position = 3)$A
position_max(df, col = "B", position = 3)$B
position_max(df, col = "C", position = 3)$C

# Randomize which elements are left and right of the position
position_max(df, col = "A", position = 3, shuffle_sides = TRUE)$A

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  position_max(col = "A", position = 2)

# Plot the rearranged values
plot(x = 1:10, y = position_max(df, col = "B", position = 3)$B)
plot(x = 1:10, y = position_max(df, col = "B", position = 3, shuffle_sides = TRUE)$B)
```

position_min	<i>Positions the lowest value with values increasing around it</i>
--------------	--

Description

Experimental

The lowest value is positioned at the given index/quantile with the other values increasing around it.

Example:

The column values:

```
c(1,2,3,4,5)
```

and position = 2

are **ordered as:**

```
c(3, 1,2,4,5)
```

Usage

```
position_min(data, col = NULL, position = NULL, shuffle_sides = FALSE)
```

Arguments

data	data.frame or vector.
col	Column to create sorting factor by. When NULL and `data` is a data.frame, the row numbers are used.
position	Index or quantile (in 0-1) at which to position the element of interest.
shuffle_sides	Whether to shuffle which elements are left and right of the position. (Logical)

Value

The sorted data.frame (tibble) / vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: [center_max\(\)](#), [center_min\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [pair_extremes\(\)](#), [position_max\(\)](#), [rev_windows\(\)](#), [roll_elements\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)
```

```

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = c(
    1, 1, 1, 2, 2,
    2, 3, 3, 3, 3
  ),
  stringsAsFactors = FALSE
)

# Position the smallest index (row number)
position_min(df, position = 3)$index
position_min(df, position = 8)$index

# Position the minimum value in each of the columns
position_min(df, col = "A", position = 3)$A
position_min(df, col = "B", position = 3)$B
position_min(df, col = "C", position = 3)$C

# Randomize which elements are left and right of the position
position_min(df, col = "A", position = 3, shuffle_sides = TRUE)$A

# Grouped by G
df %>%
  dplyr::select(G, A) %>% # For clarity
  dplyr::group_by(G) %>%
  position_min(col = "A", position = 2)

# Plot the rearranged values
plot(x = 1:10, y = position_min(df, col = "B", position = 3)$B)
plot(x = 1:10, y = position_min(df, col = "B", position = 3, shuffle_sides = TRUE)$B)

```

rev_windows

Reverse order window-wise

Description

Experimental

The values are windowed and reversed within windows.

The `*_vec()` version takes and returns a vector.

Example:

The column values:

```
c(1,2,3,4,5,6)
```

With `window_size = 3`

Are **ordered as**:

```
c(3,2,1,6,4,5)
```


Usage

```
rev_windows(data, window_size, factor_name = ".window", overwrite = FALSE)

rev_windows_vec(data, window_size)
```

Arguments

data	data.frame or vector.
window_size	Size of the windows. (Logical)
factor_name	Name of the factor with window identifiers. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

The sorted data.frame (tibble) / vector. Optionally with the windows factor added.

When `data` is a vector and `keep_windows` is FALSE, the output will be a vector. Otherwise, a data.frame.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other rearrange functions: [center_max\(\)](#), [center_min\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [pair_extremes\(\)](#), [position_max\(\)](#), [position_min\(\)](#), [roll_elements\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "index" = 1:10,
  "A" = sample(1:10),
  "B" = runif(10),
  "C" = LETTERS[1:10],
  "G" = rep(1:2, each = 5),
  stringsAsFactors = FALSE
)

# For vector
rev_windows_vec(1:10, window_size = 3)

# For data frame
rev_windows(df, window_size = 3)
rev_windows(df, window_size = 3, factor_name = NULL)

# Grouped by G
```

```
df %>%
  dplyr::select(G, index) %>% # For clarity
  dplyr::group_by(G) %>%
  rev_windows(window_size = 3)

# Plot the extreme pairs
plot(
  x = 1:10,
  y = rev_windows_vec(1:10, window_size = 3)
)
```

roll_elements

Roll elements

Description

Experimental

Rolls positions of elements.

Example:

Rolling `c(1,2,3,4,5)` with ``n = 2`` becomes:

```
c(3,4,5,1,2)
```

`roll_elements_vec()` takes and returns a vector.

Should not be confused with [roll_values\(\)](#), which changes the *values* of the elements and wraps to a given range.

Usage

```
roll_elements(
  data,
  cols = NULL,
  n = NULL,
  n_fn = NULL,
  n_col_name = ".n",
  overwrite = FALSE,
  ...
)

roll_elements_vec(data, n = NULL, n_fn = NULL, ...)
```

Arguments

<code>data</code>	vector or <code>data.frame</code> to roll elements of. When a <code>data.frame</code> is grouped, the rolling is applied group-wise.
<code>cols</code>	Names of columns in <code>`data`</code> to roll. If <code>NULL</code> , the <i>index</i> is rolled and used to reorder <code>`data`</code> . N.B. only used when <code>`data`</code> is a <code>data.frame</code> .
<code>n</code>	Number of positions to roll. A positive number rolls <i>left/up</i> . A negative number rolls <i>right/down</i> .

n_fn	Function to find `n`. Useful when `data` is a grouped data.frame and `n` should depend on the rows in the group. Input: Each specified vector/column in `data` is passed to the function as a separate argument. Output: It should return either a vector with one integer-like scalar <i>per column</i> or a single integer-like scalar to use for all columns. Can be created with create_n_fn() . See also median_index() and quantile_index() .
n_col_name	Name of new column with the applied `n` values. If NULL, no column is added.
overwrite	Whether to allow overwriting of columns with the same name as `n_col_name`. (Logical)
...	Extra arguments for `n_fn`.

Value

Rolled `data`.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other roll functions: [roll_values\(\)](#)

Other rearrange functions: [center_max\(\)](#), [center_min\(\)](#), [closest_to\(\)](#), [furthest_from\(\)](#), [pair_extremes\(\)](#), [position_max\(\)](#), [position_min\(\)](#), [rev_windows\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)

# Roll vector left
roll_elements(1:10, n = 2)

# Roll vector right and return the vector
roll_elements_vec(1:10, n = -2)

# Roll vector left by median index (rounded to 6)
roll_elements(3:12, n_fn = median_index)

# Roll vector right by median value (rounded to 8)
roll_elements(3:12, n_fn = create_n_fn(median, negate = TRUE))

# Pass extra arguments (here 'prob') to 'n_fn' via '...'
roll_elements(
  1:10,
  n_fn = quantile_index,
  prob = 0.2
)

#
# Roll data.frame
#
```

```

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = 1:20,
  "y" = runif(20) * 10,
  "g" = rep(1:4, each = 5)
)

# Roll rows left/up
roll_elements(df, n = 2)

# Roll rows right/down
roll_elements(df, n = -2)

# Roll 'x' column right/down
roll_elements(df, cols = "x", n = -2)

# Roll rows right by median index in each group
# Specify 'negate' for the 'median_index' function
roll_elements(
  df %>% dplyr::group_by(g),
  n_fn = median_index,
  negate = TRUE
)

```

roll_values

Shift values and wrap to range

Description

Experimental

Adds a specified value to each element in the vector and wraps the values around the min-max range with:

$$(x - .min) \% (.max - .min + between) + .min$$

Useful when adding to the degrees of a circle, where the values should remain in the 0-360 range. A value larger than 360 will start over from 0, e.g. 365 → 5, while a value smaller than 0 would become e.g. -5 → 355. Here, 0 and 360 are considered the same angle. If we were instead adding days to the weekdays 1-7, where 1 and 7 are separate days, we can set `between = 1` to have one day in-between them.

wrap_to_range() is a wrapper with `add = 0`.

The *_vec() versions take and return a vector.

Should not be confused with [roll_elements\(\)](#), which changes the *positions* of the elements.

Usage

```

roll_values(
  data,
  cols = NULL,

```

```

    add = 0,
    .min = NULL,
    .max = NULL,
    between = 0,
    na.rm = FALSE,
    suffix = "_rolled",
    keep_original = TRUE,
    range_col_name = ".range",
    overwrite = FALSE
  )

```

```

wrap_to_range(
  data,
  cols = NULL,
  .min = NULL,
  .max = NULL,
  between = 0,
  na.rm = FALSE,
  suffix = "_wrapped",
  keep_original = TRUE,
  range_col_name = ".range",
  overwrite = FALSE
)

```

```

roll_values_vec(
  data,
  add = 0,
  .min = NULL,
  .max = NULL,
  between = 0,
  na.rm = FALSE
)

```

```
wrap_to_range_vec(data, .min = NULL, .max = NULL, between = 0, na.rm = FALSE)
```

Arguments

data	vector or data.frame to roll/wrap values of. When a data.frame is grouped, the rolling/wrapping is applied group-wise.
cols	Names of columns to roll/wrap in `data`. Must be specified when `data` is a data.frame.
add	Amount to add to each element. (numeric scalar) When 0, the wrapping is applied without any rolling.
.min	Minimum value allowed. If NULL, the minimum value in the vector/column is used.
.max	Maximum value allowed. If NULL, the maximum value in the vector/column is used.
between	The wrapping distance between `.max` and `.min`. When 0, they are considered the same. I.e. <code>`.max` == `.min`</code> . When 1, `x` can be greater than `.max` by up to 1, why `.min` and `.max` are two separate values with 1 in-between them. I.e. <code>`.max` + 1 == `.min`</code> .

na.rm	Whether to remove missing values (NAs) when finding the <code>`.min`</code> and <code>`.max`</code> values.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. <code>""</code>) to overwrite the original columns.
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
range_col_name	Name of new column with the min-max range. If NULL, no column is added. N.B. Ignored when <code>`data`</code> is a vector.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

``data`` with new columns with values in the specified min-max range(s) and columns with the applied ranges.

The `*_vec()` versions return a vector.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other roll functions: [roll_elements\(\)](#)

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)

# Add 90 to all degrees
# Note that 0 and 360 is considered the same angle
# why there is no distance between the two
roll_values(c(0:360), add = 90)

# Get as vector
roll_values_vec(c(0:360), add = 90)

# Change limits to 0-180
# so e.g. 270 becomes 90
roll_values(c(0:360), .min = 0, .max = 180)

# Change values first, then wrap to range
x <- c(1:7)
x <- x^2
wrap_to_range(x, .min = 1, .max = 7)

# With 1 in-between .min and .max
wrap_to_range(x, .min = 1, .max = 7, between = 1)
```

```

# Get as vector
wrap_to_range_vec(x, .min = 1, .max = 7, between = 1)

#
# Roll data.frame
#

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "w" = 1:7,
  "d" = c(0, 45, 90, 135, 180, 270, 360)
)

# Roll weekdays by 1 day
roll_values(
  df,
  cols = "w",
  add = 1,
  .min = 1,
  .max = 7,
  between = 1
)

# Roll degrees by -90 degrees
roll_values(
  df,
  cols = "d",
  add = -90,
  .min = 0,
  .max = 360,
  between = 0
)

# Roll both weekdays and degrees by 1
# We don't specify .min and .max, so they
# are based on the values in the columns
# Note: This is not that meaningful but shows
# the option
roll_values(
  df,
  cols = c("w", "d"),
  add = 1
)

# Wrap weekdays to 2-5 range
wrap_to_range(
  df,
  cols = "w",
  .min = 2,
  .max = 5,
  between = 1
)

```

rotate_2d

*Rotate the values around an origin in 2 dimensions***Description****Experimental**

The values are rotated counterclockwise around a specified origin.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped `data.frame` and rotating around e.g. the centroid of each group.

Usage

```
rotate_2d(
  data,
  degrees,
  x_col = NULL,
  y_col = NULL,
  suffix = "_rotated",
  origin = NULL,
  origin_fn = NULL,
  keep_original = TRUE,
  degrees_col_name = ".degrees",
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

<code>data</code>	<code>data.frame</code> or vector.
<code>degrees</code>	Degrees to rotate values counterclockwise. In $[-360, 360]$. Can be a vector with multiple degrees.
<code>x_col</code>	Name of x column in <code>`data`</code> . If <code>NULL</code> and <code>`data`</code> is a vector, the index of <code>`data`</code> is used. If <code>`data`</code> is a <code>data.frame</code> , it must be specified.
<code>y_col</code>	Name of y column in <code>`data`</code> . If <code>`data`</code> is a <code>data.frame</code> , it must be specified.
<code>suffix</code>	Suffix to add to the names of the generated columns. Use an empty string (i.e. <code>""</code>) to overwrite the original columns.
<code>origin</code>	Coordinates of the origin to rotate around. A vector with 2 elements (i.e. <code>origin_x</code> , <code>origin_y</code>). Ignored when <code>`origin_fn`</code> is not <code>NULL</code> .
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of <code>`cols`</code> . Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.

degrees_col_name	Name of new column with the degrees. If NULL, no column is added.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Details

Applies the following rotation matrix:

$$\begin{bmatrix} \cos\theta & , & -\sin\theta \\ \sin\theta & , & \cos\theta \end{bmatrix}$$

That is:

$$x' = x\cos\theta - y\sin\theta$$

$$y' = x\sin\theta + y\cos\theta$$

Where θ is the angle in radians.

As specified at [Wikipedia/Rotation_matrix](#).

Value

data.frame (tibble) with seven new columns containing the rotated x-,y- and z-values and the degrees, radiuses and origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other rotation functions: [rotate_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "Index" = 1:12,
  "A" = c(1:4, 9:12, 15:18),
  "G" = rep(1:3, each = 4)
)
```

```

# Rotate values around (0, 0)
rotate_2d(df, degrees = 45, x_col = "Index", y_col = "A", origin = c(0, 0))

# Rotate A around the centroid
df_rotated <- df %>%
  rotate_2d(
    x_col = "Index",
    y_col = "A",
    degrees = c(0, 120, 240),
    origin_fn = centroid
  )
df_rotated

# Plot A and A rotated around overall centroid
ggplot(df_rotated, aes(x = Index_rotated, y = A_rotated, color = factor(.degrees))) +
  geom_hline(yintercept = mean(df$A), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_vline(xintercept = mean(df$Index), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_line(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "Index", y = "Value", color = "Degrees")

# Rotate around group centroids
df_grouped <- df %>%
  dplyr::group_by(G) %>%
  rotate_2d(
    x_col = "Index",
    y_col = "A",
    degrees = c(0, 120, 240),
    origin_fn = centroid
  )
df_grouped

# Plot A and A rotated around group centroids
ggplot(df_grouped, aes(x = Index_rotated, y = A_rotated, color = factor(.degrees))) +
  geom_point() +
  theme_minimal() +
  labs(x = "Index", y = "Value", color = "Degrees")

```

rotate_3d

Rotate the values around an origin in 3 dimensions

Description

Experimental

The values are rotated counterclockwise around a specified origin.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and rotating around e.g. the centroid of each group.

Usage

```

rotate_3d(
  data,

```

```

    x_col,
    y_col,
    z_col,
    x_deg = 0,
    y_deg = 0,
    z_deg = 0,
    suffix = "_rotated",
    origin = NULL,
    origin_fn = NULL,
    keep_original = TRUE,
    degrees_col_name = ".degrees",
    origin_col_name = ".origin",
    overwrite = FALSE
)

```

Arguments

<code>data</code>	data.frame or vector.
<code>x_col, y_col, z_col</code>	Name of x/y/z column in `data`. All must be specified.
<code>x_deg, y_deg, z_deg</code>	Degrees to rotate values around the x/y/z-axis counterclockwise. In $[-360, 360]$. Can be vectors with multiple degrees. `x_deg` is <i>roll</i> . `y_deg` is <i>pitch</i> . `z_deg` is <i>yaw</i> .
<code>suffix</code>	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
<code>origin</code>	Coordinates of the origin to rotate around. Vector with 3 elements (i.e. <code>origin_x, origin_y, origin_z</code>). Ignored when `origin_fn` is not NULL.
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>create_origin_fn(median)</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>degrees_col_name</code>	Name of new column with the degrees. If NULL, no column is added. Also adds a string version with the same name + "_str", making it easier to group by the degrees when plotting multiple rotations.
<code>origin_col_name</code>	Name of new column with the origin coordinates. If NULL, no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Details

Applies the following rotation matrix:

$$\begin{bmatrix} \cos\alpha\cos\beta & , \cos\alpha\sin\beta\sin\gamma - \sin\alpha\cos\gamma & , \cos\alpha\sin\beta\cos\gamma + \sin\alpha\sin\gamma \\ \sin\alpha\cos\beta & , \sin\alpha\sin\beta\sin\gamma + \cos\alpha\cos\gamma & , \sin\alpha\sin\beta\cos\gamma - \cos\alpha\sin\gamma \\ -\sin\beta & , \cos\beta\sin\gamma & , \cos\beta\cos\gamma \end{bmatrix}$$

Where $\alpha = \text{'z_deg'}$ in radians, $\beta = \text{'y_deg'}$ in radians, $\gamma = \text{'x_deg'}$ in radians.

As specified at [Wikipedia/Rotation_matrix](#).

Value

data.frame (tibble) with six new columns containing the rotated x-,y- and z-values and the degrees and origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other rotation functions: [rotate_2d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(3)

# Create a data frame
df <- data.frame(
  "x" = 1:12,
  "y" = c(1:4, 9:12, 15:18),
  "z" = runif(12),
  "g" = rep(1:3, each = 4)
)

# Rotate values 45 degrees around x-axis at (0, 0, 0)
rotate_3d(df, x_col = "x", y_col = "y", z_col = "z", x_deg = 45, origin = c(0, 0, 0))

# Rotate all axes around the centroid
df_rotated <- df %>%
  rotate_3d(
    x_col = "x",
    y_col = "y",
    z_col = "z",
    x_deg = c(0, 72, 144, 216, 288),
    y_deg = c(0, 72, 144, 216, 288),
    z_deg = c(0, 72, 144, 216, 288),
    origin_fn = centroid
  )
```

```

    )
df_rotated

# Plot rotations
ggplot(df_rotated, aes(x = x_rotated, y = y_rotated, color = .degrees_str, alpha = z_rotated)) +
  geom_vline(xintercept = mean(df$x), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$y), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_line(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "degrees", alpha = "z (opacity)")

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_rotated$x_rotated,
  y = df_rotated$y_rotated,
  z = df_rotated$z_rotated,
  type = "scatter3d",
  mode = "markers",
  color = df_rotated$.degrees_str
)

## End(Not run)

# Rotate randomly around all axes
df_rotated <- df %>%
  rotate_3d(
    x_col = "x",
    y_col = "y",
    z_col = "z",
    x_deg = round(runif(10, min = 0, max = 360)),
    y_deg = round(runif(10, min = 0, max = 360)),
    z_deg = round(runif(10, min = 0, max = 360)),
    origin_fn = centroid
  )
df_rotated

# Plot rotations
ggplot(df_rotated, aes(x = x_rotated, y = y_rotated, color = .degrees_str, alpha = z_rotated)) +
  geom_vline(xintercept = mean(df$x), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$y), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_line(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "degrees", alpha = "z (opacity)")

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_rotated$x_rotated,
  y = df_rotated$y_rotated,
  z = df_rotated$z_rotated,
  type = "scatter3d",
  mode = "markers",

```

```

    color = df_rotated$.degrees_str
  )

## End(Not run)

# Rotate around group centroids
df_grouped <- df %>%
  dplyr::group_by(g) %>%
  rotate_3d(
    x_col = "x",
    y_col = "y",
    z_col = "z",
    x_deg = c(0, 72, 144, 216, 288),
    y_deg = c(0, 72, 144, 216, 288),
    z_deg = c(0, 72, 144, 216, 288),
    origin_fn = centroid
  )

# Plot A and A rotated around group centroids
ggplot(df_grouped, aes(x = x_rotated, y = y_rotated, color = .degrees_str, alpha = z_rotated)) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "degrees", alpha = "z (opacity)")

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_grouped$x_rotated,
  y = df_grouped$y_rotated,
  z = df_grouped$z_rotated,
  type = "scatter3d",
  mode = "markers",
  color = df_grouped$.degrees_str
)

## End(Not run)

```

shear_2d

Shear the values around an origin in 2 dimensions

Description

Experimental

Shear a set of 2d points around an origin. The shearing formulas (excluding the origin movements) is:

$$x' = x + x_shear * y$$

$$y' = y + y_shear * x$$

The data points in `data` are moved prior to the shearing, to bring the origin to 0 in all dimensions. After the shearing, the inverse move is applied to bring the origin back to its original position.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and shearing around e.g. the centroid of each group.

Usage

```
shear_2d(
  data,
  x_shear,
  y_shear = 0,
  x_col = NULL,
  y_col = NULL,
  suffix = "_sheared",
  origin = NULL,
  origin_fn = NULL,
  keep_original = TRUE,
  shear_col_name = ".shear",
  origin_col_name = ".origin",
  overwrite = FALSE
)
```

Arguments

data	data.frame or vector.
x_shear	Shear factor for the x dimension (numeric). Decides the amount of shearing. Can be a vector with multiple shear factors.
y_shear	Shear factor for the y dimension (numeric). Decides the amount of shearing. Can be a vector with multiple shear factors.
x_col	Name of x column in `data`.
y_col	Name of y column in `data`.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
origin	Coordinates of the origin to shear around. Vector with 2 elements (origin_x, origin_y). Ignored when `origin_fn` is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
shear_col_name	Name of new column with the shearing factors. If NULL, no column is added. Also adds a string version with the same name + "_str", making it easier to group by the shearing factors when plotting multiple shearings.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with sheared columns, the shearing factors and the origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other shearing functions: [shear_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Create a data frame
df <- data.frame(
  "x" = rep(1:6, each = 2),
  "y" = rep(c(1, 4), 6),
  "g" = rep(1:2, each = 6)
)

# Shear the x variable with regards to y
# around the centroid
df_sheared <- shear_2d(
  data = df,
  x_shear = 2.5,
  x_col = "x",
  y_col = "y",
  origin_fn = centroid
)

# Plot sheared data
# Black: original points
# Red: sheared points
df_sheared %>%
  ggplot(aes(x = x, y = y)) +
  geom_point() +
  geom_point(aes(x = x_sheared, y = y_sheared, color = "red")) +
  theme_minimal()

# Shear in both dimensions
df_sheared <- shear_2d(
  data = df,
  x_shear = 2.5,
  y_shear = 2.5,
  x_col = "x",
  y_col = "y",
  origin_fn = centroid
)

# Plot sheared data
# Black: original points
# Red: sheared points
```



```

df_sheared %>%
  ggplot(aes(x = x, y = y)) +
  geom_point() +
  geom_point(aes(x = x_sheared, y = y_sheared, color = "red")) +
  theme_minimal()

# Shear grouped data frame
# Affects the calculated origin
df_sheared <- shear_2d(
  data = dplyr::group_by(df, g),
  x_shear = 2.5,
  x_col = "x",
  y_col = "y",
  origin_fn = centroid
)

# Plot sheared data
# Black: original points
# Red: sheared points
df_sheared %>%
  ggplot(aes(x = x, y = y)) +
  geom_point() +
  geom_point(aes(x = x_sheared, y = y_sheared, color = "red")) +
  theme_minimal()

# Shear a vector with multiple shearing factors
shear_2d(
  data = c(1:10),
  x_shear = c(1, 1.5, 2, 2.5),
  origin = c(0, 0)
)

```

shear_3d

Shear values around an origin in 3 dimensions

Description

Experimental

Shears points around an origin in 3-dimensional space. See applied shearing matrices under **Details**.

The data points in `data` are moved prior to the shearing, to bring the origin to 0 in all dimensions. After the shearing, the inverse move is applied to bring the origin back to its original position.

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and shearing around e.g. the centroid of each group.

Usage

```

shear_3d(
  data,
  x_col,
  y_col,
  z_col,
  x_shear = NULL,

```

```

y_shear = NULL,
z_shear = NULL,
suffix = "_sheared",
origin = NULL,
origin_fn = NULL,
keep_original = TRUE,
shear_col_name = ".shear",
origin_col_name = ".origin",
overwrite = FALSE
)

```

Arguments

<code>data</code>	data.frame or vector.
<code>x_col, y_col, z_col</code>	Name of x/y/z column in `data`. All must be specified.
<code>x_shear, y_shear, z_shear</code>	Shear factor for the x/y/z dimension (numeric). Decides the amount of shearing. Can be vectors with multiple shear factors. N.B. Exactly 2 of the dimensions must have shear factors specified.
<code>suffix</code>	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
<code>origin</code>	Coordinates of the origin to shear around. Vector with 3 elements (i.e. <code>origin_x</code> , <code>origin_y</code> , <code>origin_z</code>). Ignored when `origin_fn` is not NULL.
<code>origin_fn</code>	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of `cols`. Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>shear_col_name</code>	Name of new column with the shearing amounts. If NULL, no column is added. Also adds a string version with the same name + "_str", making it easier to group by the shearing amounts when plotting multiple shears.
<code>origin_col_name</code>	Name of new column with the origin coordinates. If NULL, no column is added.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Details

Applies one of the following transformation matrices, depending on which two shearing amounts are specified:

Given `x_shear` and `y_shear`:

$$\begin{bmatrix} 1 & , 0 & , x_shear \\ 0 & , 1 & , y_shear \\ 0 & , 0 & , 1 \end{bmatrix}$$

Given `x_shear` and `z_shear`:

$$\begin{bmatrix} 1 & , x_shear & , 0 \\ 0 & , 1 & , 0 \\ 0 & , z_shear & , 1 \end{bmatrix}$$

Given `y_shear` and `z_shear`:

$$\begin{bmatrix} 1 & , 0 & , 0 \\ y_shear & , 1 & , 0 \\ z_shear & , 0 & , 1 \end{bmatrix}$$

Value

data.frame (tibble) with six new columns containing the sheared x-, y- and z-values and the shearing amounts and origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [swirl_2d\(\)](#), [swirl_3d\(\)](#)

Other shearing functions: [shear_2d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(1)

df_square <- square(runif(100)) %>%
  rename(x = .square_x,
         y = Value) %>%
  mutate(z = 1)

# Shear the x and z axes
# around the centroid
df_sheared <- shear_3d(
  data = df_square,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  x_shear = 2,
  z_shear = 4,
  origin_fn = centroid
```

```

)

# Plot sheared data
# Black: original points
# Red: sheared points
df_sheared %>%
  ggplot(aes(x = x, y = y)) +
  geom_point() +
  geom_point(aes(x = x_sheared, y = y_sheared, color = "red")) +
  theme_minimal()

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_sheared$x_sheared,
  y = df_sheared$y_sheared,
  z = df_sheared$z_sheared,
  type = "scatter3d",
  mode = "markers",
  color = df_sheared$shear_str
)

## End(Not run)

# Shear the y and z axes
# around the centroid
df_sheared <- shear_3d(
  data = df_square,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  y_shear = 2,
  z_shear = 4,
  origin_fn = centroid
)

# Plot sheared data
# Black: original points
# Red: sheared points
df_sheared %>%
  ggplot(aes(x = x, y = y)) +
  geom_point() +
  geom_point(aes(x = x_sheared, y = y_sheared, color = "red")) +
  theme_minimal()

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_sheared$x_sheared,
  y = df_sheared$y_sheared,
  z = df_sheared$z_sheared,
  type = "scatter3d",
  mode = "markers",
  color = df_sheared$shear_str
)

## End(Not run)

```

```

# Shear the y and z axes with multiple amounts at once
# around the centroid
df_sheared <- shear_3d(
  data = df_square,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  y_shear = c(0, 2, 4),
  z_shear = c(0, 4, 6),
  origin_fn = centroid
)

# Plot sheared data
df_sheared %>%
  ggplot(aes(x = x_sheared, y = y_sheared, color = .shear_str)) +
  geom_point() +
  theme_minimal()

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_sheared$x_sheared,
  y = df_sheared$y_sheared,
  z = df_sheared$z_sheared,
  type = "scatter3d",
  mode = "markers",
  color = df_sheared$.shear_str
)

## End(Not run)

```

square

Create x-coordinates so the points form a square

Description

Experimental

Create the x-coordinates for a vector of y-coordinates such that they form a rotated square.

This will likely look most like a square when the y-coordinates are somewhat equally distributed, e.g. a uniform distribution.

Usage

```

square(
  data,
  y_col = NULL,
  .min = NULL,
  .max = NULL,
  offset_x = 0,
  keep_original = TRUE,
  x_col_name = ".square_x",
  edge_col_name = ".edge",

```

```
    overwrite = FALSE
  )
```

Arguments

<code>data</code>	<code>data.frame</code> or vector.
<code>y_col</code>	Name of column in <code>`data`</code> with y-coordinates to create x-coordinates for.
<code>.min</code>	Minimum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>.max</code>	Maximum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>offset_x</code>	Value to offset the x-coordinates by.
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>x_col_name</code>	Name of new column with the x-coordinates.
<code>edge_col_name</code>	Name of new column with the edge identifiers. If NULL, no column is added. Numbering is clockwise and starts at the upper-right edge.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Value

`data.frame` (tibble) with the added x-coordinates and an identifier for the edge the data point is a part of.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other forming functions: [circularize\(\)](#), [hexagonalize\(\)](#), [triangularize\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "y" = runif(200),
  "g" = factor(rep(1:5, each = 40))
)

# Square 'y'
df_sq <- square(df, y_col = "y")
df_sq
```

```

# Plot square
df_sq %>%
  ggplot(aes(x = .square_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Grouped squaring
#

# Square 'y' for each group
# First cluster the groups a bit to move the
# squares away from each other
df_sq <- df %>%
  cluster_groups(
    cols = "y",
    group_cols = "g",
    suffix = "",
    overwrite = TRUE
  ) %>%
  dplyr::group_by(g) %>%
  square(
    y_col = "y",
    overwrite = TRUE
  )

# Plot squares
df_sq %>%
  ggplot(aes(x = .square_x, y = y, color = g)) +
  geom_point() +
  theme_minimal()

#
# Specifying minimum value
#

# Specify minimum value manually
df_sq <- square(df, y_col = "y", .min = -2)
df_sq

# Plot square
df_sq %>%
  ggplot(aes(x = .square_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Multiple squares by contraction
#

# Start by squaring 'y'
df_sq <- square(df, y_col = "y")

# Contract '.square_x' and 'y' towards the centroid
# To contract with multiple multipliers at once,
# we wrap the call in purrr::map_dfr
df_expanded <- purrr::map_dfr(

```

```

.x = c(1, 0.75, 0.5, 0.25, 0.125),
.f = function(mult) {
  expand_distances(
    data = df_sq,
    cols = c(".square_x", "y"),
    multiplier = mult,
    origin_fn = centroid,
    overwrite = TRUE
  )
}
)
df_expanded

df_expanded %>%
  ggplot(aes(
    x = .square_x_expanded, y = y_expanded,
    color = .edge, alpha = .multiplier
  )) +
  geom_point() +
  theme_minimal()

```

swirl_2d

Swirl the values around an origin in 2 dimensions

Description

Experimental

The values are swirled counterclockwise around a specified origin. The swirling is done by rotating around the origin with the degrees based on the distances to the origin as so:

$$\text{degrees} = \text{scale_fn}(\text{distances}) / (2 * \text{radius}) * 360$$

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and swirling around e.g. the centroid of each group.

Usage

```

swirl_2d(
  data,
  radius,
  x_col = NULL,
  y_col = NULL,
  suffix = "_swirled",
  origin = NULL,
  origin_fn = NULL,
  scale_fn = identity,
  keep_original = TRUE,
  degrees_col_name = ".degrees",
  radius_col_name = ".radius",
  origin_col_name = ".origin",
  overwrite = FALSE
)

```


Arguments

data	data.frame or vector.
radius	Radius of the most-inner swirl on the x-axis in the <i>simplest</i> case. A negative number changes the direction to clockwise rotation. Can be a vector with multiple radiuses. Note: With a custom <code>`scaling_fn`</code> , this might not be the actual swirl radius anymore. Think of it more as a width setting where a larger number leads to fewer full rotations.
x_col	Name of x column in <code>`data`</code> . If NULL and <code>`data`</code> is a vector, the index of <code>`data`</code> is used. If <code>`data`</code> is a data.frame, it must be specified.
y_col	Name of y column in <code>`data`</code> . If <code>`data`</code> is a data.frame, it must be specified.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. <code>""</code>) to overwrite the original columns.
origin	Coordinates of the origin to swirl around. Vector with 2 elements (i.e. <code>origin_x</code> , <code>origin_y</code>). Ignored when <code>`origin_fn`</code> is not NULL.
origin_fn	Function for finding the origin coordinates. Input: Each column will be passed as a vector in the order of <code>`cols`</code> . Output: A vector with one scalar per dimension. Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension. E.g. <code>`create_origin_fn(median)`</code> would find the median of each column. Built-in functions are <code>centroid()</code> , <code>most_centered()</code> , and <code>midrange()</code>
scale_fn	Function for scaling the distances before calculating the degrees. Input: A numeric vector (the distances). Output: A numeric vector (the scaled distances) of the same length. E.g.: <pre>function(d){ d ^ 1.5 }</pre>
keep_original	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
degrees_col_name	Name of new column with the degrees. If NULL, no column is added.
radius_col_name	Name of new column with the radius. If NULL, no column is added.
origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with three new columns containing the swirled x- and y-values, the degrees, the radius, and the origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_3d\(\)](#)

Other rotation functions: [rotate_2d\(\)](#), [rotate_3d\(\)](#), [swirl_3d\(\)](#)

Other distance functions: [closest_to\(\)](#), [dim_values\(\)](#), [distance\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [furthest_from\(\)](#), [swirl_3d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(4)

# Create a data frame
df <- data.frame(
  "x" = 1:50,
  "y" = 1,
  "r1" = runif(50),
  "r2" = runif(50) * 35,
  "g" = rep(1:5, each = 10)
)

# Swirl values around (0, 0)
swirl_2d(
  data = df,
  radius = 45,
  x_col = "x",
  y_col = "y",
  origin = c(0, 0)
)

# Swirl around the centroid
# with 6 different radius settings
# Scale the distances with custom function
df_swirled <- swirl_2d(
  data = df,
  radius = c(95, 96, 97, 98, 99, 100),
  x_col = "x",
  y_col = "y",
  origin_fn = centroid,
  scale_fn = function(d) {
    d^1.6
  }
)

df_swirled

# Plot swirls
df_swirled %>%
```

```

ggplot(aes(x = x_swirled, y = y_swirled, color = factor(.radius))) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = ".radius")

#
# Swirl random data
# The trick lies in finding the right radius
#

# Swirl the random columns
df_swirled <- swirl_2d(
  data = df,
  radius = 5,
  x_col = "r1",
  y_col = "r2",
  origin_fn = centroid
)

# Plot swirls
df_swirled %>%
  ggplot(aes(x = r1_swirled, y = r2_swirled)) +
  geom_point() +
  theme_minimal() +
  labs(x = "r1", y = "r2")

```

swirl_3d

Swirl the values around an origin in 3 dimensions

Description

Experimental

The values are swirled counterclockwise around a specified origin. The swirling is done by rotating around the origin, basing the degrees for each rotation-axis on the distances to the origin as so:

$$x_{degrees} = scale_{fn}(distances)/(2 * x_{radius}) * 360$$

The origin can be supplied as coordinates or as a function that returns coordinates. The latter can be useful when supplying a grouped data.frame and swirling around e.g. the centroid of each group.

Usage

```

swirl_3d(
  data,
  x_col,
  y_col,
  z_col,
  x_radius = 0,
  y_radius = 0,
  z_radius = 0,
  suffix = "_swirled",
  origin = NULL,

```

```

origin_fn = NULL,
scale_fn = identity,
keep_original = TRUE,
degrees_col_name = ".degrees",
radius_col_name = ".radius",
origin_col_name = ".origin",
overwrite = FALSE
)

```

Arguments

<code>data</code>	data.frame or vector.
<code>x_col, y_col, z_col</code>	Name of x/y/z column in `data`. All must be specified.
<code>x_radius, y_radius, z_radius</code>	<p>Radiuses of the most-inner swirls around each axis (in the <i>simplest</i> case). Can be vectors with multiple radiuses.</p> <p>E.g. the `x_radius` specifies the radius when rotating <i>around</i> the x-axis, not the radius <i>on</i> the x-axis.</p> <p>Note: With a custom `scaling_fn`, these might not be the actual swirl radiuses anymore. Think of them more as width settings where a larger number leads to fewer full rotations.</p>
<code>suffix</code>	<p>Suffix to add to the names of the generated columns.</p> <p>Use an empty string (i.e. "") to overwrite the original columns.</p>
<code>origin</code>	Coordinates of the origin to swirl around. Vector with 3 elements (i.e. <code>origin_x</code> , <code>origin_y</code> , <code>origin_z</code>). Ignored when `origin_fn` is not NULL.
<code>origin_fn</code>	<p>Function for finding the origin coordinates.</p> <p>Input: Each column will be passed as a vector in the order of `cols`.</p> <p>Output: A vector with one scalar per dimension.</p> <p>Can be created with <code>create_origin_fn()</code> if you want to apply the same function to each dimension.</p> <p>E.g. <code>create_origin_fn(median)</code> would find the median of each column.</p> <p>Built-in functions are <code>centroid()</code>, <code>most_centered()</code>, and <code>midrange()</code></p>
<code>scale_fn</code>	<p>Function for scaling the distances before calculating the degrees.</p> <p>Input: A numeric vector (the distances).</p> <p>Output: A numeric vector (the scaled distances) of the same length.</p> <p>E.g.:</p> <pre>function(d){ d ^ 1.5 }</pre>
<code>keep_original</code>	<p>Whether to keep the original columns. (Logical)</p> <p>Some columns may have been overwritten, in which case only the newest versions are returned.</p>
<code>degrees_col_name</code>	<p>Name of new column with the degrees. If NULL, no column is added.</p> <p>Also adds a string version with the same name + "_str", making it easier to group by the degrees when plotting multiple rotations.</p>
<code>radius_col_name</code>	Name of new column with the radiuses. If NULL, no column is added.

origin_col_name	Name of new column with the origin coordinates. If NULL, no column is added.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with new columns containing the swirled x- and y-values, the degrees, the radiuses, and the origin coordinates.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other mutate functions: [apply_transformation_matrix\(\)](#), [cluster_groups\(\)](#), [dim_values\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [flip_values\(\)](#), [roll_values\(\)](#), [rotate_2d\(\)](#), [rotate_3d\(\)](#), [shear_2d\(\)](#), [shear_3d\(\)](#), [swirl_2d\(\)](#)

Other rotation functions: [rotate_2d\(\)](#), [rotate_3d\(\)](#), [swirl_2d\(\)](#)

Other distance functions: [closest_to\(\)](#), [dim_values\(\)](#), [distance\(\)](#), [expand_distances_each\(\)](#), [expand_distances\(\)](#), [furthest_from\(\)](#), [swirl_2d\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(ggplot2)

# Set seed
set.seed(4)

# Create a data frame
df <- data.frame(
  "x" = 1:50,
  "y" = 1:50,
  "z" = 1:50,
  "r1" = runif(50),
  "r2" = runif(50) * 35,
  "o" = 1,
  "g" = rep(1:5, each = 10)
)

# Swirl values around (0, 0, 0)
swirl_3d(
  data = df,
  x_radius = 45,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  origin = c(0, 0, 0)
)

# Swirl around the centroid
df_swirled <- swirl_3d(
```

```

    data = df,
    x_col = "x",
    y_col = "y",
    z_col = "z",
    x_radius = c(100, 0, 0),
    y_radius = c(0, 100, 0),
    z_radius = c(0, 0, 100),
    origin_fn = centroid
  )

df_swirled

# Plot swirls
ggplot(df_swirled, aes(x = x_swirled, y = y_swirled, color = .radius_str, alpha = z_swirled)) +
  geom_vline(xintercept = mean(df$x), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$y), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_path(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "radius", alpha = "z (opacity)")

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_swirled$x_swirled,
  y = df_swirled$y_swirled,
  z = df_swirled$z_swirled,
  type = "scatter3d",
  mode = "markers",
  color = df_swirled$.radius_str
)

## End(Not run)

# Swirl around the centroid
df_swirled <- swirl_3d(
  data = df,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  x_radius = c(50, 0, 0),
  y_radius = c(0, 50, 0),
  z_radius = c(0, 0, 50),
  origin_fn = centroid
)

df_swirled

# Plot swirls
ggplot(df_swirled, aes(x = x_swirled, y = y_swirled, color = .radius_str, alpha = z_swirled)) +
  geom_vline(xintercept = mean(df$x), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$y), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_path(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "radius", alpha = "z (opacity)")

```

```

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_swirled$x_swirled,
  y = df_swirled$y_swirled,
  z = df_swirled$z_swirled,
  type = "scatter3d",
  mode = "markers",
  color = df_swirled$.radius_str
)

## End(Not run)

df_swirled <- swirl_3d(
  data = df,
  x_col = "x",
  y_col = "y",
  z_col = "z",
  x_radius = c(25, 50, 25, 25),
  y_radius = c(50, 75, 100, 25),
  z_radius = c(75, 25, 25, 25),
  origin_fn = centroid,
  scale_fn = function(x) {
    x^0.81
  }
)

# Plot swirls
ggplot(df_swirled, aes(x = x_swirled, y = y_swirled, color = .radius_str, alpha = z_swirled)) +
  geom_vline(xintercept = mean(df$x), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$y), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_path(alpha = .4) +
  geom_point() +
  theme_minimal() +
  labs(x = "x", y = "y", color = "radius", alpha = "z (opacity)")

## Not run:
# Plot 3d with plotly
plotly::plot_ly(
  x = df_swirled$x_swirled,
  y = df_swirled$y_swirled,
  z = df_swirled$z_swirled,
  type = "scatter3d",
  mode = "markers",
  color = df_swirled$.radius_str
)

## End(Not run)

#
# Swirl random data
# The trick lies in finding the right radiuses
#

```

```

# Swirl the random columns
df_swirled <- swirl_3d(
  data = df,
  x_col = "r1",
  y_col = "r2",
  z_col = "o",
  x_radius = c(0, 0, 0, 0),
  y_radius = c(0, 30, 60, 90),
  z_radius = c(10, 10, 10, 10),
  origin_fn = centroid
)

# Not let's rotate it every 10 degrees
df_rotated <- df_swirled %>%
  rotate_3d(
    x_col = "r1_swirled",
    y_col = "r2_swirled",
    z_col = "o_swirled",
    x_deg = rep(0, 36),
    y_deg = rep(0, 36),
    z_deg = (1:36) * 10,
    suffix = "",
    origin = df_swirled$.origin[[1]],
    overwrite = TRUE
  )

# Plot rotated swirls
ggplot(
  df_rotated,
  aes(
    x = r1_swirled,
    y = r2_swirled,
    color = .degrees_str,
    alpha = o_swirled
  )
) +
  geom_vline(xintercept = mean(df$r1), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_hline(yintercept = mean(df$r2), size = 0.2, alpha = .4, linetype = "dashed") +
  geom_point(show.legend = FALSE) +
  theme_minimal() +
  labs(x = "r1", y = "r2", color = "radius", alpha = "o (opacity)")

```

to_unit_length

Scale to unit length

Description

Experimental

Scales the vectors to unit length *row-wise* or *column-wise*.

The `*_vec()` version take and return a vector.

Usage

```
to_unit_length(  
  data,  
  cols = NULL,  
  by_row = is.data.frame(data),  
  suffix = ifelse(isTRUE(by_row), "_row_unit", "_col_unit"),  
  overwrite = FALSE  
)  
  
to_unit_length_vec(data)
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to scale.
by_row	Whether to scale row vectors instead of column vectors. (Logical) Note: Disable when `data` is a vector.
suffix	Suffix to add to the names of the generated columns. Use an empty string (i.e. "") to overwrite the original columns.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

Scaled vector or data.frame (tibble) with the scaled columns.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other scaling functions: [min_max_scale\(\)](#)

Examples

```
# Attach packages  
library(rearr)   
library(dplyr)  
  
# Set seed  
set.seed(1)  
  
# Create a data frame  
df <- data.frame(  
  "x" = runif(20),  
  "y" = runif(20),  
  "g" = rep(1:4, each = 5)  
)  
  
# Scale row-wise  
to_unit_length(df, cols = c("x", "y"), by_row = TRUE)  
  
# Scale column-wise
```

```

to_unit_length(df, cols = c("x", "y"), by_row = FALSE)

# Overwrite columns
to_unit_length(df, cols = c("x", "y"), suffix = "", overwrite = TRUE)

# By groups in 'g'
df %>%
  dplyr::group_by(g) %>%
  to_unit_length(cols = c("x", "y"), by_row = FALSE)

# Scale a vector
to_unit_length_vec(c(1:10))
to_unit_length(c(1:10), suffix = "", overwrite = TRUE)
vector_length(to_unit_length_vec(c(1:10)))

```

transfer_centroids	<i>Transfer centroids from one data frame to another</i>
--------------------	--

Description

Experimental

Given two data.frames with the same columns (and groupings), transfer the centroids from one to the other.

This is commonly used to restore the centroids after transforming the columns.

Usage

```
transfer_centroids(to_data, from_data, cols, group_cols = NULL)
```

Arguments

to_data	data.frame. Existing `dplyr` groups are ignored. Specify in `group_cols` instead.
from_data	data.frame with the same columns (and groupings) as `to_data`. Existing `dplyr` groups are ignored. Specify in `group_cols` instead.
cols	Names of numeric columns to transfer centroids to. Must exist in both `to_data` and `from_data`.
group_cols	Names of grouping columns.

Value

The `to_data` data.frame (tibble) with the centroids from the `from_data` data.frame.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other clustering functions: [cluster_groups\(\)](#), [generate_clusters\(\)](#)

Examples

```

# Attach packages
library(rearr)
library(dplyr)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "x" = runif(20),
  "y" = runif(20),
  "g" = rep(1:4, each = 5)
)

# Create another data frame with different x and y values
df2 <- df
df2$x <- runif(20)
df2$y <- runif(20)

# Check centroids before transfer

df %>%
  dplyr::group_by(g) %>%
  dplyr::summarize_all(mean)

df2 %>%
  dplyr::group_by(g) %>%
  dplyr::summarize_all(mean)

# Now let's transfer the centroids from df to df2

df3 <- transfer_centroids(
  to_data = df2,
  from_data = df,
  cols = c("x", "y"),
  group_cols = "g"
)

# Check that the transfer gave us the same centroids as df
df3 %>%
  dplyr::group_by(g) %>%
  dplyr::summarize_all(mean)

```

triangularize

Create x-coordinates so the points form a triangle

Description**Experimental**

Create the x-coordinates for a vector of y-coordinates such that they form a triangle.

The data points are stochastically distributed based on edge lengths, why it might be preferable to set a random seed.

This will likely look most like a triangle when the y-coordinates are somewhat equally distributed, e.g. a uniform distribution.

Usage

```
triangularize(
  data,
  y_col = NULL,
  .min = NULL,
  .max = NULL,
  offset_x = 0,
  keep_original = TRUE,
  x_col_name = ".triangle_x",
  edge_col_name = ".edge",
  overwrite = FALSE
)
```

Arguments

<code>data</code>	data.frame or vector.
<code>y_col</code>	Name of column in `data` with y-coordinates to create x-coordinates for.
<code>.min</code>	Minimum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>.max</code>	Maximum y-coordinate. If NULL, it is inferred by the given y-coordinates.
<code>offset_x</code>	Value to offset the x-coordinates by.
<code>keep_original</code>	Whether to keep the original columns. (Logical) Some columns may have been overwritten, in which case only the newest versions are returned.
<code>x_col_name</code>	Name of new column with the x-coordinates.
<code>edge_col_name</code>	Name of new column with the edge identifiers. If NULL, no column is added. Numbering is clockwise and starts at the upper-right edge.
<code>overwrite</code>	Whether to allow overwriting of existing columns. (Logical)

Value

data.frame (tibble) with the added x-coordinates and an identifier for the edge the data point is a part of.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other forming functions: [circularize\(\)](#), [hexagonalize\(\)](#), [square\(\)](#)

Examples

```
# Attach packages
library(rearr)
library(dplyr)
library(purrr)
```

```

library(ggplot2)

# Set seed
set.seed(1)

# Create a data frame
df <- data.frame(
  "y" = runif(200),
  "g" = factor(rep(1:5, each = 40))
)

# Triangularize 'y'
df_tri <- triangularize(df, y_col = "y")
df_tri

# Plot triangle
df_tri %>%
  ggplot(aes(x = .triangle_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Grouped squaring
#

# Triangularize 'y' for each group
# First cluster the groups a bit to move the
# triangles away from each other
df_tri <- df %>%
  cluster_groups(
    cols = "y",
    group_cols = "g",
    suffix = "",
    overwrite = TRUE
  ) %>%
  dplyr::group_by(g) %>%
  triangularize(
    y_col = "y",
    overwrite = TRUE
  )

# Plot triangles
df_tri %>%
  ggplot(aes(x = .triangle_x, y = y, color = g)) +
  geom_point() +
  theme_minimal()

#
# Specifying minimum value
#

# Specify minimum value manually
df_tri <- triangularize(df, y_col = "y", .min = -2)
df_tri

# Plot triangle
df_tri %>%

```

```

ggplot(aes(x = .triangle_x, y = y, color = .edge)) +
  geom_point() +
  theme_minimal()

#
# Multiple triangles by contraction
#

# Start by squaring 'y'
df_tri <- triangularize(df, y_col = "y")

# Contract '.triangle_x' and 'y' towards the centroid
# To contract with multiple multipliers at once,
# we wrap the call in purrr::map_dfr
df_expanded <- purrr::map_dfr(
  .x = 1:10 / 10,
  .f = function(mult) {
    expand_distances(
      data = df_tri,
      cols = c(".triangle_x", "y"),
      multiplier = mult,
      origin_fn = centroid,
      overwrite = TRUE
    )
  }
)
df_expanded

df_expanded %>%
  ggplot(aes(
    x = .triangle_x_expanded, y = y_expanded,
    color = .edge, alpha = .multiplier
  )) +
  geom_point() +
  theme_minimal()

```

vector_length	<i>Calculate vector length(s)</i>
---------------	-----------------------------------

Description

Experimental

Calculates vector lengths/magnitudes *row-* or *column-wise* with

$$\sqrt{\text{sum}(x^2)}$$

Where x is the vector to get the length/magnitude of.

Should not be confused with `length()`, which counts the elements.

Usage

```
vector_length(  
  data,  
  cols = NULL,  
  by_row = is.data.frame(data),  
  len_col_name = ".vec_len",  
  overwrite = FALSE  
)
```

Arguments

data	data.frame or vector.
cols	Names of columns in `data` to measure vector length of.
by_row	Whether to measure length of row vectors instead of column vectors. (Logical) Note: Disable when `data` is a vector.
len_col_name	Name of new column with the row vector lengths when `data` is a data.frame and `by_row` is TRUE.
overwrite	Whether to allow overwriting of existing columns. (Logical)

Value

Vector length(s).

When `data` is a vector: scalar

When `data` is a data.frame and `by_row` is TRUE: `data` with an extra column with row vector lengths.

When `data` is a data.frame and `by_row` is FALSE: A data.frame with the summarized column vector lengths.

Author(s)

Ludvig Renbo Olsen, <r-pkgs@ludvigolsen.dk>

See Also

Other measuring functions: [angle\(\)](#), [distance\(\)](#)

Examples

```
# Attach packages  
library(rearr)   
library(dplyr)  
  
# Set seed  
set.seed(1)  
  
# Create a data frame  
df <- data.frame(  
  "x" = runif(20),  
  "y" = runif(20),  
  "g" = rep(1:4, each = 5)  
)
```

```
# Measure row-wise
vector_length(df, cols = c("x", "y"), by_row = TRUE)

# Measure column-wise
vector_length(df, cols = c("x", "y"), by_row = FALSE)

# By groups in 'g'
df %>%
  dplyr::group_by(g) %>%
  vector_length(cols = c("x", "y"), by_row = FALSE)

# Measure vector length of a vector
vector_length(c(1:10))
```


Index

angle, [2](#), [31](#), [103](#)
apply_transformation_matrix, [4](#), [19](#), [28](#),
[33](#), [38](#), [42](#), [70](#), [73](#), [76](#), [80](#), [83](#), [90](#), [93](#)

ceiling, [23](#), [53](#)
center_max, [7](#), [9](#), [16](#), [45](#), [60](#), [62](#), [63](#), [65](#), [67](#)
center_min, [8](#), [9](#), [16](#), [45](#), [60](#), [62](#), [63](#), [65](#), [67](#)
centroid, [10](#), [24](#), [52](#), [55](#), [57](#)
centroid(), [3](#), [5](#), [15](#), [27](#), [30](#), [32](#), [37](#), [42](#), [45](#),
[72](#), [75](#), [79](#), [82](#), [89](#), [92](#)
circularize, [12](#), [50](#), [86](#), [100](#)
closest_to, [8](#), [9](#), [14](#), [28](#), [31](#), [33](#), [38](#), [45](#), [60](#),
[62](#), [63](#), [65](#), [67](#), [90](#), [93](#)
closest_to_vec (closest_to), [14](#)
cluster_groups, [6](#), [17](#), [28](#), [33](#), [38](#), [42](#), [48](#), [70](#),
[73](#), [76](#), [80](#), [83](#), [90](#), [93](#), [98](#)
cluster_groups(), [47](#)
create_dimming_fn, [21](#), [23](#), [24](#)
create_dimming_fn(), [26](#), [27](#)
create_n_fn, [21](#), [22](#), [24](#), [54](#)
create_n_fn(), [53](#), [67](#)
create_origin_fn, [11](#), [21](#), [23](#), [24](#), [52](#), [55](#), [57](#)
create_origin_fn(), [3](#), [5](#), [15](#), [27](#), [30](#), [32](#), [37](#),
[42](#), [45](#), [72](#), [75](#), [79](#), [82](#), [89](#), [92](#)

degrees_to_radians, [25](#)
dim_values, [6](#), [16](#), [19](#), [26](#), [31](#), [33](#), [38](#), [42](#), [45](#),
[70](#), [73](#), [76](#), [80](#), [83](#), [90](#), [93](#)
distance, [4](#), [16](#), [28](#), [29](#), [33](#), [38](#), [45](#), [90](#), [93](#), [103](#)
dplyr::group_by(), [18](#)

expand_distances, [6](#), [16](#), [19](#), [28](#), [31](#), [31](#), [38](#),
[42](#), [45](#), [70](#), [73](#), [76](#), [80](#), [83](#), [90](#), [93](#)
expand_distances(), [36](#)
expand_distances_each, [6](#), [16](#), [19](#), [28](#), [31](#),
[33](#), [36](#), [42](#), [45](#), [70](#), [73](#), [76](#), [80](#), [83](#), [90](#),
[93](#)
expand_distances_each(), [32](#)

farthest_from (furthest_from), [44](#)
flip_values, [6](#), [19](#), [28](#), [33](#), [38](#), [41](#), [70](#), [73](#), [76](#),
[80](#), [83](#), [90](#), [93](#)
flip_values_vec (flip_values), [41](#)
floor, [23](#), [53](#)

furthest_from, [8](#), [9](#), [16](#), [28](#), [31](#), [33](#), [38](#), [44](#),
[60](#), [62](#), [63](#), [65](#), [67](#), [90](#), [93](#)
furthest_from_vec (furthest_from), [44](#)

generate_clusters, [19](#), [47](#), [98](#)

hexagonalize, [13](#), [49](#), [86](#), [100](#)

identity, [23](#)
is_most_centered, [11](#), [24](#), [51](#), [55](#), [57](#)
is_most_centered(), [57](#)

length(), [102](#)

matrix multiplication, [5](#)
median_index, [23](#), [53](#)
median_index(), [67](#)
midrange, [11](#), [24](#), [52](#), [54](#), [57](#)
midrange(), [3](#), [5](#), [15](#), [27](#), [30](#), [32](#), [37](#), [42](#), [45](#),
[72](#), [75](#), [79](#), [82](#), [89](#), [92](#)
min_max_scale, [55](#), [97](#)
most_centered, [11](#), [24](#), [52](#), [55](#), [57](#)
most_centered(), [3](#), [5](#), [15](#), [27](#), [30](#), [32](#), [37](#), [42](#),
[45](#), [52](#), [72](#), [75](#), [79](#), [82](#), [89](#), [92](#)

pair_extremes, [8](#), [9](#), [16](#), [45](#), [58](#), [62](#), [63](#), [65](#), [67](#)
pair_extremes_vec (pair_extremes), [58](#)
position_max, [8](#), [9](#), [16](#), [45](#), [60](#), [61](#), [63](#), [65](#), [67](#)
position_min, [8](#), [9](#), [16](#), [45](#), [60](#), [62](#), [63](#), [65](#), [67](#)

quantile(), [53](#)
quantile_index (median_index), [53](#)
quantile_index(), [67](#)

radians_to_degrees
(degrees_to_radians), [25](#)
rev_windows, [8](#), [9](#), [16](#), [45](#), [60](#), [62](#), [63](#), [64](#), [67](#)
rev_windows_vec (rev_windows), [64](#)
roll_elements, [8](#), [9](#), [16](#), [45](#), [60](#), [62](#), [63](#), [65](#),
[66](#), [70](#)
roll_elements(), [22](#), [68](#)
roll_elements_vec (roll_elements), [66](#)
roll_values, [6](#), [19](#), [28](#), [33](#), [38](#), [42](#), [67](#), [68](#), [73](#),
[76](#), [80](#), [83](#), [90](#), [93](#)
roll_values(), [66](#)

`roll_values_vec (roll_values)`, 68
`rotate_2d`, 6, 19, 28, 33, 38, 42, 70, 72, 76,
80, 83, 90, 93
`rotate_3d`, 6, 19, 28, 33, 38, 42, 70, 73, 74,
80, 83, 90, 93
`round`, 23, 53

`shear_2d`, 6, 19, 28, 33, 38, 42, 70, 73, 76, 78,
83, 90, 93
`shear_3d`, 6, 19, 28, 33, 38, 42, 70, 73, 76, 80,
81, 90, 93
`square`, 13, 50, 85, 100
`swirl_2d`, 6, 16, 19, 28, 31, 33, 38, 42, 45, 70,
73, 76, 80, 83, 88, 93
`swirl_3d`, 6, 16, 19, 28, 31, 33, 38, 42, 45, 70,
73, 76, 80, 83, 90, 91

`to_unit_length`, 56, 96
`to_unit_length_vec (to_unit_length)`, 96
`transfer_centroids`, 19, 48, 98
`triangularize`, 13, 50, 86, 99

`vector_length`, 4, 31, 102

`wrap_to_range (roll_values)`, 68
`wrap_to_range_vec (roll_values)`, 68