

Package ‘factorEx’

November 28, 2025

Type Package

Title Design and Analysis for Factorial Experiments

Version 1.1.0

Maintainer Naoki Egami <naoki.egami5@gmail.com>

Description Provides design-based and model-based estimators for the population average marginal component effects in general factorial experiments, including conjoint analysis. The package also implements a series of recommendations offered in de la Cuesta, Egami, and Imai (2022) <[doi:10.1017/pan.2020.40](https://doi.org/10.1017/pan.2020.40)>, and Egami and Imai (2019) <[doi:10.1080/01621419.2019.1644444](https://doi.org/10.1080/01621419.2019.1644444)>

License GPL-2

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Depends R (>= 3.5.0), arm, genlasso

Imports prodlim, sandwich, igraph, pbmcapply, pbapply, mvtnorm, stringr, doParallel, foreach, estimatr

URL <https://github.com/naoki-egami/factorEx>

BugReports <https://github.com/naoki-egami/factorEx/issues>

NeedsCompilation no

Author Naoki Egami [aut, cre],
Brandon de la Cuesta [aut],
Kosuke Imai [aut]

Repository CRAN

Date/Publication 2025-11-28 09:50:07 UTC

Contents

decompose_pAMCE	2
design_pAMCE	2
diagnose_pAMCE	4
model_pAMCE	5

OnoBurden	7
plot.pAMCE	7
plot_decompose	8
plot_diagnose	9
summary.pAMCE	10
weights_pAMCE	10

Index	12
--------------	-----------

decompose_pAMCE	<i>Decompose the difference between the pAMCEs</i>
-----------------	--

Description

See examples in 'model_pAMCE'.

Usage

```
decompose_pAMCE(out, effect_name, target_diff)
```

Arguments

out	An object of class "pAMCE", a result of a call to 'model_pAMCE'.
effect_name	Effect for which the function decomposes the difference in the pAMCEs. The first element should be a factor name and the second element should be a level name.
target_diff	Two target profile distributions for which the function compares the pAMCEs. If missing, the function compares the first target profile distribution and the in-sample profile distribution.

Value

decompose_pAMCE returns 'data.frame' showing the decomposition of the difference between the pAMCEs.

design_pAMCE	<i>Estimating the population AMCE using a design-based approach</i>
--------------	---

Description

design_pAMCE implements the design-based approach to estimate the pAMCE. See de la Cuesta, Egami, and Imai (2022) for details. More examples are available at the GitHub page of factorEx.

Usage

```
design_pAMCE(
  formula,
  factor_name,
  data,
  pair = FALSE,
  pair_id = NULL,
  cross_int = FALSE,
  cluster_id = NULL,
  target_dist,
  target_type,
  partial_joint_name
)
```

Arguments

formula	Formula
factor_name	Factors for which the function estimates the pAMCEs. If not specified, the function estimates for all factors.
data	Data
pair	Whether we use a paired-choice conjoint design.
pair_id	Unique identifiers for pairs in the paired-choice conjoint design (optional).
cross_int	Include interactions across profiles. Default is FALSE.
cluster_id	Unique identifiers for computing cluster standard errors (optional).
target_dist	Target profile distributions to be used. See Examples in the GitHub page for details.
target_type	Types of target profile distributions. 'marginal', 'partial_joint', or 'target_data'.
partial_joint_name	(when 'target_type = "partial_joint"') Names of factors representing partial joint distributions. See Examples in the GitHub page for details.

Value

design_pAMCE returns an object of pAMCE class.

- AMCE: Estimates of the pAMCE for all factors.
- design_weight: Weight for each observation used in the weighted difference-in-means.
- approach: "design_based"
- input: Input into the function.
- ...: Values for internal use.

References

de la Cuesta, Egami, and Imai. (2022). Improving the External Validity of Conjoint Analysis: The Essential Role of Profile Distribution. *Political Analysis*.

Egami and Imai. (2019). Causal Interaction in Factorial Experiments: Application to Conjoint Analysis. *Journal of the American Statistical Association*, Vol.114, No.526 (June), pp. 529–540.

Examples

```

# Small example
data("OnoBurden")
OnoBurden_data_pr_s <- OnoBurden$OnoBurden_data_pr[1:500, ]
# randomization based on marginal population design
target_dist_marginal_s <- OnoBurden$target_dist_marginal[c("gender", "age")]

# design-based estimation
out_design_mar_s <-
  design_pAMCE(formula = Y ~ gender + age,
               factor_name = "gender",
               data = OnoBurden_data_pr_s,
               pair_id = OnoBurden_data_pr_s$pair_id,
               cluster_id = OnoBurden_data_pr_s$id,
               target_dist = target_dist_marginal_s, target_type = "marginal")
summary(out_design_mar_s)

# Example
data("OnoBurden")
OnoBurden_data_pr <- OnoBurden$OnoBurden_data_pr
# randomization based on marginal population design
target_dist_marginal <- OnoBurden$target_dist_marginal

# design-based estimation
out_design_mar <-
  design_pAMCE(formula = Y ~ gender + age + family + race + experience + party + pos_security,
               factor_name = c("gender", "age", "experience"),
               data = OnoBurden_data_pr,
               pair_id = OnoBurden_data_pr$pair_id,
               cluster_id = OnoBurden_data_pr$id,
               target_dist = target_dist_marginal, target_type = "marginal")
summary(out_design_mar)

```

diagnose_pAMCE

Diagnose modeling assumptions for the model-based approach

Description

Diagnose modeling assumptions for the model-based approach

Usage

```
diagnose_pAMCE(x, factor_name)
```

Arguments

x An object of class "pAMCE", a result of a call to 'model_pAMCE'.

factor_name A factor for which the function diagnoses modeling assumptions.

Value

No return value, called for side effects

model_pAMCE	<i>Estimating the population AMCE using a model-based approach</i>
-------------	--

Description

model_pAMCE implements the model-based approach to estimate the pAMCE. See de la Cuesta, Egami, and Imai (2022) for details. More examples are available at the GitHub page of factorEx.

Usage

```
model_pAMCE(
  formula,
  formula_three = NULL,
  data,
  reg = TRUE,
  ord_fac,
  pair = FALSE,
  pair_id = NULL,
  cross_int = FALSE,
  cluster_id = NULL,
  target_dist,
  target_type,
  difference = FALSE,
  cv_type = "cv.1Std",
  nfolds = 5,
  boot = 100,
  seed = 1234,
  numCores = NULL
)
```

Arguments

formula	Formula
formula_three	Formula for three-way interactions (optional)
data	Data
reg	TRUE (regularization) or FALSE (no regularization). Default is TRUE
ord_fac	Whether we assume each factor is ordered. When not specified, we assume all of them are ordered
pair	Whether we use a paired-choice conjoint design
pair_id	Unique identifiers for pairs in the paired-choice conjoint design (optional)
cross_int	Include interactions across profiles. Default is FALSE.

cluster_id	Unique identifiers for computing cluster standard errors (optional).
target_dist	Target profile distributions to be used. This argument should be 'list'
target_type	Types of target profile distributions. 'marginal' or 'target_data'. See Examples for details.
difference	Whether we compute the differences between the multiple pAMCEs. Default is FALSE.
cv_type	(optimal only when 'reg = TRUE') 'cv.1Std' (stronger regularization; default) or 'cv.min' (weaker regularization).
nfolds	Number of cross validation folds. Default is 5.
boot	The number of bootstrap samples.
seed	Seed for bootstrap.
numCores	Number of cores to be used for parallel computing. If not specified, detect the number of available cores internally.

Value

model_pAMCE returns an object of pAMCE class.

- AMCE: Estimates of the pAMCE for all factors.
- boot_AMCE: Estimates of the pAMCE for all factors in each bootstrap sample.
- boot_coef: Estimates of coefficients for the linear probability model in each bootstrap sample.
- approach: "model_based"
- input: Input into the function.
- ...: Values for internal use.

References

de la Cuesta, Egami, and Imai. (2022). Improving the External Validity of Conjoint Analysis: The Essential Role of Profile Distribution. *Political Analysis*.

Egami and Imai. (2019). Causal Interaction in Factorial Experiments: Application to Conjoint Analysis. *Journal of the American Statistical Association*, Vol.114, No.526 (June), pp. 529–540.

Examples

```
# Small example
target_dist_marginal <- OnoBurden$target_dist_marginal
OnoBurden_data <- OnoBurden$OnoBurden_data
OnoBurden_data_small <- OnoBurden_data[1:300, ]
target_dist_marginal_small <- target_dist_marginal[c("gender", "race")]

# model-based estimation without regularization
out_model_s <-
  model_pAMCE(formula = Y ~ gender + race,
              data = OnoBurden_data_small, reg = FALSE,
              pair_id = OnoBurden_data_small$pair_id,
```

```

cluster_id = OnoBurden_data_small$id,
target_dist = target_dist_marginal_small,
target_type = "marginal")

# model-based estimation with regularization
out_model <-
  model_pAMCE(formula = Y ~ gender + age + family + race + experience + party + pos_security,
              data = OnoBurden_data_small, reg = TRUE,
              pair_id = OnoBurden_data_small$pair_id,
              cluster_id = OnoBurden_data_small$id,
              target_dist = target_dist_marginal,
              target_type = "marginal",
              nfolds = 2, # suggest "nfolds = 5" in practice
              numCores = 1, # when numCores = NULL, it automatically uses all cores.
              boot = 5) # suggest "boot = 500" in practice
summary(out_model, factor_name = c("gender"))

# decompose the difference in the pAMCEs
decompose_pAMCE(out_model, effect_name = c("gender", "Female"))

```

OnoBurden

Dataset from Ono and Burden (2018)

Description

Dataset from Ono and Burden (2018)

Usage

OnoBurden

Format

A list containing the conjoint data, target profile distributions based on (1) marginals, (2) a combination of marginal and partial joint distributions, and (3) the full joint distribution.

plot.pAMCE

Plotting the estimated population AMCEs

Description

Plotting the estimated population AMCEs

Usage

```
## S3 method for class 'pAMCE'
plot(
  x,
  factor_name,
  target_dist_name,
  legend_pos = "topright",
  main = "Estimated population AMCEs",
  xlim,
  mar = 12,
  diagnose = FALSE,
  ...
)
```

Arguments

x	An object of class "pAMCE", a result of a call to 'model_pAMCE' or 'design_pAMCE'
factor_name	Factors for which the function visualizes the pAMCEs
target_dist_name	Names of the target profile distributions to be used
legend_pos	Position of the legend. Default is 'topright'
main	Title of the plot
xlim	Range for the x-axis
mar	Space on the left side of the plot. Default is 12
diagnose	Whether we plot diagnostic checks recommended in de la Cuesta, Egami, and Imai (2019). Default is FALSE
...	Other graphical parameters

Value

No return value, called for side effects

plot_decompose	<i>Plot decomposition of the difference between pAMCEs</i>
----------------	--

Description

See examples in 'model_pAMCE'.

Usage

```
plot_decompose(x, effect_name, target_diff, mar = 12)
```


Arguments

x	An object of class "pAMCE", a result of a call to 'model_pAMCE'.
effect_name	Effect for which the function decomposes the difference in the pAMCEs. The first element should be a factor name and the second element should be a level name.
target_diff	Two target profile distributions for which the function compares the pAMCEs. If missing, the function compares the first target profile distribution and the in-sample profile distribution.
mar	Space on the left side of the plot. Default is 12.

Value

No return value, called for side effects

plot_diagnose	<i>Plotting diagnostic checks</i>
---------------	-----------------------------------

Description

Plotting diagnostic checks

Usage

```
plot_diagnose(
  x,
  factor_name,
  legend_pos = "topright",
  target_dist_name,
  xlim,
  mar
)
```

Arguments

x	An object of class "pAMCE", a result of a call to 'model_pAMCE.'
factor_name	A factor for which the function diagnoses modeling assumptions.
legend_pos	Position of the legend. Default is 'topright'.
target_dist_name	Names of the target profile distributions to be used.
xlim	Range for the x-axis.
mar	Space on the left side of the plot. Default is 12.

Value

No return value, called for side effects

summary.pAMCE	<i>Summarizing the estimated population AMCEs</i>
---------------	---

Description

Summarizing the estimated population AMCEs

Usage

```
## S3 method for class 'pAMCE'
summary(object, factor_name, target_dist_name, sample = FALSE, ...)
```

Arguments

object	An object of class "pAMCE", a result of a call to 'model_pAMCE' or 'design_pAMCE'
factor_name	Factors for which the function visualizes the pAMCEs
target_dist_name	Names of the target profile distributions to be used
sample	Whether to print the sample AMCEs, which is estimated based on the profile distribution used for randomization
...	Other parameters

Value

No return value, called for side effects

weights_pAMCE	<i>Computing weights for estimating the population AMCE using a design-based approach</i>
---------------	---

Description

Computing weights for estimating the population AMCE using a design-based approach

Usage

```
weights_pAMCE(
  formula,
  factor_name,
  data,
  pair,
  pair_id,
  cross_int,
```

```
target_dist,  
target_type,  
partial_joint_name  
)
```

Arguments

formula	Formula
factor_name	A factor for which the function computes weights
data	Data
pair	Whether we use a paired-choice conjoint design
pair_id	Unique identifiers for pairs in the paired-choice conjoint design (optional)
cross_int	Include interactions across profiles. Default is FALSE
target_dist	Target profile distributions to be used. This argument should be 'list'
target_type	Types of target profile distributions. 'marginal', 'partial_joint' or 'target_data'. See Examples for details
partial_joint_name	Names of factors representing partial joint distributions. See Examples for details.

Value

No return value, called for side effects

Index

* **dataset**

OnoBurden, [7](#)

decompose_pAMCE, [2](#)

design_pAMCE, [2](#)

diagnose_pAMCE, [4](#)

model_pAMCE, [5](#)

OnoBurden, [7](#)

plot.pAMCE, [7](#)

plot_decompose, [8](#)

plot_diagnose, [9](#)

summary.pAMCE, [10](#)

weights_pAMCE, [10](#)