

Package ‘konfound’

October 17, 2024

Type Package

Title Quantify the Robustness of Causal Inferences

Version 1.0.2

Description Statistical methods that quantify the conditions necessary to alter inferences, also known as sensitivity analysis, are becoming increasingly important to a variety of quantitative sciences. A series of recent works, including Frank (2000) [<doi:10.1177/0049124100029002001 >](https://doi.org/10.1177/0049124100029002001) and Frank et al. (2013) [<doi:10.3102/0162373713493129 >](https://doi.org/10.3102/0162373713493129) extend previous sensitivity analyses by considering the characteristics of omitted variables or unobserved cases that would change an inference if such variables or cases were observed. These analyses generate statements such as “an omitted variable would have to be correlated at xx with the predictor of interest (e.g., the treatment) and outcome to invalidate an inference of a treatment effect”. Or “one would have to replace pp percent of the observed data with nor which the treatment had no effect to invalidate the inference”.

We implement these recent developments of sensitivity analysis and provide modules to calculate these two robustness indices and generate such statements in R. In particular, the functions `konfound()`, `pkonfound()` and `mkonfound()` allow users to calculate the robustness of inferences for a user's own model, a single published study and multiple studies respectively.

License MIT + file LICENSE

URL <https://github.com/konfound-project/konfound>,
<https://konfound-it.org/konfound/>

BugReports <https://github.com/konfound-project/konfound/issues>

Depends R ($\geq 3.5.0$)

Imports broom, broom.mixed, crayon, dplyr, ggplot2, lavaan, purrr, rlang, tidyr, lme4 ($\geq 1.1-35.1$), tibble, ggrepel, pbkrtest

Suggests covr, devtools, forcats, knitr, rmarkdown, mice, roxygen2, testthat, Matrix ($\geq 1.6-2$)

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.3.1

NeedsCompilation no

Author Joshua M Rosenberg [aut, cre],

Ran Xu [ctb],

Qinyun Lin [ctb],

Spiro Maroulis [ctb],

Sarah Narvaiz [ctb],

Kenneth A Frank [ctb],

Wei Wang [ctb],

Yunhe Cui [ctb],

Gaofei Zhang [ctb],

Xuesen Cheng [ctb],

JiHoon Choi [ctb],

Guan Saw [ctb]

Maintainer Joshua M Rosenberg <jmrosen48@gmail.com>

Repository CRAN

Date/Publication 2024-10-17 16:10:02 UTC

Contents

binary_dummy_data	3
cal_delta_star	3
cal_rxy	4
cal_rxz	5
cal_ryz	5
chisq_p	6
concord1	6
get_kr_df	7
konfound	7
konfound_glm	9
konfound_glm_dichotomous	9
konfound_lm	10
konfound_lmer	11
mkonfound	12
mkonfound_ex	13
output_df	13
output_print	14
output_table	16
pkonfound	16
plot_correlation	20
plot_threshold	20
tkonfound	21

<i>binary_dummy_data</i>	3
tkonfound_fig	22
verify_reg_Gzcv	23
verify_reg_uncond	23
zzz	24
Index	25

<code>binary_dummy_data</code>	<i>Binary dummy data</i>
--------------------------------	--------------------------

Description

This data is made-up data for use in examples.

Format

A data.frame with 107 rows and 3 variables.

<code>cal_delta_star</code>	<i>Calculate delta star for sensitivity analysis</i>
-----------------------------	--

Description

Calculate delta star for sensitivity analysis

Usage

```
cal_delta_star(
  FR2max,
  R2,
  R2_uncond,
  est_eff,
  eff_thr,
  var_x,
  var_y,
  est_uncond,
  rxz,
  n_obs
)
```

Arguments

FR2max	maximum R2
R2	current R2
R2_uncond	unconditional R2
est_eff	estimated effect
eff_thr	effect threshold
var_x	variance of X
var_y	variance of Y
est_uncond	unconditional estimate
rxz	correlation coefficient between X and Z
n_obs	number of observations

Value

delta star value

cal_rxy	<i>Calculate rxy based on ryxGz, rxz, and ryz</i>
---------	---

Description

Calculate rxy based on ryxGz, rxz, and ryz

Usage

```
cal_rxy(ryxGz, rxz, ryz)
```

Arguments

ryxGz	correlation coefficient between Y and X given Z
rxz	correlation coefficient between X and Z
ryz	correlation coefficient between Y and Z

Value

rxxy value

cal_rxz	<i>Calculate R2xz based on variances and standard error</i>
---------	---

Description

Calculate R2xz based on variances and standard error

Usage

```
cal_rxz(var_x, var_y, R2, df, std_err)
```

Arguments

var_x	variance of X
var_y	variance of Y
R2	coefficient of determination
df	degrees of freedom
std_err	standard error

Value

R2xz value

cal_ryz	<i>Calculate R2yz based on ryxGz and R2</i>
---------	---

Description

Calculate R2yz based on ryxGz and R2

Usage

```
cal_ryz(ryxGz, R2)
```

Arguments

ryxGz	correlation coefficient between Y and X given Z
R2	coefficient of determination

Value

R2yz value

chisq_p	<i>Perform a Chi-Square Test</i>
---------	----------------------------------

Description

'chisq_p' calculates the p-value for a chi-square test given a contingency table.

Usage

```
chisq_p(a, b, c, d)
```

Arguments

a	Frequency count for row 1, column 1.
b	Frequency count for row 1, column 2.
c	Frequency count for row 2, column 1.
d	Frequency count for row 2, column 2.

Value

P-value from the chi-square test.

concord1	<i>Concord1 data</i>
----------	----------------------

Description

This data is from Hamilton (1983)

Format

A data.frame with 496 rows and 10 variables.

References

Hamilton, Lawrence C. 1983. Saving water: A causal model of household conservation. *Sociological Perspectives* 26(4):355-374.

get_kr_df	<i>Extract Degrees of Freedom for Fixed Effects in a Linear Mixed-Effects Model</i>
-----------	---

Description

Extract Degrees of Freedom for Fixed Effects in a Linear Mixed-Effects Model

Usage

```
get_kr_df(model_object)
```

Arguments

model_object The mixed-effects model object produced by lme4::lmer.

Value

A vector containing degrees of freedom for the fixed effects in the model.

konfound	<i>Konfound Analysis for Various Model Types</i>
----------	--

Description

Performs sensitivity analysis on fitted models including linear models ('lm'), generalized linear models ('glm'), and linear mixed-effects models ('lmerMod'). It calculates the amount of bias required to invalidate or sustain an inference, and the impact of an omitted variable necessary to affect the inference.

Usage

```
konfound(  
  model_object,  
  tested_variable,  
  alpha = 0.05,  
  tails = 2,  
  index = "RIR",  
  to_return = "print",  
  two_by_two = FALSE,  
  n_treat = NULL,  
  switch_trm = TRUE,  
  replace = "control"  
)
```

Arguments

<code>model_object</code>	A model object produced by 'lm', 'glm', or 'lme4::lmer'.
<code>tested_variable</code>	Variable associated with the coefficient to be tested.
<code>alpha</code>	Significance level for hypothesis testing.
<code>tails</code>	Number of tails for the test (1 or 2).
<code>index</code>	Type of sensitivity analysis ('RIR' by default).
<code>to_return</code>	Type of output to return ('print', 'raw_output', 'table').
<code>two_by_two</code>	Boolean; if 'TRUE', uses a 2x2 table approach for 'glm' dichotomous variables.
<code>n_treat</code>	Number of treatment cases (used only if 'two_by_two' is 'TRUE').
<code>switch_trm</code>	Boolean; switch treatment and control in the analysis.
<code>replace</code>	Replacement method for treatment cases ('control' by default).

Value

Depending on 'to_return', prints the result, returns a raw output, or a summary table.

Examples

```
# using lm() for linear models
m1 <- lm(mpg ~ wt + hp, data = mtcars)
konfound(m1, wt)
konfound(m1, wt, to_return = "table")

# using glm() for non-linear models
if (requireNamespace("forcats")) {
  d <- forcats::gss_cat

  d$married <- ifelse(d$marital == "Married", 1, 0)

  m2 <- glm(married ~ age, data = d, family = binomial(link = "logit"))
  konfound(m2, age)
}

# using lme4 for mixed effects (or multi-level) models
if (requireNamespace("lme4")) {
  library(lme4)
  m3 <- fm1 <- lme4::lmer(Reaction ~ Days + (1 | Subject), sleepstudy)
  konfound(m3, Days)
}

m4 <- glm(outcome ~ condition, data = binary_dummy_data, family = binomial(link = "logit"))
konfound(m4, condition, two_by_two = TRUE, n_treat = 55)
```

`konfound_glm`*Konfound Analysis for Generalized Linear Models*

Description

This function performs konfound analysis on a generalized linear model object. It uses 'broom' to tidy model outputs and calculates the sensitivity of inferences. It supports analysis for a single variable or multiple variables.

Usage

```
konfound_glm(  
  model_object,  
  tested_variable_string,  
  alpha,  
  tails,  
  index = "RIR",  
  to_return  
)
```

Arguments

<code>model_object</code>	The model object produced by glm.
<code>tested_variable_string</code>	The name of the variable being tested.
<code>alpha</code>	Significance level for hypothesis testing.
<code>tails</code>	Number of tails for the test (1 or 2).
<code>index</code>	Type of sensitivity analysis ('RIR' by default).
<code>to_return</code>	The type of output to return.

Value

The results of the konfound analysis for the specified variable(s).

`konfound_glm_dichotomous`*Konfound Analysis for Generalized Linear Models with Dichotomous Outcomes*

Description

This function performs konfound analysis on a generalized linear model object with a dichotomous outcome. It uses 'broom' to tidy model outputs and calculates the sensitivity of inferences.

Usage

```
konfound_glm_dichotomous(
  model_object,
  tested_variable_string,
  alpha,
  tails,
  to_return,
  n_treat,
  switch_trm,
  replace
)
```

Arguments

model_object	The model object produced by glm.
tested_variable_string	The name of the variable being tested.
alpha	Significance level for hypothesis testing.
tails	Number of tails for the test (1 or 2).
to_return	The type of output to return.
n_treat	Number of treatment cases.
switch_trm	Term to switch for sensitivity analysis.
replace	Boolean indicating whether to replace cases or not.

Value

The results of the konfound analysis.

 konfound_lm

Konfound Analysis for Linear Models

Description

This function performs konfound analysis on a linear model object produced by lm. It calculates the sensitivity of inferences for coefficients in the model. It supports analysis for a single variable or multiple variables.

Usage

```
konfound_lm(
  model_object,
  tested_variable_string,
  alpha,
  tails,
  index,
  to_return
)
```

Arguments

model_object	The linear model object produced by lm.
tested_variable_string	The name of the variable being tested.
alpha	Significance level for hypothesis testing.
tails	Number of tails for the test (1 or 2).
index	Type of sensitivity analysis ('RIR' by default).
to_return	The type of output to return.

Value

The results of the konfound analysis for the specified variable(s).

konfound_lmer	<i>Konfound Analysis for Linear Mixed-Effects Models</i>
---------------	--

Description

This function performs konfound analysis on a linear mixed-effects model object produced by lme4::lmer. It calculates the sensitivity of inferences for fixed effects in the model. It supports analysis for a single variable or multiple variables.

Usage

```
konfound_lmer(
  model_object,
  tested_variable_string,
  test_all,
  alpha,
  tails,
  index,
  to_return
)
```

Arguments

model_object	The mixed-effects model object produced by lme4::lmer.
tested_variable_string	The name of the fixed effect being tested.
test_all	Boolean indicating whether to test all fixed effects or not.
alpha	Significance level for hypothesis testing.
tails	Number of tails for the test (1 or 2).
index	Type of sensitivity analysis ('RIR' by default).
to_return	The type of output to return.

Value

The results of the konfound analysis for the specified fixed effect(s).

mkonfound

Meta-Analysis and Sensitivity Analysis for Multiple Studies

Description

Performs sensitivity analysis for multiple models, where parameters are stored in a data frame. It calculates the amount of bias required to invalidate or sustain an inference for each case in the data frame.

Usage

```
mkonfound(d, t, df, alpha = 0.05, tails = 2, return_plot = FALSE)
```

Arguments

<code>d</code>	A data frame or tibble containing t-statistics and associated degrees of freedom.
<code>t</code>	Column name or vector of t-statistics.
<code>df</code>	Column name or vector of degrees of freedom associated with t-statistics.
<code>alpha</code>	Significance level for hypothesis testing.
<code>tails</code>	Number of tails for the test (1 or 2).
<code>return_plot</code>	Whether to return a plot of the percent bias (default is 'FALSE').

Value

Depending on 'return_plot', either returns a data frame with analysis results or a plot.

Examples

```
## Not run:  
mkonfound_ex  
str(d)  
mkonfound(mkonfound_ex, t, df)  
  
## End(Not run)
```

`mkonfound_ex`*Example data for the mkonfound function*

Description

A dataset containing `t` and `df` values from example studies from Educational Evaluation and Policy Analysis (as detailed in Frank et al., 2013): <https://drive.google.com/file/d/1aGhxGjvMvEPVAgOA8rrxvA97uUO5TTMe/view>

Usage`mkonfound_ex`**Format**

A data frame with 30 rows and 2 variables:

t t value

df degrees of freedom associated with the t value ...

Source

<https://drive.google.com/file/d/1aGhxGjvMvEPVAgOA8rrxvA97uUO5TTMe/view>

`output_df`*Output data frame based on model estimates and thresholds*

Description

Output data frame based on model estimates and thresholds

Usage

```
output_df(  
  est_eff,  
  beta_threshold,  
  unstd_beta,  
  bias = NULL,  
  sustain = NULL,  
  recase,  
  obs_r,  
  critical_r,  
  r_con,  
  itcv,  
  non_linear  
)
```

Arguments

est_eff	estimated effect
beta_threshold	threshold for beta
unstd_beta	unstandardized beta value
bias	bias to change inference
sustain	sustain to change inference
recase	number of cases to replace null
obs_r	observed correlation
critical_r	critical correlation
r_con	correlation for omitted variable
itcv	inferential threshold for confounding variable
non_linear	flag for non-linear models

Value

data frame with model information

output_print	<i>Output printed text with formatting</i>
--------------	--

Description

This function outputs printed text for various indices such as RIR (Robustness of Inference to Replacement) and IT (Impact Threshold for a Confounding Variable) with specific formatting like bold, underline, and italic using functions from the crayon package. It handles different scenarios based on the effect difference, beta threshold, and other parameters, providing formatted output for each case.

Usage

```
output_print(
  n_covariates,
  est_eff,
  beta_threshold,
  bias = NULL,
  sustain = NULL,
  nu,
  eff_thr,
  recase,
  obs_r,
  critical_r,
  r_con,
  itcv,
```

```

    alpha,
    index,
    far_bound,
    sdx = NA,
    sdy = NA,
    R2 = NA,
    rxcv = NA,
    rycv = NA
  )

```

Arguments

n_covariates	number of covariates.
est_eff	The estimated effect.
beta_threshold	The threshold value of beta, used for statistical significance determination.
bias	The percentage of the estimate that could be due to bias (optional).
sustain	The percentage of the estimate necessary to sustain an inference (optional).
nu	The hypothesized effect size used in replacement analysis.
eff_thr	Threshold for estimated effect.
recase	The number of cases that need to be replaced to change the inference.
obs_r	The observed correlation coefficient in the data.
critical_r	The critical correlation coefficient for statistical significance.
r_con	The correlation coefficient of an omitted variable with both the outcome and the predictor.
itcv	The impact threshold for a confounding variable.
alpha	The level of statistical significance.
index	A character string indicating the index for which the output is generated ('RIR' or 'IT').
far_bound	Indicator whether the threshold is towards the other side of nu or 0, by default is zero (same side), alternative is one (the other side).
sdx	Standard deviation of x.
sdy	Standard deviation of y.
R2	the unadjusted, original R2 in the observed function.
rxcv	the correlation between x and CV.
rycv	the correlation between y and CV.

output_table	<i>Output a Tidy Table from a Model Object</i>
--------------	--

Description

This function takes a model object and the tested variable, tidies the model output using ‘broom::tidy’, calculates the impact threshold for confounding variables (ITCV) and impact for each covariate, and returns a rounded, tidy table of model outputs.

Usage

```
output_table(model_object, tested_variable)
```

Arguments

`model_object` A model object from which to generate the output.
`tested_variable` The variable being tested in the model.

Value

A tidy data frame containing model outputs, ITCV, and impacts for covariates.

pkonfound	<i>Perform sensitivity analysis for published studies</i>
-----------	---

Description

For published studies, this command calculates (1) how much bias there must be in an estimate to invalidate/sustain an inference; (2) the impact of an omitted variable necessary to invalidate/sustain an inference for a regression coefficient.

Usage

```
pkonfound(
  est_eff,
  std_err,
  n_obs,
  n_covariates = 1,
  alpha = 0.05,
  tails = 2,
  index = "RIR",
  nu = 0,
  n_treat = NULL,
  switch_trm = TRUE,
```

```

  model_type = "ols",
  a = NULL,
  b = NULL,
  c = NULL,
  d = NULL,
  two_by_two_table = NULL,
  test = "fisher",
  replace = "control",
  sdx = NA,
  sdy = NA,
  R2 = NA,
  far_bound = 0,
  eff_thr = NA,
  FR2max = 0,
  FR2max_multiplier = 1.3,
  to_return = "print"
)

```

Arguments

<code>est_eff</code>	the estimated effect (such as an unstandardized beta coefficient or a group mean difference)
<code>std_err</code>	the standard error of the estimate of the unstandardized regression coefficient
<code>n_obs</code>	the number of observations in the sample
<code>n_covariates</code>	the number of covariates in the regression model
<code>alpha</code>	probability of rejecting the null hypothesis (defaults to 0.05)
<code>tails</code>	integer whether hypothesis testing is one-tailed (1) or two-tailed (2; defaults to 2)
<code>index</code>	whether output is RIR or IT (impact threshold); defaults to "RIR"
<code>nu</code>	what hypothesis to be tested; defaults to testing whether <code>est_eff</code> is significantly different from 0
<code>n_treat</code>	the number of cases associated with the treatment condition; applicable only when <code>model_type = "logistic"</code>
<code>switch_trm</code>	whether to switch the treatment and control cases; defaults to FALSE; applicable only when <code>model_type = "logistic"</code>
<code>model_type</code>	the type of model being estimated; defaults to "ols" for a linear regression model; the other option is "logistic"
<code>a</code>	cell is the number of cases in the control group showing unsuccessful results
<code>b</code>	cell is the number of cases in the control group showing successful results
<code>c</code>	cell is the number of cases in the treatment group showing unsuccessful results
<code>d</code>	cell is the number of cases in the treatment group showing successful results
<code>two_by_two_table</code>	table that is a matrix or can be coerced to one (data.frame, tibble, tribble) from which the a, b, c, and d arguments can be extracted

<code>test</code>	whether using Fisher's Exact Test or A chi-square test; defaults to Fisher's Exact Test
<code>replace</code>	whether using entire sample or the control group to calculate the base rate; default is control
<code>sdx</code>	the standard deviation of X
<code>sdY</code>	the standard deviation of Y
<code>R2</code>	the unadjusted, original R2 in the observed function
<code>far_bound</code>	whether the estimated effect is moved to the boundary closer (default 0) or further away (1);
<code>eff_thr</code>	for RIR: unstandardized coefficient threshold to change an inference; for IT: correlation defining the threshold for inference
<code>FR2max</code>	the largest R2, or R2max, in the final model with unobserved confounder
<code>FR2max_multiplier</code>	the multiplier of R2 to get R2max, default is set to 1.3
<code>to_return</code>	whether to return a data.frame (by specifying this argument to equal "raw_output" for use in other analyses) or a plot ("plot"); default is to print ("print") the output to the console; can specify a vector of output to return

Value

pkonfound prints the bias and the number of cases that would have to be replaced with cases for which there is no effect to nullify the inference. If `to_return = "raw_output,"` a list will be given with the following components:

obs_r correlation between predictor of interest (X) and outcome (Y) in the sample data.

act_r correlation between predictor of interest (X) and outcome (Y) from the sample regression based on the t-ratio accounting for non-zero null hypothesis.

critical_r critical correlation value at which the inference would be nullified (e.g., associated with $p=.05$).

r_final final correlation value given CV. Should be equal to `critical_r`.

rxcv correlation between predictor of interest (X) and CV necessary to nullify the inference for smallest impact.

rycv correlation between outcome (Y) and CV necessary to nullify the inference for smallest impact.

rxcvGz correlation between predictor of interest and CV necessary to nullify the inference for smallest impact conditioning on all observed covariates (given z).

rycvGz correlation between outcome and CV necessary to nullify the inference for smallest impact conditioning on all observed covariates (given z).

itcvGz ITCV conditioning on the observed covariates.

itcv Unconditional ITCV.

r2xz R2 using all observed covariates to explain the predictor of interest (X).

r2yz R2 using all observed covariates to explain the outcome (Y).

delta_star delta calculated using Oster's unrestricted estimator.

delta_star_restricted delta calculated using Oster's restricted estimator.

delta_exact correlation-based delta.

delta_pctbias percent of bias when comparing delta_star with delta_exact.

cor_oster correlation matrix implied by delta_star.

cor_exact correlation matrix implied by delta_exact.

beta_threshold threshold value for estimated effect.

beta_threshold_verify estimated effect given RIR. Should be equal to beta_threshold.

perc_bias_to_change percent bias to change the inference.

RIR_primary Robustness of Inference to Replacement (RIR).

RIR_supplemental RIR for an extra row or column that is needed to nullify the inference.

RIR_perc RIR as % of total sample (for linear regression) or as % of data points in the cell where replacement takes place (for logistic and 2 by 2 table).

fragility_primary Fragility. the number of switches (e.g., treatment success to treatment failure) to nullify the inference.

fragility_supplemental Fragility for an extra row or column that is needed to nullify the inference.

starting_table Observed 2 by 2 table before replacement and switching. Implied table for logistic regression.

final_table The 2 by 2 table after replacement and switching.

user_SE user entered standard error. Only applicable for logistic regression.

needtworows whether double row switches are needed.

analysis_SE the standard error used to generate a plausible 2 by 2 table. Only applicable for logistic regression.

Fig_ITCV figure for ITCV.

Fig_RIR figure for RIR.

Examples

```
# using pkonfound for linear models
pkonfound(2, .4, 100, 3)
pkonfound(-2.2, .65, 200, 3)
pkonfound(.5, 3, 200, 3)
pkonfound(-0.2, 0.103, 20888, 3, n_treat = 17888, model_type = "logistic")

pkonfound(2, .4, 100, 3, to_return = "thresh_plot")
pkonfound(2, .4, 100, 3, to_return = "corr_plot")

# using pkonfound for a 2x2 table
pkonfound(a = 35, b = 17, c = 17, d = 38)
pkonfound(a = 35, b = 17, c = 17, d = 38, alpha = 0.01)
pkonfound(a = 35, b = 17, c = 17, d = 38, alpha = 0.01, switch_trm = FALSE)
pkonfound(a = 35, b = 17, c = 17, d = 38, test = "chisq")

# use pkonfound to calculate delta* and delta_exact
pkonfound(est_eff = .4, std_err = .1, n_obs = 290, sdx = 2, sdy = 6, R2 = .7,
```

```

  eff_thr = 0, FR2max = .8, index = "COP", to_return = "raw_output")
# use pkonfound to calculate rxcv and rycv when preserving standard error
pkonfound(est_eff = .5, std_err = .056, n_obs = 6174, eff_thr = .1,
  sd_x = 0.22, sd_y = 1, R2 = .3, index = "PSE", to_return = "raw_output")

```

plot_correlation *Plot Correlation Diagram*

Description

This function creates a plot to illustrate the correlation between different variables, specifically focusing on the confounding variable, predictor of interest, and outcome. It uses ggplot2 for graphical representation.

Usage

```
plot_correlation(r_con, obs_r, critical_r)
```

Arguments

r_con Correlation coefficient related to the confounding variable.
 obs_r Observed correlation coefficient.
 critical_r Critical correlation coefficient for decision-making.

Value

A ggplot object representing the correlation diagram.

plot_threshold *Plot Effect Threshold Diagram*

Description

This function creates a plot to illustrate the threshold of an effect estimate in relation to a specified beta threshold. It uses ggplot2 for graphical representation.

Usage

```
plot_threshold(beta_threshold, est_eff)
```

Arguments

beta_threshold The threshold value for the effect.
 est_eff The estimated effect size.

Value

A ggplot object representing the effect threshold diagram.

tkonfound

Perform Sensitivity Analysis on 2x2 Tables

Description

This function performs a sensitivity analysis on a 2x2 contingency table. It calculates the number of cases that need to be replaced to invalidate or sustain the statistical inference. The function also allows switching between treatment success and failure or control success and failure based on the provided parameters.

Usage

```
tkonfound(
  a,
  b,
  c,
  d,
  alpha = 0.05,
  switch_trm = TRUE,
  test = "fisher",
  replace = "control",
  to_return = to_return
)
```

Arguments

a	Number of unsuccessful cases in the control group.
b	Number of successful cases in the control group.
c	Number of unsuccessful cases in the treatment group.
d	Number of successful cases in the treatment group.
alpha	Significance level for the statistical test, default is 0.05.
switch_trm	Boolean indicating whether to switch treatment row cells, default is TRUE.
test	Type of statistical test to use, either "fisher" (default) or "chisq".
replace	Indicates whether to use the entire sample or the control group for base rate calculation, default is "control".
to_return	Type of output to return, either "raw_output" or "print".

Value

Returns detailed information about the sensitivity analysis, including the number of cases to be replaced (RIR), user-entered table, transfer table, and conclusions.

`tkonfound_fig`*Draw Figures for Change in Effect Size in 2x2 Tables*

Description

This function generates plots illustrating how the change in effect size is influenced by switching or replacing outcomes in a 2x2 table. It produces two plots: one showing all possibilities (switching) and another zoomed in the area for positive RIR (Relative Impact Ratio).

Usage

```
tkonfound_fig(  
  a,  
  b,  
  c,  
  d,  
  thr_p = 0.05,  
  switch_trm = TRUE,  
  test = "fisher",  
  replace = "control"  
)
```

Arguments

<code>a</code>	Number of cases in the control group with unsuccessful outcomes.
<code>b</code>	Number of cases in the control group with successful outcomes.
<code>c</code>	Number of cases in the treatment group with unsuccessful outcomes.
<code>d</code>	Number of cases in the treatment group with successful outcomes.
<code>thr_p</code>	P-value threshold for statistical significance, default is 0.05.
<code>switch_trm</code>	Whether to switch the two cells in the treatment or control row, default is TRUE (treatment row).
<code>test</code>	Type of statistical test used, either "Fisher's Exact Test" (default) or "Chi-square test".
<code>replace</code>	Indicates whether to use the entire sample or just the control group for calculating the base rate, default is "control".

Value

Returns two plots showing the effect of hypothetical case switches on the effect size in a 2x2 table.

Examples

```
tkonfound_fig(14, 17, 6, 25, test = "chisq")
```

verify_reg_Gzcv	<i>Verify regression model with control variable Z</i>
-----------------	--

Description

Verify regression model with control variable Z

Usage

```
verify_reg_Gzcv(n_obs, sdx, sdy, sdz, sdcv, rxy, rxz, rzy, rcvy, rcvx, rcvz)
```

Arguments

n_obs	number of observations
sdx	standard deviation of X
sdv	standard deviation of Y
sdz	standard deviation of Z
sdcv	sd between C and V
rxy	correlation coefficient between X and Y
rxz	correlation coefficient between X and Z
rzy	correlation coefficient between Z and Y
rcvy	correlation coefficient between V and Y
rcvx	correlation coefficient between V and X
rcvz	correlation coefficient between V and Z

Value

list of model parameters

verify_reg_uncond	<i>Verify unconditional regression model</i>
-------------------	--

Description

Verify unconditional regression model

Usage

```
verify_reg_uncond(n_obs, sdx, sdy, rxy)
```

Arguments

n_obs	number of observations
sdx	standard deviation of X
sdy	standard deviation of Y
rxy	correlation coefficient between X and Y

Value

list of model parameters

zzz

Package Initialization Functions and Utilities

Description

These functions are used for initializing the package environment and providing utility functions for the package.

Index

* datasets

 mkonfound_ex, 13

binary_dummy_data, 3

cal_delta_star, 3

cal_rxy, 4

cal_rxz, 5

cal_ryz, 5

chisq_p, 6

concord1, 6

get_kr_df, 7

konfound, 7

konfound_glm, 9

konfound_glm_dichotomous, 9

konfound_lm, 10

konfound_lmer, 11

mkonfound, 12

mkonfound_ex, 13

output_df, 13

output_print, 14

output_table, 16

pkonfound, 16

plot_correlation, 20

plot_threshold, 20

tkonfound, 21

tkonfound_fig, 22

verify_reg_Gzcv, 23

verify_reg_uncond, 23

zzz, 24